

DAA/LANGLEY

OLD DOMINION UNIVERSITY RESEARCH FOUNDATION

DEPARTMENT OF MATHEMATICAL SCIENCES  
SCHOOL OF SCIENCES AND HEALTH PROFESSIONS  
OLD DOMINION UNIVERSITY  
NORFOLK, VIRGINIA 23508

SUMMARY OF MATHEMATICAL MODELS  
FOR A CONVENTIONAL AND VERTICAL  
JUNCTION PHOTOCONVERTER

By


John H. Heinbockel, Principal Investigator

Progress Report  
For the period March 1, 1986 to June 30, 1986

Prepared for the  
National Aeronautics and Space Administration  
Langley Research Center  
Hampton, Virginia 23665

Under  
Research Grant NAG-1-148  
Gilbert H. Walker, Technical Monitor  
SSD-High Energy Science Branch

June 1986



(NASA-CR-177144) SUMMARY OF MATHEMATICAL  
MODELS FOR A CONVENTIONAL AND VERTICAL  
JUNCTION PHOTOCONVERTER Progress Report, 1  
Mar. - 30 Jun. 1986 (Old Dominion Univ.)  
104 p

N86-31099

Unclas

CSCL 10A G3/44 43379

DEPARTMENT OF MATHEMATICAL SCIENCES  
SCHOOL OF SCIENCES AND HEALTH PROFESSIONS  
OLD DOMINION UNIVERSITY  
NORFOLK, VIRGINIA 23508

SUMMARY OF MATHEMATICAL MODELS  
FOR A CONVENTIONAL AND VERTICAL  
JUNCTION PHOTOCONVERTER

By


John H. Heinbockel, Principal Investigator

Progress Report  
For the period March 1, 1986 to June 30, 1986

Prepared for the  
National Aeronautics and Space Administration  
Langley Research Center  
Hampton, Virginia 23665

Under  
Research Grant NAG-1-148  
Gilbert H. Walker, Technical Monitor  
SSD-High Energy Science Branch

Submitted by the  
Old Dominion University Research Foundation  
P. O. Box 6369  
Norfolk, Virginia 23508



June 1986

## TABLE OF CONTENTS

	<u>PAGE</u>
SYMBOLS AND UNITS OF MEASUREMENTS.....	iv
1. ONE-DIMENSIONAL CONVENTIONAL PHOTOCONVERTER.....	1
2. ONE-DIMENSIONAL VERTICAL JUNCTION PHOTOCONVERTER MODEL.....	7
3. THREE-DIMENSIONAL CONVENTIONAL PHOTOCONVERTER.....	10
Dark Currents.....	24
4. THREE-DIMENSIONAL VERTICAL JUNCTION SOLAR CELL.....	27
REFERENCES.....	31
APPENDIX A: BASIC COMPUTER PROGRAM FOR ONE-DIMENSIONAL CONVENTIONAL PHOTOCONVERTER.....	A-1
APPENDIX B: BASIC COMPUTER PROGRAM FOR ONE-DIMENSIONAL VERTICAL JUNCTION PHOTOCONVERTER.....	B-1
APPENDIX C: PROGRAM "SC3D" FOR SOLAR CELL 3-DIMENSIONAL.....	C-1
APPENDIX D: "VSC3D" FOR VERTICAL JUNCTION SOLAR CELL 3-DIMENSIONAL.....	D-1

## LIST OF FIGURES

<u>FIGURE</u>	<u>PAGE</u>
1 Device geometry for conventional photoconverter.....	2
2 Equivalent circuit for solar cell.....	6
3 Vertical junction photoconverter geometry.....	8
4 Geometry for three dimensional model of photoconverter.....	11
5 Graphical scheme for determining eigenvalues.....	18
A1 Representative output from the program "CONVEN" illustrating spectral response and current voltage relationship for conventional photoconverter.....	A-10
B1 Representative output from the program "VJSCP" illustrating spectral response and current-voltage relationship for vertical junction photoconverter.....	B-12

# TABLE OF CONTENTS - Concluded

## LIST OF FIGURES - Concluded

<u>FIGURE</u>		<u>PAGE</u>
C1	Representative output from program "SC3D" illustrating the spectral response, the current-voltage relation and contour plot of current density in the planes $Z=Z_j$ and $Z=Z_j+W$ .....	C-20
D1	Representative output from the program "VSC3D" illustrating the spectral response, the current-voltage relation and contour plots of the current density in the planes $Z=Z_j$ and $Z=Z_j+W$ .....	D-21

## SYMBOLS AND UNITS OF MEASUREMENTS

$g(x)$	generation rate [photons/cm <sup>3</sup> s]
$\phi_0$	incident photons [cm <sup>-2</sup> s <sup>-1</sup> ]
$R$	reflection coefficient (dimensionless)
$\alpha$	absorption coefficient [cm <sup>-1</sup> ]
$w$	width of depletion region [cm]
$H$	depth of planar cell [cm]
$H'$	$H-(z_j+W)$ depth parameter [cm]
$x_j, z_j$	junction depths [cm]
$p_n, p_{no}$	density of holes in n-region [cm <sup>-3</sup> ]
$n_p, n_{po}$	density of electrons in p-region [cm <sup>-3</sup> ]
$D_p, D_n$	diffusion coefficient of holes, electrons [cm <sup>2</sup> /s]
$\tau_p, \tau_n$	lifetimes of holes, electrons [s]
$S_p, S_n$	surface recombination velocity of holes, electrons [cm s <sup>-1</sup> ]
$J_p, J_n$	current density for holes, electrons [Amp cm <sup>-2</sup> ]
$L_p, L_n$	diffusion lengths of holes, electrons ( $L^2=D\tau$ ) [cm]
$J_{dr}$	photocurrent density from depletion region [Amp cm <sup>-2</sup> ]
$J_{sc}$	short circuit current density [Amp cm <sup>-2</sup> ]
$J_{inj}$	injection current density [Amp cm <sup>-2</sup> ]
$J_{rec}$	recombination current density [Amp cm <sup>-2</sup> ]
$q$	charge of electron [coulomb]
$N_a, N_d$	doping densities for acceptors, donors [cm <sup>-3</sup> ]
$n_i$	intrinsic carrier density [cm <sup>-3</sup> ]
$V$	voltage [volts]
$V_{bi}$	built in voltage [volts]
$K$	Boltzmann's constant [ev/deg K]

$J$	total current density [Amp cm <sup>-2</sup> ]
$J_0$	dark current density [Amp cm <sup>-2</sup> ]
$R_s$	series resistance [ohms]
$R_{sh}$	shunt resistance [ohms]
$n$	depth parameter [cm]
$x, y$	coordinates for photoconverter reference [cm]
$B$	width of vertical junction cell [cm]
$A$	depth of vertical junction cell [cm]
$x_p, x_n$	coordinates defining space charge region [cm]
$I_{sc}$	total short circuit current [Amp]
$I_p, I_n$	hole, electron current [Amp]
$W_0$	power density of laser [watts cm <sup>-2</sup> ]
$P_{in}, P_{out}$	input, output power [watts]
Eff	efficiency [%]
$a$	half width in x direction [cm]
$b$	half width in y direction [cm]
$\delta(x_0 - x)$	Dirac delta function
$G_1, G_2$	Green's function
$u$	eigenfunctions
$S_0, S_1$	surface recombination velocities [cm s <sup>-1</sup> ]
$U_m, V_m, U_m^*, V_m^*$	Eigenfunctions

# SUMMARY OF MATHEMATICAL MODELS FOR A CONVENTIONAL AND VERTICAL JUNCTION PHOTOCONVERTER

By

John H. Heinbockel\*

## 1. ONE-DIMENSIONAL CONVENTIONAL PHOTOCONVERTER

The first model considered is for a one-dimensional analysis of a conventional photoconverter as described in References 1, 2. The geometry for this conventional n/p photoconverter is illustrated in Figure 1. We assume a generation rate

$$g(x) = \phi_0 (1 - R_e) \alpha \exp(-\alpha x) \quad (1.1)$$

and solve for the minority carriers in the n-region. These minority carriers must satisfy the diffusion equation

$$D_p \frac{d^2}{dx^2} (P_n - P_{n0}) - \frac{(P_n - P_{n0})}{\tau_p} = -g(x) \quad (1.2)$$

subject to the boundary conditions

$$D_p \frac{d}{dx} (P_n - P_{n0}) = S_p (P_n - P_{n0}) \text{ at } x = 0 \quad (1.3)$$

and

$$P_n - P_{n0} = 0 \quad \text{at} \quad x = x_j. \quad (1.4)$$

The solutions of the equations (1.2) (1.3) (1.4) gives the photocurrent density at the junction edge.

$$J_p = -qD_p \frac{d}{dx} (P_n - P_{n0}) \quad \text{at} \quad x = x_j \quad (1.5)$$

---

\*Professor, Department of Mathematical Sciences, Old Dominion University, Norfolk, Virginia 23508.




FIGURE 1. Device geometry for conventional photoconverter



which evaluates to

$$J_p = \frac{q\phi_0 (1-Re) \alpha L_p}{\alpha^2 L_p^2 - 1} (f_1/f_2 - \alpha L_p \text{Exp}(-\alpha X_j)) \quad (1.6)$$

where

$$f_1 = \frac{S_p L_p}{D_p} + \alpha L_p - \exp(-\alpha X_j) f\left(\frac{S_p L_p}{D_p}, 1, \frac{X_j}{D_p}\right) \quad (1.7)$$

$$f_2 = f\left(1, \frac{S_p L_p}{D_p}, X_j/L_p\right) \quad (1.8)$$

and

$$f(a, b, c) = a \cosh(c) + b \sinh(c) \quad (1.9)$$

The diffusion equation for minority carriers in the p-region is given by

$$D_p \frac{d^2}{dx^2} (n_p - n_{po}) - \frac{(n_p - n_{po})}{\tau_n} = -g(x) \quad (1.10)$$

with boundary conditions

$$n_p - n_{po} = 0 \quad \text{at} \quad X = X_j + w \quad (1.11)$$

$$-D_n \frac{d}{dx} (n_p - n_{po}) = S_n (n_p - n_{po}) \quad \text{at} \quad X=H. \quad (1.12)$$

This produces the photocurrent density

$$J_n = q D_n \frac{d}{dx} (n_p - n_{p0}) \quad \text{at} \quad x = x_j + \omega \quad (1.13)$$

which evaluates as

$$J_n = \frac{q\phi_0 (1-R_e)\alpha L_n}{\alpha^2 L_n^2 - 1} \exp(-\alpha(x_j + \omega)) [\alpha L_n - f_3/f_4] \quad (1.14)$$

where

$$f_3 = \left[ \alpha L_n - \frac{S_n L_n}{D_n} \right] \exp[-\alpha(H - x_j - \omega)] + f \left( \frac{S_n L_n}{D_n}, 1, \frac{H - x_j - \omega}{L_n} \right) \quad (1.15)$$

$$f_4 = f \left( 1, \frac{S_n L_n}{D_n}, \frac{H - x_j - \omega}{L_n} \right) \quad (1.16)$$

where  $f$  is defined by equation (1.9).

The photocurrent from the depletion region is given by

$$J_{dr} = q\phi_0 (1-R_e) e^{-\alpha x_j} [1 - e^{-\alpha \omega}] \quad (1.17)$$

and the total current due to the light source is

$$J_{sc} = J_p + J_n + J_{dr} \quad (1.18)$$

For the dark currents we have the injection current  $J_{inj}$  and the recombination current  $J_{rec}$  which are given by

$$J_{inj} = J_0 \left[ \exp \left( \frac{qV}{KT} \right) - 1 \right] \quad (1.19)$$

with

$$J_0 = \frac{qD_p}{L_p} \frac{n_i^2}{N_d} f\left(\frac{S_p L_p}{D_p}, 1, \frac{X_j}{L_p}\right) / f\left(1, \frac{S_p L_p}{D_p}, \frac{X_j}{L_p}\right) \\ + \frac{qD_n}{L_n} \frac{n_i^2}{N_a} f\left(\frac{S_n L_n}{D_n}, 1, \frac{H-X_j-\omega}{L_n}\right) / f\left(1, \frac{S_n L_n}{D_n}, H-X_j-\omega\right) \quad (1.20)$$


and

$$J_{rec} = \frac{\pi q n_i \omega \sinh \left( \frac{q V_j}{2KT} \right)}{\sqrt{\tau_p \tau_n} q(V_{bi} - V)/kT} \quad (1.21)$$

The dark current is  $J_D = J_{inj} + J_{rec}$  and the total current is  $J = J_{sc} - J_D$ .

The effect of a series resistance  $R_s$  and shunt resistance  $R_{sh}$  can be included in the model by considering the equivalent circuit diagram of Figure 2.

Nominal values for the conventional solar cell parameters are given in the computer program "conven" listed in the Appendix A. In this computer program the absorption coefficient as a function of energy is obtained from interpolation of numerical input data. Empirical formulas approximating lifetimes, mobilities, intrinsic carrier density and bandgap energy as functions of temperature are included in the program.



$$I_{out}(1+R_s/R_{sh}) = I_{sc} - V_{out}/R_{sh} - I_{dark}$$

FIGURE 2. Equivalent circuit for solar cell

## 2. ONE-DIMENSION VERTICAL JUNCTION PHOTOCONVERTER MODEL

The geometry for the vertical junction photoconverter is illustrated in Figure 3. We consider a narrow strip at a depth  $n$  below the surface  $y = A$ . Following References 3, 4, we treat this strip as a conventional photoconverter and then sum the results over all  $n$ ,  $0 < n < A$ .

In the  $n$ -region we have the diffusion equation

$$D_p \frac{d^2}{dx^2} (P_n - P_{no}) - \frac{(P_n - P_{no})}{\tau_p} = -g(A-y), \quad (2.1)$$

subject to the boundary conditions:

$$P_n - P_{no} = 0 \quad \text{at} \quad x = x_j + x_n \quad (2.2)$$

$$-D_p \frac{d}{dx} (P_n - P_{no}) = S_p (P_n - P_{no}) \quad \text{at} \quad x = B \quad (2.3)$$

From this equation we obtain the current density at  $x_j + x_n$  given by

$$J_p = q D_p \frac{d}{dx} (P_n - P_{no}) \quad \text{at} \quad x = x_j + x_n \quad (2.4)$$

which simplifies to

$$J_p = -g(A-y) q L_p \frac{[S_p - f(S_p, D_p/L_p, (B-x_j-x_n)/L_p)]}{f(D_p/L_p, S_p, (B-x_j-x_n)/L_p)} \quad (2.5)$$

In the  $p$ -region we have the diffusion equation




FIGURE 3. Vertical junction photoconverter geometry.

$$D_n \frac{d^2}{dx^2} (n_p - n_{po}) - (n_p - n_{po})/\tau_n = -g(A-y) \quad (2.6)$$

which is subject to the boundary conditions:

$$n_p - n_{po} = 0 \quad \text{at} \quad x = x_j - x_p \quad (2.7)$$

$$D_n \frac{d}{dx} (n_p - n_{po}) = S_n (n_p - n_{po}) \quad \text{at} \quad x=0 \quad (2.8)$$

This produces the current density at  $x_j - x_p$  given by

$$J_n = -q D_n \frac{d}{dx} (n_p - n_{po}) \quad \text{at} \quad x = x_j - x_p \quad (2.9)$$

which simplifies to

$$J_n = -g(A-y) q L_n \left[ \frac{S_n - f(S_n, D_n/L_n, (x_j - x_p)/L_n)}{f(D_n/L_n, S_n, (x_j - x_p)/L_n)} \right] \quad (2.10)$$

The total current is obtained by integrating these current densities over the depth of the photoconverter. Assuming the photoconverter is 1 cm in depth we have:

$$I_{sc} = \int_0^A J_p(n) dn + \int_0^A J_n(n) dn = I_p + I_n \quad (2.11)$$

The dark current is given by  $I_d = I_p^* + I_n^*$  where

$$I_p^* = \frac{P_{no} q D_p}{L_p} \frac{f(1, D_p/L_p S_p, (B-x_j-x_n)/L_p)}{f(D_p/L_p S_p, 1, (B-x_j-x_n)/L_p)} [e^{qV/kT} - 1] A \quad (2.12)$$

$$I_n^* = \frac{n_{po} q D_n}{L_n} \frac{f(1, D_n/L_n S_n, (x_j-x_p)/L_n)}{f(D_n/L_n S_n, 1, (x_j-x_p)/L_n)} [e^{qV/kT} - 1] A \quad (2.13)$$

Using  $P_{in} = B W_0(1000)$  (watts) as the input power and  $P_{out} = P_{max}$  as the maximum power obtained from the I-V curve, we calculate the efficiency as

$$E_{ff} = 100 P_{in}/P_{out} \quad (2.14)$$

Nominal values for the vertical junction photoconverter are given in the computer program "VJSCP" listed in Appendix B. We use the same empirical formulas approximating the lifetimes, mobilities, intrinsic carrier density and bandgap energy as a function of temperature as listed in the Appendix B. For both computer programs listed in Appendix A and Appendix B the temperature of the photoconverter is assumed controlled by the use of a heat pipe. The current voltage relationship is obtained from the equivalent circuit diagram of Figure 2.

### 3. THREE-DIMENSIONAL CONVENTIONAL PHOTOCONVERTER

The geometry for the three-dimensional conventional photoconverter model is illustrated in Figure 4. We let  $R_n = \{(x,y,z) \mid |x| < a, |y| < b, 0 < z < z_j\}$  denote the n-region and let  $R_p = \{(x,y,z) \mid |x| < a, |y| < b, z_j + w < z < H\}$  denote the p-region. We assume that the light impinges upon the surfaces  $z=0$ . The equation for the diffusion of the minority carriers in the n-






FIGURE 4: Geometry for three dimensional model of photoconverter

material is given by

$$L(P_n - P_{no}) = \nabla^2(P_n - P_{no}) - (P_n - P_{no})/L_p^2 = -g(Z)/D_p, \quad x, y, z \in R_n \quad (3.1)$$

where  $L()$  is the linear operator  $\nabla^2() - ()/L_p^2$  and  $g(x)$  is the generation rate defined by (1.1). Boundary conditions for the above equation are:

$$D_p \frac{\partial}{\partial Z} (P_n - P_{no}) = S_p (P_n - P_{no}) \text{ at } Z=0, \quad P_n - P_{no} = 0 \text{ at } Z=Z_j \quad (3.2)$$

$$-D_p \frac{\partial}{\partial x} (P_n - P_{no}) = S_0 (P_n - P_{no}) \text{ at } x=a, \quad D_p \frac{\partial}{\partial x} (P_n - P_{no}) = S_0 (P_n - P_{no}) \text{ at } x=-a \quad (3.3)$$

$$-D_p \frac{\partial}{\partial y} (P_n - P_{no}) = S_0 (P_n - P_{no}) \text{ at } y=b, \quad D_p \frac{\partial}{\partial y} (P_n - P_{no}) = S_0 (P_n - P_{no}) \text{ at } y=-b \quad (3.4)$$

where we have assumed that the surface recombination velocity is  $S_0$  on the sides and  $S_p$  on the surface  $z=0$ .

Similarly, the equation for the diffusion of minority carriers in the p-material is given by

$$L(n_p - n_{po}) = \nabla^2 (n_p - n_{po}) - (n_p - n_{po})/L_n^2 = -g(z)/D_n, \quad x, y, z \in R_p \quad (3.5)$$

with the boundary conditions

$$n_p - n_{po} = 0 \text{ at } Z=Z_j+w, \quad -D_n \frac{\partial}{\partial z} (n_p - n_{po}) = S_n (n_p - n_{po}) \text{ at } Z=H \quad (3.6)$$

$$-D_n \frac{\partial}{\partial x} (n_p - n_{p0}) = S_1 (n_p - n_{p0}) \text{ at } x=a, \quad D_n \frac{\partial}{\partial x} (n_p - n_{p0}) = S_1 (n_p - n_{p0}) \text{ at } x=-a \quad (3.7)$$

$$-D_n \frac{\partial}{\partial y} (n_p - n_{p0}) = S_1 (n_p - n_{p0}) \text{ at } y=b, \quad D_n \frac{\partial}{\partial y} (n_p - n_{p0}) = S_1 (n_p - n_{p0}) \text{ at } y=-b \quad (3.8)$$

where  $S_1$ ,  $S_n$  are respectively the surface recombination velocities of the sides and bottom surface  $z=H$ .

The solution to the equations (3.1) and (3.5) which satisfy the corresponding boundary conditions is given in terms of Green's functions  $G_1(x,y,z; x_0,y_0,z_0)$  for the region  $R_n$  and  $G_2(x,y,z; x_0,y_0,z_0)$  for the region  $R_p$ .

The Lagrange identity associated with the linear operator  $L()$  is

$$uL(v) - VL(u) = U\nabla^2 V - V\nabla^2 u. \quad (3.9)$$

By Green's second formula we can write

$$\iiint_{V_0} [uL(v) - VL(u)] d\tau_0 = \iiint_{V_0} [u\nabla^2 V - V\nabla^2 u] d\tau_0 = \iint_S (u\nabla V - V\nabla u) \cdot \hat{n} d\sigma_0 \quad (3.10)$$

where  $d\tau_0$  is a volume element,  $d\sigma_0$  is an element of surface area and  $\hat{n}$  is a unit normal to the surface. Let  $V = G_1(x,y,z; x_0,y_0,z_0)$  be a Green's function and let  $U = P_n - P_{n0}$  denote the solution to (3.1) with  $vol = R_n$ , then the integral (3.10) can be written

$$\iiint_{R_n} (p_n - p_{n0}) L(G_1) d\tau_0 - \iiint_{R_n} G_1 \left( \frac{-g(Z_0)}{D_p} \right) d\tau_0 =$$

$$\iint_S [(p_n - p_{n0}) \nabla G_1 - G_1 \nabla (p_n - p_{n0})] \cdot \nu d\sigma_0 \quad (3.11)$$

For  $L(G_1) = \delta(x_0 - x) \delta(y_0 - y) \delta(z_0 - z)$ ,  $\delta$  = Dirac delta function, the above gives

$$p_n - p_{n0} = \int_0^{Z_j} \int_{-b}^b \int_{-a}^a \frac{-\alpha \phi_0 (1 - Re) e^{-\alpha Z_0}}{D_p} G_1(x, y, z; x_0, y_0, z_0) dx_0 dy_0 dz_0 \quad (3.12)$$

where the boundary conditions on  $G_1$  are chosen such that the surface integral vanishes. The surface integral in (3.11) can be written for the region  $R_n$  as follows:

$$\begin{aligned} & \int_{-b}^b \int_0^{Z_j} [(p_n - p_{n0}) \left( \frac{-\partial G_1}{\partial x_0} \right) - G_1 \left( \frac{-\partial (p_n - p_{n0})}{\partial x_0} \right)] dy_0 dz_0 \Big|_{x_0=-a} \\ & + \int_{-a}^a \int_0^{Z_j} [(p_n - p_{n0}) \left( \frac{+\partial G_1}{\partial y_0} \right) - G_1 \left( \frac{\partial (p_n - p_{n0})}{\partial y_0} \right)] dx_0 dz_0 \Big|_{y_0=b} \\ & + \int_{-b}^b \int_0^{Z_j} [(p_n - p_{n0}) \left( \frac{-\partial G_1}{\partial x_0} \right) - G_1 \left( \frac{-\partial (p_n - p_{n0})}{\partial x_0} \right)] dy_0 dz_0 \Big|_{x_0=a} \\ & + \int_{-a}^a \int_0^{Z_j} [(p_n - p_{n0}) \left( \frac{-\partial G_1}{\partial y_0} \right) - G_1 \left( \frac{-\partial (p_n - p_{n0})}{\partial y_0} \right)] dx_0 dz_0 \Big|_{y_0=-b} \\ & + \int_{-a}^a \int_{-b}^b [(p_n - p_{n0}) \left( \frac{-\partial G_1}{\partial z_0} \right) - G_1 \left( \frac{-\partial (p_n - p_{n0})}{\partial z_0} \right)] dx_0 dy_0 \Big|_{z_0=0} \end{aligned} \quad (3.13)$$

$$+ \int_{-a}^a \int_{-b}^b \left[ (P_n - P_{n0}) \left( \frac{\partial G_1}{\partial z_0} \right) - G_1 \left( \frac{\partial (P_n - P_{n0})}{\partial z_0} \right) \right]_{z_0 = z_j} dx_0 dy_0 = 0$$

The above equation gives the boundary condition for the Green's function and we obtain that  $G_1$  must satisfy

$$\frac{\partial^2 G_1}{\partial x_0^2} + \frac{\partial^2 G_1}{\partial y_0^2} + \frac{\partial^2 G_1}{\partial z_0^2} - G_1 / L_p^2 = \delta(x_0 - x) \delta(y_0 - y) \delta(z_0 - z), \quad x_0, y_0, z_0 \in R_n \quad (3.14)$$

with boundary conditions:

$$\left. \begin{aligned} D_p \frac{\partial G_1}{\partial x_0} &= S_0 G_1 \text{ at } x_0 = -a, & -D_p \frac{\partial G_1}{\partial x_0} &= S_0 G_1 \text{ at } x_0 = a \\ D_p \frac{\partial G_1}{\partial y_0} &= S_0 G_1 \text{ at } y_0 = -b, & -D_p \frac{\partial G_1}{\partial y_0} &= S_0 G_1 \text{ at } y_0 = b \\ D_p \frac{\partial G_1}{\partial z_0} &= S_p G_1 \text{ at } z_0 = 0, & G_1 &= 0 \text{ at } z_0 = z_j \end{aligned} \right\} \quad (3.15)$$

We perform a similar analysis for the region  $R_p$  and find the Green's function  $G_2$  must satisfy

$$\frac{\partial^2 G_2}{\partial x_0^2} + \frac{\partial^2 G_2}{\partial y_0^2} + \frac{\partial^2 G_2}{\partial z_0^2} - G_2 / L_p^2 = \delta(x_0 - x) \delta(y_0 - y) \delta(z_0 - z), \quad x_0, y_0, z_0 \in R_p \quad (3.16)$$

with boundary conditions

$$\left. \begin{aligned} -D_n \frac{\partial G_2}{\partial x_0} &= S_1 G_2 \quad \text{at } x_0 = a, & D_n \frac{\partial G_2}{\partial x_0} &= S_1 G_2 \quad \text{at } x_0 = -a \\ -D_n \frac{\partial G_2}{\partial y_0} &= S_1 G_2 \quad \text{at } y_0 = b, & D_n \frac{\partial G_2}{\partial y_0} &= S_1 G_2 \quad \text{at } y_0 = -b \\ -D_n \frac{\partial G_2}{\partial z_0} &= S_n G_2 \quad \text{at } z_0 = H, & G_2 &= 0 \quad \text{at } z_0 = z_j + \omega \end{aligned} \right\} \quad (3.17)$$

and the solution for the minority carrier density in the  $R_p$  region is given by

$$n_p - n_{p0} = \int_{z_j + \omega}^H \int_{-b}^b \int_{-a}^a \frac{-\alpha \phi_0 (1 - \text{Re}) e^{-\alpha z_0}}{D_n} G_2(x, y, z; x_0, y_0, z_0) dx_0 dy_0 dz_0 \quad (3.18)$$

From the relations (3.12) and (3.18) we can obtain the current densities

$$J_p = -qD_p \frac{\partial}{\partial z} (P_n - P_{n0}) \quad \text{at } Z = Z_j \quad \text{and} \quad J_n = qD_n \frac{\partial}{\partial z} (n_p - n_{p0}) \quad \text{at } Z = Z_j + \omega \quad (3.19)$$

To find the Green's functions  $G_1, G_2$  for the regions  $R_n$  and  $R_p$  we examine the eigenfunctions and eigenvalues associated with the operator  $L()$ . We let  $u = u(r)$  satisfy the eigenvalue problem

$$\frac{d^2 u}{dr^2} + \lambda^2 u = 0 \quad (3.20)$$

with boundary conditions

$$D \frac{du}{dr} + S_3 u = 0 \quad \text{at } r=h, \quad D \frac{du}{dr} - S_3 u = 0 \quad \text{at } r=-h \quad (3.21)$$

The eigenfunctions of this problem are:

$$u = u_n(r) = \cos(\lambda_n r) = u(r; D, S_3, h, \lambda_n) \quad (3.22)$$

where  $\lambda = \lambda_n$  satisfies the equation

$$(\lambda_n h) \tan(\lambda_n h) = \frac{S_3 h}{D} \quad (3.23)$$

We let  $\xi_n = \lambda_n h$  satisfy  $\tan(\xi_n) = S_3 h / D \xi_n$  then  $\xi_n$  is characterized by the intersection of the curves  $y = \tan(\xi)$  and  $y = S_3 h / D \xi$  (See Figure 5). Note that for large values of  $n$ ,  $\xi_{n+1}$  approaches  $n\pi$ , and that the above functions  $u_n(r)$  are orthogonal on the interval  $(-h, h)$

and

$$(u_n, u_m) = \int_{-h}^h u_n(r) u_m(r) dr = \begin{cases} 0, & m \neq n \\ \|u_n\|^2, & m = n \end{cases} \quad (3.24)$$

where

$$\|u_n\|^2 = h + \frac{S_3}{D \lambda_n^2} \cos^2(\lambda_n h) = h + \frac{S_3 h^2}{D} \frac{\cos^2(\xi_n)}{\xi_n^2} \quad (3.25)$$

We will use these functions in the construction of our Green's function




FIGURE 5. Graphical scheme for determining eigenvalues



solutions for  $G_1$  and  $G_2$ .

Define the eigenfunctions associated with the region  $R_n$  as

$$U_m(x) = \cos(\lambda_m x), \quad -a < x < a, \quad m=1,2,3,\dots$$

with

$$\xi_m = \lambda_m a, \quad \|U_m\|^2 = a + \frac{S_0 a^2}{D_p} \frac{\cos^2(\xi_m)}{\xi_m^2}$$

and where

$$\xi_m \tan \xi_m = S_0 a / D_p, \quad m=1,2,3,\dots$$

Also define the eigenfunctions

$$V_m(y) = \cos(\mu_m y), \quad -b < y < b$$

with

$$\eta_m = \mu_m b, \quad \|V_m\|^2 = b + \frac{S_0 b^2}{D_p} \frac{\cos^2(\eta_m)}{\eta_m^2}$$

where

$$\eta_m \tan(\eta_m) = S_0 b / D_p.$$

There will be a similar set of eigenfunctions associated with the region  $R_p$ .

We denote these eigenfunctions by  $U_m^*(x)$  and  $V_m^*(y)$  and note that  $S_0$  is

replaced by  $S_1$  in the calculation of these eigenfunctions. We now assume a solution for the Green's functions  $G_1, G_2$  as:

$$G_1 = \sum_{i=1}^{\infty} \sum_{j=1}^{\infty} A_{ij}(z_0) U_j(x_0) V_i(y_0) \quad (3.26)$$

$$G_2 = \sum_{i=1}^{\infty} \sum_{j=1}^{\infty} B_{ij}(z_0) U_j^*(x_0) V_i^*(y_0) \quad (3.27)$$

as the functions  $U_j$  and  $V_i$  satisfy the boundary conditions and

$$U_n(x) = \cos(\lambda_n h) = u(x; D_p, S_0, a, \lambda_n), \quad -a < x < a$$

$$U_n^*(x) = \cos(\lambda_n^* x) = u(x; D_n, S_1, a, \lambda_n^*), \quad -a < x < a$$

$$V_m(y) = \cos(\mu_m y) = u(y; D_p, S_0, b, \mu_m), \quad -b < y < b$$

$$V_m^*(y) = \cos(\mu_m^* y) = u(y; D_n, S_1, b, \mu_m^*), \quad -b < y < b$$

where it is assumed that  $S_0, S_1$  are different from zero. Substituting (3.26) and (3.27) into (3.14) and (3.16) respectively, we find that  $A_{mn}$  and  $B_{mn}$  must be chosen to satisfy the conditions:

$$A_{ij}'' - \frac{1}{\gamma_{ij}^2} A_{ij} = \frac{U_j(x) V_i(y) \delta(z_0 - z)}{\|U_j\|^2 \|V_i\|^2}, \quad 0 < z_0 < z_j \quad (3.28)$$

$$A_{ij}(z_j) = 0, \quad D_p \frac{dA_{ij}}{dz_0} - S_p A_{ij} = 0 \text{ at } z_0 = 0$$

with

$$\gamma_{ij}^2 = L_p^2 / (1 + L_p^2 (\lambda_i^2 + \mu_j^2))$$

$$B_{ij}'' - \frac{1}{\sigma_{ij}^2} B_{ij} = \frac{U_j^*(x) V_i^*(y) \delta(z_0 - z)}{\|U_j\|^2 \|V_i\|^2}, \quad Z_j + \omega < z_0 < H \quad (3.29)$$

$$B_{ij}(Z_j + \omega) = 0, \quad D_n \frac{dB_{ij}}{dz_0} + S_n B_{ij} = 0 \text{ at } z_0 = H.$$

with

$$\sigma_{ij}^2 = L_n^2 / (1 + L_n^2 (\lambda_i^{*2} + \mu_j^{*2})).$$

These equations have the solutions

$$A_{ij}(z_0) = \begin{cases} \frac{U_j(x) V_i(y) y_1(z_0) y_2(z)}{\|U_j\|^2 \|V_i\|^2 \Delta_1}, & 0 < z_0 < Z_j \\ \frac{U_j(x) V_i(y) y_1(z) y_2(z_0)}{\|U_j\|^2 \|V_i\|^2 \Delta_1}, & z < z_0 < Z_j \end{cases} \quad (3.30)$$

where

$$y_1(z) = \cosh(z/\gamma_{ij}) + (S_p \gamma_{ij} / D_p) \sinh(z/\gamma_{ij})$$

$$y_2(z) = \frac{\sinh(Z_j - z)/\gamma_{ij}}{\sinh(Z_j/\gamma_{ij})}$$

and

$$\Delta_1 = - \frac{1}{\gamma_{ij}} \frac{y_1(Z_j)}{\sinh(Z_j/\gamma_{ij})}.$$

Also,

$$B_{ij} = \begin{cases} \frac{U_j^*(x) V_i^*(y) y_4(z) y_3(z_0)}{\|U_j\|^2 \|V_i\|^2 \Delta_2}, & Z_j + \omega < z_0 < z \\ \frac{U_j^*(x) V_i^*(y) y_3(z) y_4(z_0)}{\|U_j\|^2 \|V_i\|^2 \Delta_2}, & z < z_0 < H \end{cases} \quad (3.31)$$

with  $y_3(z) = \sinh(Z - Z_j - \omega)/\sigma_{ij}$

$$y_4(z) = \cosh((H - z)/\sigma_{ij}) + \frac{S_n \sigma_{ij}}{D_n} \sinh((H - z)/\sigma_{ij})$$

$$\Delta_2 = - \frac{1}{\sigma_{ij}} y_4(Z_j + \omega).$$

From the equations (3.12) (3.18) (3.19) (3.26) and (3.27) we obtain the current density

$$J_p = 4\alpha q\phi_0(1-R) \sum_{m=1}^{\infty} \sum_{n=1}^{\infty} \gamma_{mn} \frac{U_n(x) V_m(y) \sin(\lambda_{na}) \sin(\mu_{mb}) G_{mn}}{\|U_n\|^2 \|V_m\|^2 \lambda_n \mu_m} \quad (3.32)$$

with

$$G_{mn} = \frac{1}{\alpha^2 \gamma_{mn}^2 - 1} \left[ \frac{S_p^{\gamma_{ij}} / D_p + \alpha \gamma_{mn} e^{-\alpha Z_j} \left\{ S_p^{\gamma_{ij}} / D_p \cosh(Z_j / \gamma_{mn}) + \sinh(Z_j / \gamma_{mn}) \right\} \alpha \gamma_{mn} e^{-\alpha Z_j}}{y_1(Z_j)} \right]$$

Observe that  $G_{mn}$  has a removable singularity where  $\alpha \gamma_{mn} = 1$  and in this case we can write

$$G_{mn} = \frac{1}{\alpha \gamma_{mn} + 1} \left[ \frac{1 + (S_p^{\gamma_{ij}} / D_p + 1) \left\{ \frac{1 - e^{-Z_j / \gamma_{mn} (\alpha \gamma_{mn} - 1)}}{\alpha \gamma_{mn} - 1} \right\} e^{-\alpha Z_j}}{y_1(Z_j)} \right]$$

The current density  $J_n$  is given by

$$J_n = 4\alpha q \phi_0 (1-R) \sum_{m=1}^{\infty} \sum_{n=1}^{\infty} \frac{U_n^*(x) V_m^*(y) \sigma_{mn} \sin(\lambda_n^* a) \sin(\mu_m^* b) H_{mn}}{\|V_n^*\|^2 \|V_m^*\|^2 \lambda_n^* \mu_m^* y_4(Z_j + w)} \quad (3.33)$$

with

$$H_{mn} = \frac{1}{\alpha^2 \sigma_{mn}^2 - 1} \left[ e^{-\alpha H} \left( \frac{S_n^{\sigma_{ij}}}{D_n} - \alpha \sigma_{mn} \right) + e^{-\alpha (Z_j + w)} \left( \frac{S_n^{\sigma_{ij}}}{D_n} \sigma_{mn} - 1 \right) \sinh(H' / \sigma_{mn}) \right. \\ \left. + e^{-\alpha (Z_j + w)} \left( \sigma_{mn} \alpha - S_n^{\sigma_{ij}} / D_n \right) \cosh(H' / \sigma_{mn}) \right]$$

with  $H' = H - z_j - w$ . The total light current is  $J_L = J_p + J_n$ .

## DARK CURRENTS

The equations describing the dark currents associated with the n and p regions may be expressed

$$\nabla^2 (P_n - P_{no}) - \frac{(P_n - P_{no})}{L_p^2} = 0$$

with boundary conditions:

$$P \equiv P_n - P_{no} = P_{no} \left[ \exp \left( \frac{qV_j}{KT} \right) - 1 \right] \text{ at } z = z_j$$

$$D_p \frac{\partial P}{\partial z} - S_p P = 0 \text{ at } z = 0$$

$$-D_p \frac{\partial P}{\partial x} - S_0 P = 0 \text{ at } x = a, \quad D_p \frac{\partial P}{\partial x} - S_0 P = 0 \text{ at } x = -a$$

$$-D_p \frac{\partial P}{\partial y} - S_0 P = 0 \text{ at } y = b, \quad D_p \frac{\partial P}{\partial y} - S_0 P = 0 \text{ at } y = -b$$

and

$$\nabla^2 (n_p - n_{po}) - \frac{(n_p - n_{po})}{L_n^2} = 0 \quad (3.35)$$

with boundary conditions

$$n = n_p - n_{po} = n_{po} \left[ \exp \left( \frac{qV_j}{KT} \right) - 1 \right] \text{ at } Z = Z_j + \omega$$

$$-D_n \frac{\partial n}{\partial z} - S_n n = 0 \quad \text{at } z = H$$

$$-D_n \frac{\partial n}{\partial x} - S_1 n = 0 \quad \text{at } x = a, \quad D_n \frac{\partial n}{\partial x} - S_1 n = 0 \quad \text{at } x = -a$$

$$-D_n \frac{\partial n}{\partial y} - S_1 n = 0 \quad \text{at } y = b, \quad D_n \frac{\partial n}{\partial y} - S_1 n = 0 \quad \text{at } y = -b$$

with  $V_j$  the junction voltage.

We use the relation (3.11) with  $g=0$  and obtain the Green's second formula

$$\iiint_{R_n} (P - P_{no}) L(G_1) d\tau_0 = P_n - P_{no} = \sum_{i=1}^6 I_i \quad (3.36)$$

where  $I_i$ ,  $i=1, \dots, 6$  are the surface integrals defined by (3.13). Applying the boundary conditions from (3.34) the relation (3.36) reduces to

$$P_n - P_{no} = \int_{-b}^b \int_{-a}^a P_{no} \left[ \exp\left(\frac{qV_j}{KT}\right) - 1 \right] \frac{\partial G_1}{\partial Z_0} \bigg|_{Z_0=Z_j} dx_0 dy_0 \quad (3.37)$$

and the dark current opposing the photo current is given by

$$J_{pd} = -q D_p \text{grad} (P_n - P_{no}) \cdot \hat{k} \bigg|_{Z=Z_j} \quad (3.38)$$

A similar analysis for the region  $R_p$  produces the electron density

$$n_p - n_{po} = \int_{-b}^b \int_{-a}^a -n_{po} \left[ \exp \left( \frac{qV_j}{KT} \right) - 1 \right] \frac{\partial G_2}{\partial z_0} \bigg|_{z_0 = Z_j + w} dx_0 dy_0 \quad (3.39)$$

and the dark current opposing the photocurrent is given by

$$J_{nd} = -qD_n \text{ grad } (n_p - n_{po}) \cdot (-\hat{k}) \bigg|_{z=Z_j+w} \quad (3.40)$$

The equations (3.38) and (3.40) simplify to

$$J_{pd} = 4abq D_p P_{no} (e^{qV_j/kT} - 1) \sum_m \sum_n \frac{U_n(x) V_m(y) y_1'(Z_j) \sin(\lambda_n a) \sin(\mu_m b)}{\|U_n\|^2 \|V_m\|^2 y_1(Z_j) (\lambda_n a) (\mu_m b)} \quad (3.41)$$

and

$$J_{nd} = 4abq D_n n_{po} (e^{qV_j/kT} - 1) \sum_m \sum_n \frac{U_n^*(x) V_m^*(y) y_4'(Z_j+w) \sin(\lambda_n^* a) \sin(\mu_m^* b)}{\|U_n^*\|^2 \|V_m^*\|^2 y_4(Z_j+w) (\lambda_n^* a) (\mu_m^* b)} \quad (3.42)$$

where  $P_{no} = n_i^2/N_d$  and  $n_{po} = n_i^2/N_a$

The total dark current density is

$$J_{dark} = J_{pd} + J_{nd} = J_0 \left( \exp \left( \frac{qV_j}{KT} \right) - 1 \right) \quad (3.43)$$

We use the recombination current density from (1.21) and calculate the total currents by integration



$$I_{sc} = \int_{-b}^b \int_{-a}^a J_L dx dy \quad (3.44)$$

$$I_{rec} = J_{rec} \cdot 4ab \quad (3.45)$$

$$I_0 = \int_{-b}^b \int_{-a}^a J_0 dx dy \quad (3.46)$$

$$I_{dark} = \int_{-b}^b \int_{-a}^a J_{dark} dx dy \quad (3.47)$$

The current voltage relation is obtained from the equivalent circuit diagram of Figure 2. The computer program "SC3D" which utilizes the above equations is given in Appendix C.

#### 4. THREE-DIMENSIONAL VERTICAL JUNCTION SOLAR CELL

With reference to the geometry illustrated in Figure 4, we assume the photoconverter is illuminated from the side  $x=a$ . For this assumption, we use the generation term  $g(a-x)$  where  $g(x)$  is defined by equation (1.1). Also we must modify the Green's functions  $G_1, G_2$  used in the conventional photoconverter. Note that  $G_1, G_2$  were expanded as double Fourier series which were symmetric in both  $x$  and  $y$ . For illumination from the side  $x=a$  we must remove the symmetry in the  $x$ -direction. Consequently, for the  $n$ -region and  $p$ -region we construct Green's functions  $g_1, g_2$  having the following form:

$$g_1 = \sum_{m=1}^{\infty} \sum_{\ell=1}^{\infty} \frac{V_m(y_0) W_{\ell}(z_0) V_m(y) W_{\ell}(z) \psi_{3m\ell}}{\|V_m\|^2 \|W_{\ell}\|^2 \rho_{m\ell}} \quad (4.1)$$

$$g_2 = \sum_{m=1}^{\infty} \sum_{\ell=1}^{\infty} \frac{V_m^*(y_0) W_{\ell}^*(z_0) V_m^*(y) W_{\ell}^*(z) \psi_{4m\ell}}{\|V_m^*\|^2 \|W_{\ell}^*\|^2 \rho_{m\ell}^*} \quad (4.2)$$

where  $W_{\ell} = \sin(\eta_{\ell}(Z_j - z)), \quad 0 < z < Z_j, \ell=1,2,3,\dots$  (4.3)

and  $W_{\ell}^* = \sin(\eta_{\ell}^*(z - Z_j - w)), \quad Z_j + w < z < H, \ell=1,2,3,\dots$  (4.4)

are eigenfunctions with eigenvalues determined by the roots of the equations

$$-D_p(\eta_{\ell} Z_j) / (S_p Z_j) = \tan(\eta_{\ell} Z_j) \quad (4.5)$$

and

$$-D_n(\eta_{\ell}^* H') / (S_n H') = \tan(\eta_{\ell}^* H'), \quad H' = H - Z_j - w \quad (4.6)$$

respectively. These eigenfunctions have the norm squared

$$\|W_{\ell}\|^2 = \frac{1}{2} Z_j - \frac{1}{4} \frac{\sin(2\eta_{\ell} Z_j)}{\eta_{\ell}} \quad (4.7)$$

$$\|W_{\ell}^*\|^2 = \frac{1}{2} H' - \frac{1}{4} \frac{\sin(2\eta_{\ell}^* H')}{\eta_{\ell}^*} \quad (4.8)$$

In (4.1) and (4.2)  $V_m, V_m^*$  have been previously defined in (3.26) and (3.27).

Also in (4.1) and (4.2) we have

$$\rho_{ij} = \left( \frac{1}{r_{ij}} + \frac{S_0^2 r_{ij}}{D_p^2} \right) \sinh \left( \frac{2a}{r_{ij}} \right) + \frac{2S_0}{D_p} \cosh \left( \frac{2a}{r_{ij}} \right) \quad (4.9)$$

$$\rho_{ij}^* = \left( \frac{1}{\epsilon_{ij}} + \frac{S_1^2 \epsilon_{ij}}{D_n^2} \right) \sinh \left( \frac{2a}{\epsilon_{ij}} \right) + \frac{2S_1}{D_n} \cosh \left( \frac{2a}{\epsilon_{ij}} \right) \quad (4.10)$$

$$r_{ij}^2 = L_p^2 / (1 + L_p^2 (\mu_i^2 + \eta_j^2)) , \quad \epsilon_{ij}^2 = L_n^2 / (1 + L_n^2 (\mu_i^*{}^2 + \eta_j^*{}^2)) \quad (4.11)$$

$$\psi_{3mn} = \begin{cases} -y_1(X)y_2(X_0), & -a < X_0 < X \\ -y_1(X_0)y_2(X), & X < X_0 < a \end{cases} \quad (4.12)$$

$$\psi_{4ij} = \begin{cases} -y_4(X)y_3(X), & -a < X_0 < X \\ -y_4(X_0)y_3(X), & X < X_0 < a \end{cases} \quad (4.13)$$

$$y_1(X) = \cosh \left( \frac{a-X}{r_{mn}} \right) + \frac{S_0 r_{mn}}{D_p} \sinh \left( \frac{a-X}{r_{mn}} \right) \quad (4.14)$$

$$y_2(X) = y_1(-X) \quad (4.15)$$

$$y_3(X) = \cosh \left( \frac{a-X}{\epsilon_{ij}} \right) + \frac{S_1 \epsilon_{ij}}{D_n} \sinh \left( \frac{a-X}{\epsilon_{ij}} \right) \quad (4.16)$$

$$y_4(X) = y_3(-X) \quad (4.17)$$

In the n-region we can represent the solution to the boundary value problem

(3.1) by

$$P_n - P_{no} = \int_0^{z_j} \int_{-b}^b \int_{-a}^a \frac{-g(a-x_0)}{D_p} g_1(x, y, z; x_0, y_0, z_0) dx_0 dy_0 dz_0 \quad (4.18)$$

and in the p-region we can represent the solution to the boundary value problem (3.5) by

$$n_p - n_{po} = \int_{z_j+w}^H \int_{-b}^b \int_{-a}^a \frac{-g(a-x_0)}{D_n} g_2(x, y, z; x_0, y_0, z_0) dx_0 dy_0 dz_0 \quad (4.19)$$

where the source term has been replaced by  $g(a-x_0)$  which models the illumination from the side  $x_0 = a$ . From these equations we use (3.19) to obtain the photocurrents. The computer program "VSC3D" describing the vertical junction model is given in the Appendix D together with representative graphic output.

## REFERENCES

1. Hovel, H.J. Semiconductors and Semimetals, Volume II, Solar Cells, Academic Press, 1975.
2. Sze, S.M. Physics of Semiconductor Devices, John Wiley and Sons, 1969.
3. Gover, A., Stella, P. Vertical Multijunction Solar Cell One-Dimensional Analysis, IEEE Transactions on Electron Devices, June 1974.
4. Rahilly, W.P. Vertical Multijunction Solar cells, Conference Record of the Ninth IEEE Photovoltaic Specialists Conference, Silver Springs, Maryland, May 2, 3, 4, 1972.
5. Parrott, J.E. The Limiting Efficiency of an Edge-illuminated Multigap Solar Cell, J. Phys. D:Appl. Phys. Vol. 12, 1979.

APPENDIX A

BASIC COMPUTER PROGRAM FOR  
ONE-DIMENSIONAL CONVENTIONAL PHOTOCONVERTER

```

10 OPTION BASE 1
20 !*****
30 !
40 ! PROGRAM CONVEN
50 !
60 ! CONVENTIONAL SOLAR CELL PROGRAM SET UP FOR Si SOLAR CELL CHARACTERISTICS
70 !
80 REM CONVENTIONAL SOLAR CELL PROGRAM CONSTANT TEMPERATURE
90 !
100 !*****
110 DIM X(50),Xx(50),Aa(50,4),Z(50),Volts(100),Amps(100)
120 DIM Esi(20),Asi(20)
130 !*****
140 !
150 ! READ IN Silicon ABSORPTION COEFFICIENT DATA
160 Nsi=20 ! THIS IS NUMBER OF DATA POINT PAIRS TO READ
170 ! IF YOU CHANGE THIS NUMBER CHANGE DIM STATEMENT ABOVE
180 FOR I=1 TO Nsi
190 READ Esi(I),Asi(I) !READ IN ENERGY(EV) AND ABSORPTION COEFF CM-1
200 NEXT I
210 DATA 1.1,1.15,10,1.24,100,1.378,350,1.46,950,1.77,2000
220 DATA 2.067,4500,2.48,1E4,2.76,2E4,3.1,5E4,3.26,1E5,3.5,1E6,3.6,1.1E6
230 DATA 4,1.8E6,4.2,2.5E6,5,1.9E6,5.2,2E6,6,1.5E6,8,1.3E6,10,1.1E6
240 GINIT
250 GRAPHICS ON
260 GCLEAR
270 WINDOW 0,100,0,100
280 CSIZE 9
290 LORG 5
300 MOVE 50,50
310 LABEL "SPECTRAL RESPONSE CURVE"
320 CSIZE 5
330 MOVE 50,40
340 LABEL "IT TAKES A MOMENT TO CALCULATE"
350 !SOLAR CELL CONSTANTS
360 !CONSTANTS FOR MOBILITY Mun
370 A0=65.02 !FOR Si; FOR GaAs A0=5076.11 ; FOR Ge A0=458.68
380 A1=5.72E-9 !FOR Si; FOR GaAs A1=6.03E-8 ; FOR Ge A1=7.92E-9
390 A2=2.49E+9 !FOR Si; FOR GaAs A2=2.13E6 ; FOR Ge A2=6.08E7
400 A3=2.5 !FOR Si ; FOR GaAs A3=1.0 ; FOR Ge A3=1.66
410 !CONSTANTS FOR MOBILITY Mup
420 B0=54.46 !FOR Si ; FOR GaAs B0=37.33 ; FOR Ge B0=3140.27
430 B1=6.76E-9 !FOR Si; FOR GaAs B1=8.51E-9; FOR Ge B1=1.79E-7
440 B2=2.93E+9 !FOR Si; FOR GaAs B2=6.05E7 ; FOR Ge B2=1.18E9
450 B3=2.7 !FOR Si; FOR GaAs B3=2.1; FOR Ge B3=2.33
460 !CONSTANTS FOR BANDGAP AS FUNCTION OF TEMPERATURE
470 Eggo=1.16 !FOR Si; FOR GaAs 1.522 ; FOR Ge .741
480 Alphao=7.02E-4 !FIR Si; FOR GaAs 5.8E-4; FOR Ge 4.56E-4
490 Betao=1108. !FOR Si; FOR GaAs 300; FOR Ge 210
500 !CONSTANTS FOR INTRINSIC CARRIER DENSITY
510 Nia1=4.9E+15
520 Nia2=1.61
530 B=7.1E+15 !CONSTANT FOR LIFETIME CALCULATIONS
540 Xkko=1.2E-3 !CONSTANT FOR ABSORPTION SHIFT
550 Xkk1=.95 !CONSTANT FOR ABSORPTION SHIFT -SEE BELOW
560 T0=300 ! FIXED REFERENCE TEMPERATURE
570 Kb=8.6172E-5 ! BOLTZMANN'S CONSTANT EV/K
580 Q=1.6E-19 ! ELECTRON CHARGE
590 !*****
600 !
610 ! ADJUSTABLE SOLAR CELL PARAMETERS
620 !

```

```

530 !*****
540 Parameters: ! CHANGE THE VALUES BELOW IF DESIRED
550 Sn=0.E+0 !SURFACE RECOMBINATION VELOCITY CM/SEC
560 Sp=0.E+0 !SURFACE RECOMBINATION VELOCITY CM/SEC
570 Na=1.25E+17 ! DOPING DENSITY P REGION CM-3
580 Nd=5.0E+19 ! DOPING DENSITY N-REGION CM-3
590 Tn0=1.86E-4 ! CONSTANT FOR LIFETIME CALCULATION
700 Tp0=3.52E-3 ! CONSTANT FOR LIFETIME CALCULATION
710 Wo=1.000 !LASER POWER KW/CM2
720 !Wo DETERMINES TEMPERATURE IN CELL
730 !SEE BELOW
740 Hh2=100 !HEAT TRANSFER COEFFICIENT TO BACK SURFACE
750 !UNITS OF WATTS/CM2-DEG C
760 Kback=1.5 !WATTS/CM-DEG C THERMAL CONDUCTIVITY BACK SURFACE
770 Tpipe=100 !TEMPERATURE DEG C OF HEAT PIPE (ASSUMED TEMP
780 !OF HEAT PIPE LOWER TEMPERATURE
790 Lambda=1.06 !LASER WAVELENGTH IN MICRONS
800 Re=.05 !REFLECTION COEFFICIENT FOR ILLUMINATED SURFACE
810 Rs=0. ! SOLAR CELL SERIES RESISTANCE IN OHMS
820 Rsh=1.0E+6 !SHUNT RESISTANCE IN OHMS
830 Epso=11.6 ! Si PERMITIVITY COEFFICIENT (DIMENSIONLESS)
840 H=4.500E-1 !SOLAR CELL HEIGHT IN CM
850 Xj=5.0E-4 !JUNCTION DEPTH IN CM
860 !*****
870 !
880 ! BEGIN CALCULATIONS FOR THE SPECTRAL RESPONSE
890 !
900 !*****
910 !ESTIMATE ABSORPTION COEFFICIENT ALPHA
920 T=273+Tpipe+1000*Wo*(1-Re)/Hh2 !ESTIMATE SOLAR CELL TEMP DEG K
930 Ener=1.2402/Lambda ! ENERGY IN EV FOR WAVELENGTH LAMBDA
940 Egt=Eggo-Alphao*T*T/(T+Betao) !BANDGAP FOR THIS TEMPERATURE
941 IF (Ener<=1.7) THEN Xkko=(1.3*Ener-1)*1.0E-3
950 Dele=2*Xkko*(T-T0)
960 E=Ener+Dele
970 Alpha=FNabsorp(Nsi,Esi(*),Asi(*),E) !APPROXIMATION OF ALPHA
980 !CALCULATE TEMPERATURE OF SOLAR CELL AT LASER SURFACE INTERFACE
990 Yy1=Alpha*H
1000 Yy2=0
1010 IF (Yy1<220) THEN Yy2=EXP(-Yy1)
1020 T=Tpipe+(Wo*1000*(1-Re)/Kback)*((Kback/Hh2)-1/Alpha)*(1-Yy2)
1030 IF (T<Tpipe) THEN T=Tpipe
1040 T=T+273 !CONVERT TO DEG K
1050 Kbtg=Kb*T ! BOLTZMANN'S CONSTANT TIMES TEMPERATURE
1060 Egt=Eggo-Alphao*T*T/(T+Betao) ! BANDGAP CALCULATION
1070 Tn=Tn0/(1+Na/B) ! LIFETIME CALCULATION
1080 Tp=Tp0/(1.+Nd/B) ! LIFETIME CALCULATION
1090 Mun=FNmun(Na,T,A0,A1,A2,A3) ! MOBILITY CALCULATION -SEE BELOW FOR FN
1100 Mup=FNmup(Nd,T,B0,B1,B2,B3) ! MOBILITY CALCULATION -SEE BELOW FOR FN
1110 Dn=Kbtg*Mun ! DIFFUSION COEFFICIENT CALCULATION
1120 Dp=Kbtg*Mup ! DIFFUSION COEFFICIENT CALCULATION
1130 Phio=Wo*Lambda*5.03306E+21 !PHOTONS/CM2-S
1140 Ni=(Nia1)*(Nia2)*(T^1.5)*EXP(-Egt/(Kbtg*2)) !INTRINSIC CARRIER DENSITY
1150 Vbi=Kbtg*LOG(Na*Nd/(Ni*Ni)) ! BUILT IN VOLTAGE
1160 W2=(2.*Epso*(8.85E-14)/Q)*Vbi*(1./Nd+1./Na)
1170 W=SQR(W2) !SPACE CHARGE REGION WIDTH
1180 Hp=H-Xj-W ! DEPTH OF BOTTOM SECTION (P REGION)
1190 Lp=SQR(Dp*Tp) ! DIFFUSION LENGTH CALCULATION
1200 Ln=SQR(Dn*Tn) ! DIFFUSION LENGTH CALCULATION
1210 D1=.075 ! WAVELENGTH INCREMENT FOR SPECTRAL RESPONSE CURVE

```



```

1220 !*****
1230 !
1240 !PLOT SPECTRAL RESPONSE AND THEN PAUSE TO LOOK AT IT
1250 !
1260 !*****
1270 FOR J=1 TO 50
1280 X(J)=1.115+(J-1)*D1 !THIS IS ENERGY IN EV
1290 Xx(J)=1.2402/X(J) !THIS IS WAVELENGTH IN MICRONS
1300 Ener=X(J)
1310 Engo=X(J)
1320 IF (Ener>1.7) THEN Xkk=Xkko
1330 IF (Ener<1.7) THEN Xkk=(Xkk1*Ener-1)*1.0E-3
1340 Dele=2*Xkk*(T-T0)
1350 Ene=Ener+Dele
1360 Alpha=FNABSORP(Nsi,Esi(*),Asi(*),Ene)
1370 !PRINT T,Ener,Alpha,Dele
1380 Aa1=Sp*Lp/Dp
1390 Aa2=Xj/Lp
1400 Y1=Alpha*Lp
1410 Aa0=Aa1+Y1
1420 Y2=Y1/(Y1*Y1-1)
1430 Fj=FNJ(Aa1,1.,Aa2)
1440 Z1=Alpha*Xj
1450 Z2=Alpha*(Xj+W)
1460 Z3=Alpha*W
1470 Z4=Alpha*(Hp)
1480 IF (Z1<200) THEN GOTO L53
1490 Y1z=0
1500 GOTO L63
1510 L53: Y1z=EXP(-Z1)
1520 L63: IF (Z2<200) THEN GOTO L54
1530 Y2z=0
1540 GOTO L64
1550 L54: Y2z=EXP(-Z2)
1560 L64: IF (Z3<200) THEN GOTO L55
1570 Y3z=0
1580 GOTO L65
1590 L55: Y3z=EXP(-Z3)
1600 L65: IF (Z4<200) THEN GOTO L56
1610 Y4z=0
1620 GOTO L66
1630 L56: Y4z=EXP(-Z4)
1640 L66: Y3=Aa0-Fj*Y1z
1650 Y4=FNH(Aa1,1.,Aa2)
1660 Y5=Y1*Y1z
1670 Aa(J,1)=Y2*((Y3/Y4)-Y5) !TOP OF JUNCTION
1680 Aa3=Sn*Ln/Dn
1690 Aa4=Alpha*Ln
1700 Aa5=Hp/Ln
1710 Aa6=Aa4-Aa3
1720 Y6=Aa4/(Aa4*Aa4-1)
1730 Y7=Aa6*Y4z
1740 Fj=FNJ(Aa3,1.,Aa5)
1750 Y7=Y7+Fj
1760 Y8=FNH(Aa3,1.,Aa5)
1770 Aa(J,2)=Y6*Y2z*(Aa4-Y7/Y8)
1780 Aa(J,3)=Y1z*(1.-Y3z)
1790 Aa(J,4)=Aa(J,1)+Aa(J,2)+Aa(J,3)
1800 NEXT J
1810 !*****

```

```

1820 !
1830 !      GRAPHICS FOR SPECTRAL RESPONSE CURVE
1840 !
1850 !*****
1860 GINIT
1870 GRAPHICS ON
1880 DUMP DEVICE IS 701      !FOR LARGE GRAPHS USE 701,EXPANDED
1890 WINDOW -.25,1.60,-.1,1.1 ! XMIN,XMAX,YMIN,YMAX FOR GRAPH
1900 FRAME                  ! DRAW A BOX AROUND GRAPH
1910 AXES .10,.10,0.,0,5,2,6 !XTIC,YTIC,ORIGIN,POSITION OF MAJOR TICS
1920 !*****
1930 !
1940 ! NOW TO LABEL THE AXES---X AXIS FIRST
1950 !
1960 !*****
1970 CSIZE 4
1980 LORG 6
1990 FOR X_label=0. TO 1.5 STEP .5
2000 MOVE X_label,-.045
2010 LABEL X_label
2020 NEXT X_label
2030 LORG 8
2040 FOR Y_label=0 TO 1 STEP .1
2050 MOVE -.03,Y_label
2060 LABEL Y_label
2070 NEXT Y_label
2080 LORG 6
2090 !*****
2100 !
2110 ! LABEL THE AXES WITH NAMES
2120 !
2130 !*****
2140 DEG                      !THIS SETS ANGLES TO DEGREES
2150 LDIR 0                  !ZERO ROTATION FOR DIRECTION OF LABELS
2160 MOVE (.75),-.01
2170 LABEL "WAVELENGTH(MICRONS)" !WRITE LABEL IN CENTER OF AXES
2180 LDIR 90                ! GET READY FOR A 90 DEG ROTATION OF LABEL
2190 MOVE -.18,.5          ! MOVE TO CENTER OF Y AXIS
2200 LABEL "SPECTRAL RESPONSE"
2210 !*****
2220 !
2230 !      PLOT THE SPECTRAL RESPONSE CURVES FOR
2240 !
2250 !      CONTRIBUTION: FROM FRONT;BACK;DEPLETION REGION;TOTAL
2260 !
2270 !*****
2280 FOR I=1 TO 4
2290   FOR J=1 TO 50
2300     Z(J)=Aa(J,I)
2310   NEXT J
2320   MOVE Xx(1),Z(1)
2330   FOR K=1 TO 50
2340     DRAW Xx(K),Z(K)
2350   NEXT K
2360 NEXT I
2370 LDIR 0
2380 CSIZE 3.8
2390 LORG 3
2391 MOVE -.15,-.05
2392 LABEL "Si"

```

```

010 J01=(Q*Dp/Lp)*(Ni*Ni/Nd)*(Z1/Z2)
020 J02=(Q*Dn/Ln)*(Ni*Ni/Na)*(Z3/Z4)
030 J0=J01+J02
040 Z3=Alpha*Lp
050 Z4=Alpha*Ln
060 R1=Q*Phi0*(1-Re)*Z3/(Z3*Z3-1)
070 R2=Aa1+Z3
080 R3=EXP(-Alpha*Xj)
090 Jp=R1*((R2-R3*Z1)/Z2)-Z3*R3)
100 R4=EXP(-Alpha*(Xj+W))
110 R5=Q*Phi0*(1-Re)*Z4*R4/(Z4*Z4-1)
120 R6=FNCosh(X2)
130 Yy1=Alpha*Hp
140 Yy2=0
150 IF (Yy1<220) THEN Yy2=EXP(-Yy1)
160 R7=Z4*Yy2
170 R8=Z4-(Aa3*(R6-Yy2)+FNSinh(X2)+R7)/FNH(Aa3,1.,X2)
180 Jn=R5*R8
190 Jdr=Q*Phi0*(1-Re)*EXP(-Alpha*Xj)*(1.-EXP(-Alpha*W))
200 Jsc=Jp+Jn+Jdr
210 !*****
220 !
230 ! VOLTAGE GOES FROM 0 TO ITS OPEN CIRCUIT VALUE
240 ! AND WE CALCULATE THE CORRESPONDING CURRENT
250 !*****
260 I=Jsc
270 Begin: X1x=V+I*Rs
290 Jrec=FNRec(Ni,W,X1x,Kb,T,Vbi,Tn,Tp)
300 IF (Rs=0) THEN GOTO Skiper
310 I=FNN1(Rs,V,T,J0,Jsc,Jrec,Kb,Rsh)
320 GOTO End
330 Skiper: I=Jsc-J0*(EXP(V/(Kb*T))-1)-Jrec-V/Rsh
380 End: ! SAVE RESULTS FOR PLOTTING
390 Volts(Icount)=V*1000. !MILLIVOLTS
400 Amps(Icount)=I*1000. !MILLIAMPS
410 P=V*I !POWER IN WATTS
420 IF (P>Pmax) THEN Pmax=P
430 IF (Amps(Icount)>Max) THEN Max=Amps(Icount)
440 IF (Amps(Icount)<0) THEN GOTO Stop
450 GOTO Start
460 Stop: !GRAPH CURRENT-VOLTAGE RELATIONSHIP
470 Amps(Icount)=0
480 !*****
490 !
500 ! GRAPH OF CURRENT VOLTAGE RELATIONSHIP FOLLOWS
510 !
520 !*****
530 GCLEAR
540 CSIZE 4
550 Maxy=1.2*Max
560 Y1=DROUND(.1*Maxy,2)
570 Dely=Maxy/10
580 WINDOW -150,1000,-Y1*1.6,Maxy+.2*Y1
590 FRAME
600 DEG
610 AXES 10,(Dely).0,0,10,2,6
620 ! LABEL AXES
630 LDOR 6
640 LDIR -90
650 FOR X_label=100 TO 1000 STEP 100

```

```

8660 MOVE X_label,-12*Y1/16
8670 LABEL X_label
8680 NEXT X_label
8690 LORG 8
8700 LDIR 0
8710 FOR Y_label=0 TO Maxy STEP Dely
8720 MOVE 0,Y_label
8730 LABEL DROUND(Y_label,2)
8740 NEXT Y_label
8750 LORG 5
8760 MOVE 350,-Y1*1.3
8770 LDIR 0
8780 LABEL "MILLIVOLTS"
8790 MOVE -100,Maxy/2
8800 LDIR 90
8810 LABEL "MILLIAMPS"
8820 CSIZE 4
8830 LDIR 0
8840 MOVE Volts(1),Amps(1)
8850 FOR Ij=1 TO Icount
8860 DRAW Volts(Ij),Amps(Ij)
8870 NEXT Ij
8880 CSIZE 4
8890 Xpo=300
8900 Ypo=.7
8910 LORG 5
8911 MOVE 400,.95*Maxy
8912 LABEL "CONVENTIONAL Si PHOTOCONVERTER"
8920 MOVE Xpo,(Ypo)*Maxy
8930 LABEL "Rs=";Rs
8940 MOVE Xpo,(Ypo-.04)*Maxy
8950 LABEL "T =" ;DROUND(T-273,4);"DEG C"
8960 MOVE Xpo,(Ypo-.08)*Maxy
8970 LABEL "Sn=";Sn;" Ln=";DROUND(Ln,5)
8980 MOVE Xpo,(Ypo-.12)*Maxy
8990 LABEL "Sp=";Sp;" Lp=";DROUND(Lp,5)
9000 MOVE Xpo,(Ypo-.16)*Maxy
9010 LABEL "Na=";Na;" Mun=";DROUND(Mun,5)
9020 MOVE Xpo,(Ypo-.2)*Maxy
9030 LABEL "Nd=";Nd;" Mup=";DROUND(Mup,5)
9040 MOVE Xpo,(Ypo-.24)*Maxy
9050 LABEL "Xj=";Xj
9060 MOVE Xpo,(Ypo-.28)*Maxy
9070 LABEL "H =" ;H
9080 MOVE Xpo,(Ypo-.32)*Maxy
9090 LABEL "Rsh =" ;Rsh
9100 MOVE Xpo,(Ypo-.36)*Maxy
9110 LABEL "Wo =" ;Wo
9120 MOVE Xpo,(Ypo-.4)*Maxy
9130 LABEL "Pout=";DROUND(Pmax,5)
9140 MOVE Xpo,(Ypo-.44)*Maxy
9150 LABEL "Eff=" ;DROUND(100*Pmax/(Wo*1000),5)
9160 MOVE Xpo,(Ypo-.48)*Maxy
9170 LABEL "Alpha=";Alpha
9180 MOVE Xpo,(Ypo-.52)*Maxy
9190 LABEL "Lambda=";Lambda
9200 MOVE Xpo,(Ypo-.56)*Maxy
9210 LABEL "Jsc=";Jsc
9220 !*****
9230 !
9240 ! PAUSE LOOK AT GRAPH IF YOU LIKE IT TYPE --- DUMP GRAPHICS

```

```

1250 !
1260 !*****
1270 !
1280 !           TYPE   GCLEAR   TO CLEAR THE SCREEN
1290 !
1300 !*****
1310 PAUSE
1320 GCLEAR      !CLEARS THE GRAPHICS SCREEN
1330 LORG 5
1340 CSIZE 9
1350 WINDOW 0,100,0,100
1360 MOVE 50,50
1370 LABEL "THE PROGRAM IS OVER"
1380 FOR I=1 TO 3000
1390 NEXT I
1400 GCLEAR -
1410 END
1420 !*****
1430 def FNAbsorp(Nsi,Esi(*),Asi(*),Energ)
1440 I=0
1450 IF (Energ<Esi(1)) THEN Alpha=0
1460 IF (Energ<Esi(1)) THEN Stop3
1470 St3: I=I+1
1480 IF (I>Nsi) THEN Last3
1490 IF (Esi(I)<=Energ) AND (Esi(I+1)>=Energ) THEN Ratio3
1500 GOTO St3
1510 Last3: Alpha=Asi(Nsi)
1520 GOTO Stop3
1530 Ratio3: Alpha=Asi(I)+(Asi(I+1)-Asi(I))*(Energ-Esi(I))/(Esi(I+1)-Esi(I))
1540 Stop3: !
1550 RETURN Alpha
1560 FNEND
1570 !*****
1580 def FNJ(A1,A3,A2)
1590 Y=A1*FNCosh(A2)+A3*FNSinh(A2)
1600 RETURN Y
1610 FNEND
1620 !*****
1630 def FNCosh(X)
1640 Y=(EXP(X)+EXP(-X))/2.
1650 RETURN Y
1660 FNEND
1670 !*****
1680 def FNSinh(X)
1690 Y=(EXP(X)-EXP(-X))/2.
1700 RETURN Y
1710 FNEND
1720 !*****
1730 def FNH(A,B,C)
1740 Y=A*FNSinh(C)+B*FNCosh(C)
1750 RETURN Y
1760 FNEND
1770 !*****
1780 DEF FN Mun(Nd,T,A0,A1,A2,A3)
1790 Bb1=A1*T*T/(Nd^(2./3.))
1800 D=Nd*Bb1*(1.-.5*Bb1)
1810 X1=A0*(T^1.5)/D
1820 X2=A2*EXP(-A3*LOG(T))
1830 R=1./X2+1./X1
1840 RETURN 1./R

```

```

850 FNEND
860 !*****
870 def FNMup(Na,T,B0,B1,B2,B3)
880 X1=B2*EXP(-B3*LOG(T))
890 Bb1=B1*T*T/(Na^(2./3.))
900 D=Na*Bb1*(1.-.5*Bb1)
910 X2=B0*(T^1.5)/D
920 R=1./X2+1./X1
930 RETURN 1./R
940 FNEND
950 !*****
960 def FNRec(Ni,W,V,Kb,T,Vbi,Tn,Tp)
970 J1=(1.6E-19)*Ni*W*PI*FNSinh(V/(2*Kb*T))
980 J2=SQR(Tp*Tn)*(Vbi-V)/(Kb*T)
990 Jrec=J1/J2
000 RETURN Jrec
010 FNEND
020 DEF FNN1(Rs,V,T,Io,Isc,Irec,Kb,Rsh) !NONLINEAR EQ SOLVER
030 Ib=Isc-Irec-V/Rsh+Io
040 Kbtg=Kb*T
050 U=.9999
060 Starter: U1=1+Rs/Rsh
070 F=Ib*U*U1-Ib+Io*EXP((V+U*Ib*Rs)/Kbtg)
080 Fp=Ib*U1+Io*EXP((V+Ib*U*Rs)/Kbtg)*(Rs*Ib/Kbtg)
090 U1=U-F/Fp
100 Error=ABS(U1-U)
110 IF (Error<1.0E-6) THEN GOTO Ender
120 U=U1
130 GOTO Starter
140 Ender: RETURN U1*Ib
150 FNEND

```




FIGURE A1. Representative output from the program "CONVEN" illustrating spectral response and current voltage relationship for conventional photoconverter.

## APPENDIX B

### BASIC COMPUTER PROGRAM FOR ONE-DIMENSIONAL VERTICAL JUNCTION PHOTOCONVERTER



```

10 OPTION BASE 1
20 !*****
30 !
40 ! PROGRAM VJSCP
50 !
60 ! VERTICAL JUNCTION SOLAR CELL PROGRAM
70 !
80 REM VERTICAL JUNCTION SOLAR CELL PROGRAM CONSTANT TEMPERATURE
90 !
100 !*****
110 DIM Volts(100),Amps(100),Yisc(201),Yidark(201),Yrec(201)
120 DIM Aa(100,3),Z(100),X(100),Xx(100)
130 DIM Esi(20),Asi(20)
140 !*****
150 !
160 ! Si ENERGY(EV), ABSORPTION COEFFICIENT (CM-1) DATA
170 !
180 !*****
190 Nsi=20
200 FOR I=1 TO Nsi
210 READ Esi(I),Asi(I)
220 NEXT I
230 DATA 1.1,1,1.15,10,1.24,100,1.378,350,1.46,950,1.77,2000
240 DATA 2.067,4500,2.48,1E4,2.76,2E4,3.1,5E4,3.26,1E5
250 DATA 3.5,1E6,3.6,1.1E6,4,1.8E6,4.2,2.5E6,5,1.9E6,5.2,2E6
260 DATA 6,1.5E6,8,1.3E6,10,1.1E6
270 !*****
280 GINIT !INITIALIZE GRAPHICS
290 GRAPHICS ON
300 DUMP DEVICE IS 701
310 WINDOW 0,100,0,100
320 LORG 5
330 MOVE 50,50
340 LABEL "SPECTRAL RESPONSE"
350 !*****
360 !
370 ! SOLAR CELL PARAMETERS
380 !
390 !*****
400 Parameters: !
410 Wo=1.0 !LASER POWER IN KW/CM2
420 !TEMPERATURE CALCULATED BELOW BASED ON THIS POWER
430 Re=.05 !REFLECTION COEFFICIENT
440 Lambda=1.06 !WAVELENGTH IN MICRONS
450 Rs=0. ! SERIES RESISTANCE IN OHMS
460 Rsh=1.0E+6 !SHUNT RESISTANCE IN OHMS
470 Sn=0. ! SURFACE RECOMBINATION VELOCITIES CM/S
480 Sp=0.
490 Na=1.25E+17 ! DOPING DENSITIES CM-3
500 Nd=5.0E+19 !DOPING DENSITY CM-3 IN N REGION
510 B1=7.1E+15 ! CONSTANT FOR Si LIFETIMES SEE Taun AND Taup BELOW
520 Eggo=1.16 !FOR Si;USE 1.522 FOR GaAs ;USE .741 FOR Ge
530 Alphao=7.02E-4 !FOR Si;USE 5.8E-4 FOR GaAs;USE 4.56E-4 FOR Ge
540 Betao=1108. !FOR Si;USE 300 FOR GaAs; USE 210 FOR Ge
550 ! SOLAR CELL DIMENSIONS
560 A=1.0 !CM Y=A IS TOP, Y=0 IS BOTTOM
570 B=.002 !CM X=0 IS LEFT, X=B IS RIGHT SIDE OF SOLAR CELL
580 Xj=.001 !CM JUNCTION LINE AT X=Xj
590 IF (Xj>B) THEN PRINT "PLEASE MAKE JUNCTION INSIDE OF CELL-THANK YOU"
600 Kback=1.5 !WATTS/CM-DEG C THERMAL CONDUCTIVITY FOR Si

```

```

510 Hh2=100. !WATTS/CM2-DEG C HEAT TRANSFER COEFFICIENT
520 Tpipe=20. !TEMP DEG C OF HEAT PIPE
530 Absorpo=1.6955E+3 !ABSORPTION COEFFICIENT FOR Si SEE Alpha BELOW
540 Xkk=1.2E-3 !CONSTANT FOR ABSORPTION COEFFICIENT SEE Dele BELOW
550 Xkko=1.2E-3
560 Xkk1=1.4
570 Nia0=4.9E+15 !INTRINSIC CARRIER DENSITY COEFFICIENT SEE Ni BELOW
580 Nia1=1.610 !ANOTHER CONSTANT FOR Si INTRINSIC CARRIER DENSITY
590 Epso=11.6 !PERMITIVITY FOR Si DIMENSIONLESS
700 !CONSTANTS FOR Si MOBILITY Mun
710 Ab0=55.02 ! FOR GaAs USE 5076.11 ; FOR Ge USE 458.68
720 Ab1=5.72E-9 ! FOR GaAs USE 6.03E-88 ; FOR Ge USE 7.92E-9
730 Ab2=2.49E+9 ! FOR GaAs USE 2.13E6 ; FOR Ge USE 6.08E7
740 Ab3=2.5 ! FOR GaAs USE 1.0 ; FOR Ge USE 1.66
750 !CONSTANTS FOR Si MOBILITY Mup
760 Ba0=54.46 ! FOR GaAs USE 37.33 ; FOR Ge USE 3140.27
770 Ba1=6.76E-9 ! FOR GaAs USE 8.51E-9 ; FOR Ge USE 1.79E-7
780 Ba2=2.93E+9 ! FOR GaAs USE 6.05E7 ; FOR Ge USE 1.18E9
790 Ba3=2.7 ! FOR GaAs USE 2.1 ; FOR Ge USE 2.33
800 !*****
810 !
820 ! END OF SOLAR CELL PARAMETERS
830 !
840 !*****
850 !APPROXIMATE THE TEMPERATURE
860 T=273+Tpipe+1000*(1-Re)*Wo/Hh2
870 Egt=Eggo-Alphao*T*T/(T+Betao)
880 T0=300 !CONSTANT REFERENCE TEMPERATURE
890 Engo=1.2402/Lambda
900 IF (Engo<=1.7) THEN Xkk=(1.3*Engo-1)*1.0E-3
910 Dele=Xkk*(T-T0)
920 E=Engo+Dele
930 Alpha=FNAbso(Nsi,Esi(*),Asi(*),E)
940 Ff2=0
950 IF (Alpha*A<700) THEN Ff2=EXP(-Alpha*A)
960 T=Tpipe+Wo*((1-Re)*1000/Kback)*(Kback/Hh2-1./Alpha)*(1-Ff2)
970 IF (T<Tpipe) THEN T=Tpipe
980 T=T+273 ! THIS IS THE TEMPERATURE DEG K DUE TO POWER Wo
990 Kb=8.6172E-5 ! BOLTZMANN'S CONSTANT EV/K
1000 Q=1.6E-19 ! ELECTRON CHARGE COULOMBS
1010 Tno=1.86E-4 !LIFETIME CONSTANT
1020 Tpo=3.52E-3
1030 Taun=Tno/(1.+Na/B1) !CALCULATION OF LIFETIMES
1040 Taup=Tpo/(1.+Nd/B1)
1050 Ego=Eggo-(Alphao)*T0*T0/(T0+Betao) ! 1.12 EV AT 300 DEG K
1060 Egt=Eggo-(Alphao)*T*T/(T+Betao) !BANDGAP IN EV
1070 Phi0=Wo*Lambda*5.03306E+21 !PHOTONS/CM2-S
1080 Engo=1.2402/Lambda !ENERGY IN EV
1090 IF (Engo<=1.7) THEN Xkk=(1.3*Engo-1)*1.0E-3 !SEE ABOVE FOR Xkk
110 Dele=Xkk*(T-T0) ! SHIFT IN BANDGAP DUE TO TEMP
111 E=Engo+Dele
112 Alpha=FNAbso(Nsi,Esi(*),Asi(*),E) ! ABSORPTION COEFFICIENT CM-1
113 Icount=0 !INITIALIZE COUNTER
114 Xstep=.01 !VOLTAGE STEP SIZE
115 IF (A>.02) THEN Delz=A/200 !DEPTH BELOW SURFACE STEP SIZE
116 IF (A<=.02) THEN Delz=.02/200
117 Max=0 ! DUMMY MAXIMUM CURRENT
118 Delvo=.05 !CHANGE IN VOLTAGE
119 V=-Delvo !INITIALIZE VOLTAGE
200 !*****

```

```

10!          SPECTRAL RESPONSE CURVES
20! *****
30 Kbtg=Kb*T          !BOLTZMANN'S CONSTANT*TEMP
40 Egt=Eggo-Alphao*T*T/(T+Betao) !BANDGAP
50 Tn=Tno/(1+Na/B1)   !LIFETIME
60 Tp=Tpo/(1+Nd/B1)
70 Mun=FNmun(Na,T,Ab0,Ab1,Ab2,Ab3) !MOBILITIES
80 Mup=FNmup(Nd,T,Ba0,Ba1,Ba2,Ba3)
90 Dn=Kbtg*Mun        !DIFFUSION COEFFICIENTS
100 Dp=Kbtg*Mup
110 Phio=Wo*Lambda*5.0330E+21      !PHOTONS/CM2-S
120 Ni=Nia0*Nia1*(T^1.5)*EXP(-Egt/(Kbtg*2)) !INTRINSIC CARRIER DENSITY
130 Vbi=Kbtg*LOG(Na*Nd/(Ni*Ni))    !BUILT IN VOLTAGE
140 W2=(2.*Epso*(8.85E-14)/Q)*Vbi*(1./Nd+1./Na) !SQUARE OF DEPLETION WIDTH
150 W=SQR(W2)                    !DEPLETION WIDTH
160 Lp=SQR(Dp*Tp)                !DIFFUSION LENGTH
170 Ln=SQR(Dn*Tn)
180 Xn=W*Na/(Na+Nd)              !DISTANCE INTO N REGION
190 Xp=W-Xn                       !DISTANCE INTO P REGION
200 U1=(Xj-Xp)/Ln
210 U2=Dn/Ln
220 U4=Dp/Lp
230 F1=FNRatio(U1,Sn,U2)
240 U3=(B-Xj-Xn)/Lp
250 F2=FNRatio(U3,Sp,U4)
260 Pin=B*Wo*1000                !POWER INTO CELL B by 1 CM (WATTS)
270 Imax=0
280 Kmax=60
290 FOR J=1 TO Kmax
300 X(J)=1.000+(J-1)*.03          ! ENERGY IN EV
310 Xx(J)=1.2402/X(J)             !WAVELENGTH IN MICRONS
320 Phio=Wo*Xx(J)*5.033E+21
330 Ener=X(J)
340 IF (Ener>1.7) THEN Xkk=Xkko
350 IF (Ener<1.7) THEN Xkk=(Xkk1*Ener-1)*1.0E-3
360 Del=Xkk*(T-T0)
370 E=Ener+Del
380 Alpha=FNAbso(Nsi,Esi(*),Asi(*),E) !ABSORPTION COEFFICIENT
390 !PRINT "ALPHA =";Alpha
400 Zz1=Alpha*A
410 Yyy1=0
420 IF (Zz1<700) THEN Yyy1=EXP(-Zz1) !NO NUMERICAL INTEGRATION
430 In=-Ln*F1*Q*Phio*(1-Re)*(1-Yyy1) !CURRENT FROM RIGHT SIDE AMPS
440 Ip=-Lp*F2*Q*Phio*(1-Re)*(1-Yyy1) !CURRENT FROM LEFT SIDE AMPS
450 Isr=(In+Ip)/Pin
460 IF (Isr>Imax) THEN Imax=Isr
470 !PRINT In,Ip                  !OPTIONAL PRINT STATEMENT
480 Aa(J,1)=In/Pin                !SPECTRAL RESPONSE FROM RIGHT,
490 Aa(J,2)=Ip/Pin                !LEFT
500 Aa(J,3)=Isr                   !TOTAL RESPONSE
510 NEXT J
520 !*****
530 !
540 !          PLOT SPECTRAL RESPONSE CURVES
550 !
560 !*****
570 GCLEAR
580 WINDOW -.25,1.3,-.2,1.1
590 FRAME
600 !*****

```

```

1810 !      DRAW AND LABEL AXES
1820 !*****
1830 AXES .1,.1,0.,0,5,5,6
1840 CSIZE 4
1850 LORG 6
1860 FOR X_label=.5 TO 1.5 STEP .5
1870 MOVE X_label,-.0125
1880 LABEL X_label
1890 NEXT X_label
1900 LORG 8
1910 FOR Y_label=0 TO 1. STEP .1
1920 MOVE (-.005),Y_label
1930 LABEL Y_label
1940 NEXT Y_label
1950 ! *****
1960 !      PUT LABELS ON THE AXES
1970 !*****
1980 LORG 6
1990 DEG
2000 LDIR 0
2010 MOVE .75,-.1
2020 LABEL "WAVELENGTH(MICRONS)"
2030 LDIR 90
2040 MOVE -.19,.5
2050 LABEL "NORMALIZED SPECTRAL RESPONSE"
2060 !*****
2070 !
2080 !      DRAW THE SPECTRAL RESPONSE CURVES
2090 !
2100 !*****
2110 FOR I=1 TO 3
2120 FOR J=1 TO Kmax
2130 Z(J)=Aa(J,I)/Imax
2140 NEXT J
2150 MOVE Xx(1),Z(1)
2160 FOR K=1 TO Kmax
2170 DRAW Xx(K),Z(K)
2180 NEXT K
2190 NEXT I
2200 LDIR 0
2210 MOVE -.15,-.05
2220 LABEL "Si"
2230 !*****
2240 !
2250 !      PAUSE
2260 !      TYPE      DUMP GRAPHICS      FOR HARD COPY.
2270 !*****
2280 !
2290 PAUSE
2300 !
2310 !*****
2320 LDIR 0
2330 GCLEAR      !PUT A LABEL ON THE SCREEN
2340 WINDOW 0,100,0,100
2350 LORG 5
2360 MOVE 50,25
2370 LABEL "CURRENT-VOLTAGE"
2380 MOVE 50,20
2390 LABEL "CURVE IS NEXT"
2400 MOVE 50,15
2410 LABEL "CALCULATIONS TAKE 5 MINUTES "

```

```

2420! *****
2430!
2440 PRINT " Isc          Io          Irec          Volts" !OPTIONAL
2450!
2460! *****
2470! TEMPERATURE DISTRIBUTION FROM TOP TO BOTTOM AS FUNCTION OF Z IS CONSTANT
2480      Mun=FN Mun(Na,T,Ab0,Ab1,Ab2,Ab3) !MOBILITIES AS FUNCTION OF T
2490      Mup=FN Mup(Nd,T,Ba0,Ba1,Ba2,Ba3)
2500      Kbtg=Kb*T          !BOLTZMANN'S CONSTANT TIMES TEMPERATURE
2510      Egt=Eggo-(Alpha0)*T*T/(T+Beta0) !BANDGAP IN EV
2520      Dn=Kbtg*Mun        !DIFFUSION COEFFICIENT (CM**2)/S
2530      Dp=Kbtg*Mup
2540      Ni=(Nia0)*(Nia1)*(T^1.5)*EXP(-Egt/(Kbtg*2)) !INTRINSIC DENSITY
2550      Vbi=Kb*T*LOG(Na*Nd/(Ni*Ni)) !BUILT IN VOLTAGE (VOLTS)
2560      Lp=SQR(Dp*Taup) !DIFFUSION LENGTHS (CM)
2570      Ln=SQR(Dn*Taun)
2580      U2=Dn/Ln          !CM/S
2590      U4=Dp/Lp          !CM/S
2600      Ppo=Na            ! DOPING DENSITY      CM-3
2610      Nno=Nd            !                      CM-3
2620      Npo=Ni*Ni/Ppo     !                      CM-3
2630      Pno=Ni*Ni/Nno     !                      CM-3
2640      U7=Sp/U4          ! NO DIMENSIONS
2650      U9=Sn/U2          ! NO DIMENSIONS
2660! *****
2670!
2680!      CALCULATE CURRENT VOLTAGE RELATIONSHIP
2690!
2700! *****
2710 Pmax=0
2720 Maxy=0
2730 Phi0=Wo*Lambda*5.03306E+21 !PHOTONS/CM2-S
2740 Engo=1.2402/Lambda !ENERGY IN EV
2750 IF (Engo<=1.7) THEN Xkk=(1.3*Engo-1.)*1.0E-3 !SEE ABOVE FOR Xkk
2760 Dele=Xkk*(T-T0) ! SHIFT IN BANDGAP DUE TO TEMP
2770 E=Engo+Dele ! EV
2780 Alpha=FNABso(Nsi,Esi(*),Asi(*),E) ! ABSORPTION COEFFICIENT CM-1
2790 Start: V=V+Delvo ! (VOLTS)
2800      Icount=Icount+1
2810      Volts(Icount)=V*1.0E+3 ! MILLIVOLTS
2820      IF (Volts(Icount)>Max) THEN Max=Volts(Icount)
2830      Ii=0
2840 Again: Ii=Ii+1
2850      Z2=(Ii-1)*Delz ! CM
2860      Z1=Z2+Delz/2 ! CM
2870 IF (Z1>A) THEN GOTO Over
2880 W2=(2*Epso*(8.85E-14)/Q)*(Vbi-V)*(1./Nd+1./Na) ! CM**2
2890 W=SQR(W2) ! CM
2900 Xn=W*Na/(Na+Nd) ! CM
2910 Xp=W-Xn ! CM
2920 U1=(Xj-Xp)/Ln !NO DIMENSIONS
2930 F1=FN Ratio(U1,Sn,U2) !NO DIMENSIONS
2940 U3=(B-Xj-Xn)/Lp !NO DIMENSIONS
2950 F2=FN Ratio(U3,Sp,U4) !NO DIMENSIONS
2960 In=-Ln*F1 !CM
2970 Ip=-Lp*F2 !CM
2980 !SHORT CIRCUIT CURRENT
2990 Yy1=Alpha*Z1 !NO DIMENSIONS
3000 Yy2=0
3010 IF (Yy1<700) THEN Yy2=EXP(-Yy1)

```

```

3020 Isc=(In+Ip)*Phi0*(1-Re)*Alpha*Yy2*Q !AMPS/CM2
3030 Y8=FNA(V,Ni,W,Kb,T,Vbi,Taun,Taup)
3040 Irec=Y8 ! RECOMBINATION CURRENT AMPS/CM2
3050 !*****
3060 !
3070 !PRINT Y8;V;Ni;W;Kb;T;Vbi;Taun;Taup ! OPTIONAL PRINT STATEMENT
3080 !
3090 !*****
3110 R32=FNCur(U3,U7) ! NO DIMENSIONS
3120 Ipd=R32*Pno*Q*U4 ! AMPS/CM**2
3129 U8=(Xj-Xp)/Ln ! NO DIMENSIONS
3130 R33=FNCur(U8,U9) ! NO DIMENSIONS
3140 Ind=R33*Npo*Q*U2 ! AMPS/CM**2
3150 Io=(Ipd+Ind) ! AMPS/CM2
3160 Yisc(Ii)=Isc !AMPS/CM2
3170 Yidark(Ii)=Io !AMPS/CM2
3180 Yrec(Ii)=Irec !AMPS/CM2
3190 GOTO Again
3200 !*****
3210 !
3220 ! NUMERICAL INTEGRATION OF PREVIOUS RESULTS
3230 !
3240 !*****
3250 Over: Irec=0 !AMPS/CM2
3260 Isc=0 !AMPS/CM2
3270 Io=0 !AMPS/CM2
3280 Jki=Ii-2
3290 FOR Ii=1 TO Jki STEP 2
3300 Isc=Isc+(Delz/3.)*(Yisc(Ii)+4*Yisc(Ii+1)+Yisc(Ii+2))
3310 Io=Io+(Delz/3.)*(Yidark(Ii)+4*Yidark(Ii+1)+Yidark(Ii+2))
3320 Irec=Irec+(Delz/3.)*(Yrec(Ii)+4*Yrec(Ii+1)+Yrec(Ii+2))
3330 NEXT Ii
3340 !WE INTEGRATE OVER THE HEIGHT OF CELL--UNITS ARE NOW AMPS FOR ALL I'S
3350 !*****
3360 U6=V/(Kb*T) ! NO DIMENSIONS
3370 !*****
3380 !
3390 PRINT Isc;Io;Irec;V !OPTIONAL PRINT STATEMENT
3400 !
3410 !*****
3420 IF (Rs=0) THEN GOTO Skip !TEST TO SEE IF SERIES RESISTANCE IS ZERO
3430 I=FNN1(Rs,V,T,Io,Isc,Irec,Kb,Rsh) !NONLINEAR CALCULATION OF CURRENT
3440 GOTO Ready
3450 Skip: I=Isc-Io*(EXP(U6)-1)-Irec-V/(Rsh) ! TOTAL CURRENT AMPS
3460 Ready: !
3470 Amps(Icount)=I*1000 !SAVE FOR PLOTTING CONVERT TO MILLIAMPS
3480 P=I*V !POWER (WATTS)
3490 !*****
3500 ! FIND MAXIMUM POWER IN WATTS
3510 IF (P>Pmax) THEN Pmax=P
3520 IF (Amps(Icount)>Maxy) THEN Maxy=Amps(Icount)
3530 IF (I<0) OR (Vbi<V+Delvo) THEN GOTO Finish
3540 IF (V>=.45) THEN Delvo=Xstep
3550 GOTO Start
3560 Finish: Amps(Icount)=0
3570 !*****
3580 !
3590 !NOW DO SOME GRAPHICS
3600 !
3610 !*****

```

```

3620 GCLEAR
3630 DUMP DEVICE IS 701 ! BE SURE TO TURN THE PRINTING DEVICE ON
3640 Y1=.2*Maxy
3650 Ddy=Maxy/10
3660 WINDOW -(150),(1200),-(Y1),Maxy+Y1
3670 FRAME
3680 DEG
3690 AXES 10,(Ddy),0,0,10,2,6
3700 !*****
3710 !LABEL AXES X-AXIS FIRST
3720 !*****
3730 LORG C
3740 LDIR -90
3750 FOR X_label=0 TO 1200 STEP 100
3760 MOVE X_label,-7*Y1/16
3770 LABEL X_label
3780 NEXT X_label
3790 !*****
3800 !NOW LABEL Y-AXIS
3810 !*****
3820 LORG 8
3830 LDIR 0
3840 FOR Y_label=0 TO Maxy STEP Ddy
3850 MOVE 0,Y_label
3860 LABEL DROUND(Y_label,2)
3870 NEXT Y_label
3880 LORG 5
3890 !*****
3900 !
3910 !LABEL GRAPH
3920 !
3930 !*****
3940 MOVE (350),-(Y1*13/16)
3950 LDIR 0
3960 LABEL "MILLIVOLTS"
3970 MOVE -(130),(Maxy/2)
3980 LDIR 90
3990 LABEL "MILLIAMPS"
4000 CSIZE 4
4010 LDIR 0
4020 MOVE (-75),-(13*Y1/16)
4030 LABEL "Wo=";Wo
4040 !*****
4050 !
4060 ! DRAW THE CURVE
4070 !
4080 !*****
4090 MOVE Volts(1),Amps(1)
4100 FOR Ij=1 TO Icount
4110 DRAW Volts(Ij),Amps(Ij)
4120 NEXT Ij
4130 MOVE 600,1.05*Maxy
4140 LABEL "SILICON VERTICAL JUNCTION CELL"
4150 MOVE 600,.9*Maxy
4160 LABEL "Rs=";Rs
4170 MOVE 600,.85*Maxy
4180 LABEL "T =" ;DROUND(T,4)
4190 MOVE 600,.8*Maxy
4200 LABEL "Sn=";Sn
4210 MOVE 600,.75*Maxy

```

```

4220 LABEL "Sp=";Sp
4230 MOVE 500,.7*Maxy
4240 LABEL "Pout=";Pmax
4250 MOVE 500,.65*Maxy
4260 LABEL "Eff=";DROUND(Pmax*100/Pin,4)
4270 MOVE 500,.6*Maxy
4280 LABEL "Lambda=";Lambda
4290 MOVE 500,.55*Maxy
4300 LABEL "Jsc=";DROUND(Isc/B,2);" AMP/CM2"
4310 MOVE 500,.5*Maxy
4320 LABEL "Isc=";Isc
4330 MOVE 400,.45*Maxy
4340 LABEL "WIDTH=";B;" THICKNESS=";A
4350 MOVE 500,.4*Maxy
4360 LABEL "Xj=";Xj;" Voc=";Volts(Icount)
4370 MOVE 500,.35*Maxy
4380 LABEL "Ln=";DROUND(Ln,5);" Lp=";DROUND(Lp,5)
4390 MOVE 500,.3*Maxy
4400 LABEL "Mun=";DROUND(Mun,5);" Mup=";DROUND(Mup,5)
4410 MOVE 500,.25*Maxy
4420 LABEL "Na=";Na;" Nd=";Nd
4430 !*****
4440 !
4450 PAUSE      !TYPE 'DUMP GRAPHICS' IF YOU LIKE WHAT YOU SEE
4460 !
4470 !*****
4480 GCLEAR
4490 WINDOW 0,100,0,100
4500 LGOR 5
4510 MOVE 50,50
4520 LABEL "FINISHED WITH PROGRAM"
4530 FOR K=1 TO 5000      ! PAUSE AND THEN CLEAR THE SCREEN
4540 NEXT K
4550 GCLEAR
4560 end
4570 !*****
4580 !
4590 !           FUNCTIONS USED IN THE PROGRAM
4600 !
4610 !*****
4620 def FNMun(N3,T,Ab0,Ab1,Ab2,Ab3)      ! MOBILITY FUNCTION
4630 B1=Ab1*T*T/(N3^.66667)
4640 D=N3*B1*(1-.5*B1)
4650 X1=Ab0*(T^1.5)/D
4660 X2=Ab2*EXP(-Ab3*LOG(T))
4670 R=1./X2+1./X1
4680 RETURN 1./R
4690 FNEND
4700 !*****
4710 def FNMup(N4,T,Ba0,Ba1,Ba2,Ba3) ! MOBILITY FUNCTION
4720 X1=Ba2*EXP(-Ba3*LOG(T))
4730 B1=Ba1*T*T/(N4^.66667)
4740 D=N4*B1*(1-.5*B1)
4750 X2=Ba0*(T^1.5)/D
4760 R=1./X2+1./X1
4770 RETURN 1./R
4780 FNEND
4790 !*****
4800 def FNSinh(X)           !HYPERBOLIC SINE
4810 RETURN (EXP(X)-EXP(-X))/2
4820 FNEND

```



```

4830 !*****
4840 def FNCosh(X) !HYPERBOLOIC COSINE
4850 RETURN (EXP(X)+EXP(-X))/2
4860 FNEND
4870 !*****
4880 def FNRatio(X1,S,X2) !SPECIAL FUNCTION
4890 IF (X1>230) THEN GOTO Alternative
4900 F1n=(S/FNCosh(X1))-X2*FNTanh(X1)-S
4910 F1d=X2+S*FNTanh(X1)
4920 F1=F1n/F1d
4930 GOTO Next
4940 Alternative: F1=-1
4950 Next: !
4960 RETURN F1
4970 FNEND
4980 !*****
4990 def FNTanh(X) !HYPERBOLIC TANGENT
5000 IF (X1>230) THEN GOTO Next
5010 F1=(1.-EXP(-2.*X))/(1.+EXP(-2.*X))
5020 GOTO Ret
5030 Next: F1=1
5040 Ret: RETURN F1
5050 FNEND
5060 !*****
5070 def FNCur(A,B) ! ANOTHER RATIO TYPE FUNCTION
5080 F1=(B+FNTanh(A))/(B*FNTanh(A)+1.)
5090 RETURN F1
5100 FNEND
5110 !*****
5120 def FNN1(Rs,V,T,Io,Isc,Irec,Kb,Rsh) ! NONLINEAR EQUATION SOLVER
5130 Ib=Isc-Irec-V/Rsh+Io !INITIAL GUESS AT CURRENT
5140 Kbtg=Kb*T
5150 U=.9999
5160 Start1: U1=1+Rs/Rsh
5170 F=Ib*U*U1-Ib+Io*EXP((V+U*Ib*Rs)/Kbtg)
5180 Fp=+Ib*U1+Io*EXP((V+Ib*U*Rs)/Kbtg)*(Rs*Ib/Kbtg)
5190 U1=U-F/Fp !IMPROVED GUESS BY NEWTONS METHOD
5200 Error=ABS(U1-U) !ITERATE UNTIL ERROR IS LESS THAN E-6
5210 IF (Error<1.0E-6) THEN GOTO End
5220 U=U1 !UPDATE OLD GUESS
5230 GOTO Start1 !DO EVERYTHING AGAIN
5240 End: RETURN U1*Ib
5250 FNEND
5260 !*****
5270 def FNA(X,Ni,W,Kb,T,Vbi,Taun,Taup) !RECOMBINATION CURRENT
5280 Y1=(1.6E-19)*PI*Ni*W*FNSinh(X/(2*Kb*T))
5290 Y2=SQR(Taup*Taun)*(Vbi-X)/(Kb*T)
5300 Y=Y1/Y2
5310 RETURN Y
5320 FNEND
5330 !*****
5340 def FNB(X,Ni,W,Kb,T,Vbi,Taun,Taup) !DERIVATIVE OF ABOVE FUNCTION
5350 Y1=(1.6E-19)*PI*Ni*W*SQR(Taup*Taun)/(Kb*T)
5360 Y2=((Vbi-X)/(Kb*T))*FNCosh(X/(Kb*T))
5370 Y3=FNSinh(X/(Kb*T))
5380 Y4=Taun*Taun*((Vbi-X)/(Kb*T))^2
5390 Y=Y1*(Y2+Y3)/Y4
5400 RETURN Y*1000
5410 FNEND
5420 def FNAbso(Nsi,Esi(*),Asi(*),Energ)

```

```

5430 I=0
5440 IF (Energ<Esi(1)) THEN Alpha=0
5450 IF (Energ<Esi(1)) THEN Stop3
5460 St3: I=I+1
5470     IF (I>Nsi) THEN Last3
5480     IF (Esi(I)<=Energ) AND (Esi(I+1)>=Energ) THEN Ratio3
5490     GOTO St3
5500 Last3:     Alpha=Asi(Nsi)
5510     GOTO Stop3
5520 Ratio3: Alpha=Asi(I)+(Asi(I+1)-Asi(I))*(Energ-Esi(I))/(Esi(I+1)-Esi(I))
5530 Stop3:    !
5540 RETURN Alpha
5550 FNEND

```





FIGURE B1. Representative output from the program "VJSCP" illustrating spectral response and current-voltage relationship for vertical junction photoconverter.

APPENDIX C  
PROGRAM "SC3D" FOR SOLAR CELL  
3-DIMENSIONAL

```

PROGRAM SC3D(INPUT,OUTPUT,TAPE5=INPUT,TAPE6=OUTPUT,TAPE8)
C
C SC3D=SOLAR CELL 3 DIMENSIONAL (ILLUMINATED FROM TOP Z=0)
C
C GREEN'S FUNCTION SOLUTION - SYMMETRIC IN X AND Y
C
COMMON/BLK1/NDATA,ENERG(25),ALP(25)
COMMON/BLK2/POW,LAMBDA,NA,ND,B4,SN,SP,SO,S1,RE,RS,RSH,A,B,H
COMMON/BLK3/EP50,A0,A1,A2,A3,B0,B1,B2,B3,EGGO,ALPHA0,BETA0
COMMON/BLK4/XKK0,MUN,MUP,TAUN,TAUP,DN,DP,PHIO,NI,LN,LP,VBI
COMMON/BLK5/ETAN(200),XIN(200),XIP(200),ETAP(200)
COMMON/BLK6/PI,PI2,Q,ZJ,T,TO,NIA1,NIA2,TNO,TPO,W,ALPHA
COMMON/BLK7/NEIGV,KB,KBTG,XGRAPH
COMMON/BLK8/VOC,PMAX,EFF,ISC
DIMENSION ENERGS(25),ENERGGA(25),ENERGGE(25)
DIMENSION ALPS(25),ALPGA(25),ALPGE(25)
C
C
C
REAL LAMBDA,NA,ND,NIA1,NIA2,MUN,MUP,KB,KBTG,LN,LP,NI,ISC
REAL NIAGE1,NIAGE2,NIAS1,NIAS2,NIAGA1,NIAGA2
C
CALL PSEUDO
C
C NAMELIST VARIABLES
C
NAMELIST/PARAM/POW,NA,ND,LAMBDA,A,B,H,ZJ,T,RS,RSH,SN,SP,
1 SO,S1,NEIGV,ITYPE ,ISWITCH
C
C POW = LASER POWER (KW/CM2)
C NA=DOPING DENSITY (CM-3)
C ND=DOPING DENSITY (CM-3)
C LAMBDA=WAVELENGTH (MICRONS)
C A=HALF WIDTH OF X-DIRECTION ( -A .LE. X .LE. A)
C B=HALF WIDTH OF Y-DIRECTION ( -B .LE. Y .LE. B)
C H=DEPTH OF CELL IN Z-DIRECTION ( 0 .LE. Z .LE. H)
C ZJ=JUNCTION DEPTH FROM Z=0 (CM)
C T= TEMPERATURE (DEG K)
C RS=SERIES RESISTANCE OHMS
C RSH=SHUNT RESISTANCE OHMS
C SN=SURFACE RECOMBINATION VELOCITY TOP (CM/S)
C SP=SURFACE RECOMBINATION VELOCITY BOTTOM (CM/S)
C SO=SURFACE RECOMBINATION VELOCITY TOP SIDES
C S1=SURFACE RECOMBINATION VELOCITY BOTTOM SIDES
C NEIGV=NUMBER OF EIGENVALUES
C ITYPE = TYPE OF MATERIAL
C ITYPE = 1 FOR SILICON (SI)
C ITYPE = 2 FOR GALLIUM ARSENIDE (GAAS)
C ITYPE = 3 FOR GERMANIUM (GE)
C ISWITCH TURNS CONTOUR PLOT ON AND OFF
C ISWITCH=0 CONTOUR PLOT IS OFF
C ISWITCH=1 CONTOUR PLOT IS ON
C
C

```

C  
C  
C

# NOMINAL VALUES FOR NAMELIST VARIABLES

```

POW=.001          $ RE=.05
LAMBDA=1.06        $ ITYPE = 1
TO=300.           $ T=300.
RS=0.0            $ RSH=1.0E6
SN=1.0            $ SP=1.0
SO=1.0            $ S1=1.0
NA=1.25E17        $ ND=5.0E19
A=.5              $ B=.5
H=5.00E-4         $ ZJ=2.5E-4
NEIGV=10
ISWITCH=0

```

C  
C  
C

## SILICON PARAMETERS

```

NDATAS=20
DATA (ENERGS(K),K=1,8)/1.1,1.15,1.24,1.378,1.46,1.77,2.067,2.48/
DATA (ENERGS(K),K=9,15)/2.76,3.1,3.26,3.5,3.6,4.0,4.2/
DATA (ENERGS(K),K=16,20)/5.0,5.2,6.0,8.0,10.0/
DATA (ALPS(K),K=1,7)/1.0,10.0,100.0,350.0,950.0,2.E3,4.5E3/
DATA (ALPS(K),K=8,14)/1.0E4,2.0E4,5.0E4,1.0E5,1.0E6,1.1E6,1.8E6/
DATA (ALPS(K),K=15,20)/2.5E6,1.9E6,2.0E6,1.5E6,1.3E6,1.1E6/

```

## C CONSTANTS FOR MOBILITIES

```

DATA ASO,AS1,AS2,AS3/65.02,5.72E-9,2.49E9,2.5/
DATA BSO,BS1,BS2,BS3/54.46,6.76E-9,2.93E9,2.7/

```

## C CONSTANTS FOR BANDGAP AS FUNCTION OF TEMPERATURE

```

DATA EGGOS,ALPHAOS,BETAOS/1.16,7.02E-4,1108.0/

```

## C CONSTANTS FOR INTRINSIC CARRIER DENSITY

```

DATA NIAS1,NIAS2/4.9E15,1.61/

```

## C CONSTANTS FOR LIFETIMES

```

DATA TNOS,TPOS,B4/2.79E-4,3.52E-3,7.1E15/
EPSOS=11.6

```

## C GALLIUM ARSENIDE PARAMETERS

## C ABSORPTION COEFFICIENT CURVE FOR GAAS

```

NDATAGA=16
DATA (ENERGGA(K),K=1,8)/1.37,1.38,1.4,1.41,1.42,1.43,1.44,1.5/
DATA (ENERGGA(K),K=9,16)/1.6,1.8,2.0,2.4,3.0,3.5,4.0,4.5/
DATA (ALPGA(K),K=1,8)/18.,32.,119.,175.,2.5E3,4.5E3,6.E3,1.4E4/
DATA (ALPGA(K),K=9,16)/1.8E4,3.E4,4.E4,1.E5,2.E5,3.E5,4.E5,5.E5/

```

C

## C CONSTANTS FOR MOBILITIES

```

DATA AGAO,AGA1,AGA2,AGA3/5076.11,5.24E-9,6.43E5,1.0/
DATA BGAO,BGA1,BGA2,BGA3/1477.3,8.59E-8,6.05E7,2.1/

```

## C CONSTANTS FOR BANDGAP

```

DATA EGGOGA,ALPHGA,BETGA/1.519,5.4E-4,204./

```

## C CONSTANTS FOR INTRINSIC CARRIER DENSITY

```

DATA NIAGA1,NIAGA2/4.9E15,.0488844/

```

## C CONSTANTS FOR LIFETIMES

```

DATA TNOGA,TPOGA,B4/8.8179E-7,1.404E-7,7.1E15/
EPSOGA=13.1

```

## C GERMANIUM PARAMETERS

## C GERMANIUM SOLAR CELL PARAMETERS

```

NDATAGE=22

```

```

DATA  (ENERGGE(K),K=1,8)/.66,.68,.7,.73,.76,.79,.8,.81/
DATA  (ENERGGE(K),K=9,16)/.83,.85,.875,.9,.97,1.7,2.6,3./
DATA  (ENERGGE(K),K=17,22)/3.6,4.,4.4,5.0,6.0,8./
DATA  (ALPGE(K),K=1,8)/1.,10.,20.,60.,100.,600.,1.E3,4.E3/
DATA  (ALPGE(K),K=9,16)/5.E3,8.E3,8.5E3,9.E3,1.E4,1.E5,7.E5,8.E5/
DATA  (ALPGE(K),K=17,22)/1.E6,1.4E6,2.0E6,1.3E6,1.2E6,1.0E6/

C
DATA  AGE0,AGE1,AGE2,AGE3/458.68,7.92E-9,6.08E7,1.66/
DATA  BGEO,BGE1,BGE2,BGE3/3140.27,1.79E-7,1.18E9,2.33/
DATA  EGGGE,ALPHGE,BETGE/.741,4.77E-4,235./
DATA  NIAGE1,NIAGE2/4.9E15,.33313/
DATA  TNOGE,TPOGE,B4/2.1022E-5,2.1007E-5,7.1E15/
EPSOGE=16.

C
C READ IN ANY CHANGES TO THE ABOVE PARAMETERS
C   USE NAMELIST VARIABLES
C
C   LABEL GRAPHICS OUTPUT AND PRINTED OUTPUT
XGRAPH=0.
100  CONTINUE
    READ(5,PARAM)
    IF(EOF(5))600,601
600  WRITE(6,603)
603  FORMAT(1X,28HEND OF FILE ENCOUNTERED-STOP )
    STOP 1313
601  CONTINUE
C
    WRITE(6,110)
110  FORMAT(//)
    Q=1.6E-19
    XKKO=1.2E-3
    PI=3.1415926536
    PI2=PI*.5
    KB=8.6172E-5
    KBTG=KB*T
C   EPSO IS THE PERMITIVITY
XGRAPH=XGRAPH+1

C
C   SETUP PARAMETERS FOR CORRECT TYPE OF PHOTOCONVERTER MATERIALS
C   ITYPE = 1 (SI)
C   ITYPE = 2 (GAAS)
C   ITYPE = 3 (GE)
    IF(ITYPE .EQ. 1) WRITE(6,111)
    IF(ITYPE .EQ. 2) WRITE(6,112)
    IF(ITYPE .EQ. 3) WRITE(6,113)
111  FORMAT(1X,25HSILICON PHOTOCONVERTER ,/)
112  FORMAT(1X,35HGALLIUM ARSENIDE PHOTOCONERTER ,/)
113  FORMAT(1X,25HGERMANIUM PHOTOCONVERTER ,/)
    IF(ITYPE .EQ. 1) GO TO 10
    IF(ITYPE .EQ. 2) GO TO 20
C   GERMANIUM DATA GOES HERE
    NDATA=NDATAGE
    DO 40 I=1,NDATA
        ENERG(I)=ENERGGE(I)
40  ALP(I)=ALPGE(I)

```

```

      AO=AGEO $ CZAGE1 $ A2=AGE2 $ A3=AGE3
      BO=BGEO $ B1=BGE1 $ B2=BGE2 $ B3=BGE3
      EGGO=EGGOGE $ ALPHAO=ALPHGE $ BETAO=BETGE
      NIA1=NIAGE1 $ NIA2=NIAGE2
      TNO=TNOGE $ TPO=TPOGE
      EPSO=EPSOGE
      GO TO 30
10  CONTINUE
C    SILICON PARAMETERS
      NDATA=NDATAS
      DO 41 I=1,NDATA
      ENERG(I)=ENERGS(I)
41  ALP(I)=ALPS(I)
      AO=ASO $ A1=AS1 $ A2=AS2 $ A3=AS3
      BO=BSO $ B1=BS1 $ B2=BS2 $ B3=BS3
      EGGO=EGGOS $ ALPHAO=ALPHAOS $ BETAO=BETAOS
      NIA1=NIAS1 $ NIA2=NIAS2
      TNO=TNOS $ TPO=TPOS
      EPSO=EPSOS
      GO TO 30
20  CONTINUE
C    GALLIUM ARSENIDE PARAMETERS
      NDATA=NDATAGA
      DO 42 I=1,NDATA
      ENERG(I)=ENERGGA(I)
42  ALP(I)=ALPGA(I)
      AO=AGAO $ A1=AGA1 $ A2=AGA2 $ A3=AGA3
      BO=BGAO $ B1=BGA1 $ B2=BGA2 $ B3=BGA3
      EGGO=EGGOGA $ ALPHAO=ALPHGA $ BETAO=BETGA
      NIA1=NIAGA1 $ NIA2=NIAGA2
      TNO=TNOGA $ TPO=TPOGA
      EPSO=EPSOGA
30  CONTINUE
C    CALCULATE CONSTANTS
      CALL CONST
C    CALCULATE SPECTRAL RESPONSE
      CALL SPEC
C    CALCULATE I-V CURVE
      CALL IV(LAMBDA)
      WRITE(6,199)XGRAPH
199  FORMAT(T20,6HGRAPH ,F3.0 )
      WRITE(6,200)ISC,VOC,EFF,RSH,DN,NEIGV
200  FORMAT(/,T2,4HISC=,E12.5,T20,4HVOC=,E12.5,T40,4HEFF=,
1  E12.5,T60,4HRSH=,E12.5,T80,3HDN=,E12.5,T99,8HNEIGV = ,I5)
      WRITE(6,201)NA,ND,ZJ,S1,DP,NIA1
201  FORMAT(T2,3HNA=,E12.5,T20,3HND=,E12.5,T40,3HZJ=,E12.5,
1T60,3HS1=,E12.5,T80,3HDP=,E12.5,T99,7HNIA1 = ,E12.5)
      WRITE(6,202)TAUN,TAUP,LN,LP,TNO,NIA2
202  FORMAT(T2,5HTAUN=,E12.5,T20,5HTAUP=,E12.5,T40,3HLN=,E12.5,
1 T60,3HLP=,E12.5,T80,6HTNO = ,E12.5,T99,7HNIA2 = ,E12.5)
      WRITE(6,203)A,B,H,SO,TPO
203  FORMAT(T2,2HA=,E12.5,T20,2HB=,E12.5,T40,2HH=,E12.5,T60,3HSO=,
1 E12.5,T80,6HTPO = ,E12.5)
      WRITE(6,204)MUN,MUP,LAMBDA,POW
204  FORMAT(T2,4HMUN=,E12.5,T20,4HMUP=,E12.5,T40,7HLAMBDA=,F10.4,

```



```

1T60,4HPOW=,E12.5 )
  WRITE(6,205)T,RS,SN,SP
205  FORMAT(T2,2HT=,E12.5,T20,3HRS=,E12.5,T40,3HSN=,E12.5,
1    T60,3HSP=,E12.5)
  WRITE(6,206)W,PMAX,NI,VBI,ALPHA
206  FORMAT(T2,2HW=,E12.5,T20,5HPMAX=,E12.5,T40,3HNI=,E12.5,
1    T60,4HVBI=,E12.5,T80,6HALPHA=,E12.5,///)
C    TEST TO SEE IF CONTOUR PLOT IS WANTED
  IF(ISWITCH.EQ.1) CALL CONTOUR
  GO TO 100
  END
  SUBROUTINE CONTOUR
C    CONTOUR PLOTS OF CURRENT DENSITY
C    VALUES STORED IN AAA AND BBB ARRAYS
  DIMENSION AAA(20,20),BBB(20,20)
C  AAA IS 20X20 ARRAY OF CURRENT DENSITY VALUES AT X,Y AND Z=ZJ
C  BBB IS 20X20 ARRAY OF CURRENT DENSITY VALUES AT X,Y AND Z=ZJ+W
C
  N=20
C  CALCULATE JP AND STORE IN AAA. FIND AMAX AND AMIN VALUES FOR ARRAY
C
  CALL CDENAB(AAA,BBB,AMAX,AMIN,BMAX,BMIN,N)
C
C  FINC=0 $ NSET=0 $ NHI=-1 $ NDOT=0
C  CALCULATE JN AND STORE IN BBB. FIND BMAX AND BMIN VALURS FOR ARRAY
C
C
C  PLOT CONTOUR GRAPH OF AAA
  CALL CONREC(AAA,N,N,N,AMIN,AMAX,FINC,NSET,NHI,NDOT)
  CALL EZTRN
  CALL NFRAME
C  PLOT CONTOUR GRAPH OF BBB
  CALL CONREC(BBB,N,N,N,BMIN,BMAX,FINC,NSET,NHI,NDOT)
  CALL EZTRN
  CALL NFRAME
  RETURN
  END
  SUBROUTINE CDENAB(AAA,BBB,AMAX,AMIN,BMAX,BMIN,N)
C    CALCULATE CURRENT DENSITY AT X,Y COORDINATES SPECIFIED
C    PUT RESULTS IN AAA AND BBB ARRAYS
C    ALSO FIND MAX AND MIN VALUES OF ARRAY ELEMENTS
  DIMENSION AAA(20,20),BBB(20,20)
  COMMON/BLK2/POW,LAMBDA,NA,ND,B4,SN,SP,SO,S1,RE,RS,RSH,A,B,H
  COMMON/BLK4/XKKO,MUN,MUP,TAUN,TAUP,DN,DP,PHIO,NI,LN,LP,VBI
  COMMON/BLK6/PI,PI2,Q,ZJ,T,TO,NIA1,NIA2,TNO,TPO,W,ALPHA
C  CALCULATE JP(X,Y) AND STORE IN AAA
  REAL NA,ND
C  CALCULATE JN(X,Y) AND STORE IN BBB
  DELX=2.*A/FLOAT(N+1)
  AMIN=5.E5
  YWQ=ZJ+W
  AMAX=0.0
  DELY=2.*B/FLOAT(N+1)
  BMIN=5.0E5
  BMAX=0.0

```

```

DO 10 J=1,N
WRITE(6,99)
99 FORMAT(T5,1HX,T15,1HY,T25,2HZJ,T43,2HJP,T55,1HX,
1 T65,1HY,T75,4HZJ+W,T93,2HJN )
DO 20 I=1,N
X=-A+I*DELX
Y=-B+J*DELY
CALL SUMIJ(X,Y,XJP,XJN)
WRITE(6,100)X,Y,ZJ,XJP,X,Y,YWQ,XJN
100 FORMAT(3F10.4,E15.7,3X,3F10.6,E15.7 )
AAA(I,J)=4.0*Q*ALPHA*PHIO*(1-RE)*XJP
BBB(I,J)=4.0*Q*ALPHA*PHIO*(1-RE)*XJN
IF(AAA(I,J).GT.AMAX) AMAX=AAA(I,J)
IF(AAA(I,J).LT.AMIN) AMIN=AAA(I,J)
IF(BBB(I,J).GT.BMAX) BMAX=BBB(I,J)
IF(BBB(I,J).LT.BMIN) BMIN=BBB(I,J)
20 CONTINUE
10 CONTINUE
RETURN
END
SUBROUTINE SUMIJ(X,Y,XJP,XJN)
C SUM TERMS OF DOUBLE FOURIER SERIES FOR CURRENT
C DENSITIES JN AND JP
C
COMMON/BLK2/POW,LAMBDA,NA,ND,B4,SN,SP,SO,S1,RE,RS,RSH,A,B,H
COMMON/BLK4/XKKO,MUN,MUP,TAUN,TAUP,DN,DP,PHIO,NI,LP,VBI
COMMON/BLK5/ETAN(200),XIN(200),XIP(200),ETAP(200)
COMMON/BLK6/PI,PI2,Q,ZJ,T,TO,NIA1,NIA2,TNO,TPO,W,ALPHA
COMMON/BLK7/NEIGV,KB,KBTG,XGRAPH
C INSERT COMMON BLKS 2,4,5,6,7
C REAL NA,ND,MUN,MUP,NI,LP,NIA1,NIA2KB,KBTG
C
XJP=0.0
XJN=0.0
DO 10 I=1,NEIGV
DO 20 J=1,NEIGV
CALL TERNIJ(X,Y,I,J,FPIJ,FNIJ)
XJP=XJP+FPIJ
XJN=XJN+FNIJ
20 CONTINUE
10 CONTINUE
RETURN
END
SUBROUTINE TERNIJ(X,Y,I,J,FPIJ,FNIJ)
C I,J TERM OF DOUBLE FOURIER SERIES
C
COMMON/BLK2/POW,LAMBDA,NA,ND,B4,SN,SP,SO,S1,RE,RS,RSH,A,B,H
COMMON/BLK4/XKKO,MUN,MUP,TAUN,TAUP,DN,DP,PHIO,NI,LP,VBI
COMMON/BLK5/ETAN(200),XIN(200),XIP(200),ETAP(200)
COMMON/BLK6/PI,PI2,Q,ZJ,T,TO,NIA1,NIA2,TNO,TPO,W,ALPHA
COMMON/BLK7/NEIGV,KB,KBTG,XGRAPH
REAL NA,ND,LP,LP,NN,MUN,MUP,NI,NIA1,NIA2,KB,KBTG
G(Z)=FUN(-ALPHA*Z)
HH(AA,X)=(ALPHA*COS(AA*X)+AA*SIN(AA*X))/(ALPHA*ALPHA+AA*AA)
S(AA,X)=HH(AA,X)-G(2*X)*HH(AA,-X)

```

```

Y1(AA,X)=AA*SINH(X)+COSH(X)
YI4(AA,B,X)=AA*(B*COSH(X)+SINH(X)-B)
C   FPIJ (TOP REGION) SOLVE FOR JP
    UJPNOR=A+(SO*A*A/DP)*(COS(XIP(J))/XIP(J))**2
    XMUI=ETAP(I)/B
    XLAMJ=(XIP(J))/A
    DEN2=(XMUI**2)+(XLAMJ**2)
    GIJ2=LP*LP/(1.+LP*LP*DEN2)
    GIJ=SQRT(GIJ2)
    VIPNOR=B+(SO*B*B/DP)*(COS(ETAP(I))/ETAP(I))**2
    NP=SP*GIJ/DP
    XXT=ZJ/GIJ
    SPI1=B*SIN(ETAP(I))/ETAP(I)
    SPI2=A*SIN(XIP(J))/XIP(J)
    SPI3=COS(XLAMJ*X)/UJPNOR
    SPI4=COS(XMUI*Y)/VIPNOR
    SPI6=NP*SINH(XXT)+COSH(XXT)
    ZO=ALPHA*GIJ-1
    XO=(1-EXP(-XXT*ZO))/ZO
    X1=(1+(NP+1)*XO)/SPI6
    X2=X1-EXP(-ALPHA*ZJ)
    X3=1./(1+ALPHA*GIJ)
    GMN=X3*X2
    FPIJ=GIJ*SPI4*SPI3*SPI2*SPI1*GMN
C   CALCULATE FNIJ
    HP=H-(ZJ+W)
    UJNNOR=A+(S1*A*A/DN)*(COS(XIN(J))/XIN(J))**2
    VINNOR=B+(S1*B*B/DN)*(COS(ETAN(I))/ETAN(I))**2
    XMUI=ETAN(I)/B
    XLAMJ=XIN(J)/A
    DEN3=(XLAMJ**2)+(XMUI**2)
    SIJ2=LN*LN/(1.+LN*LN*DEN3)
    SIJ=SQRT(SIJ2)
    NN=SN*SIJ/DN
    XXB=HP/SIJ
    SNI1=B*SIN(ETAN(I))/ETAN(I)
    SNI2=A*SIN(XIN(J))/XIN(J)
    SNI3=COS(XLAMJ*X)/UJNNOR
    SNI4=COS(XMUI*Y)/VINNOR
    SNI5=YI4(SIJ,NN,XXB)
    Z1=EXP(-ALPHA*H)
    Z2=EXP(-ALPHA*(ZJ+W))
    Z3=(ALPHA*SIJ)**2
    Z4=1./(Z3-1)
    Z5=NN-ALPHA*SIJ
    Z6=NN*ALPHA*SIJ-1
    SNI6=COSH(XXB)+NN*SINH(XXB)
    HMN=Z4*(Z1*Z5+Z2*Z6*SINH(XXB)+Z2*(-Z5)*COSH(XXB))
    FNIJ=SIJ*SNI1*SNI2*SNI3*SNI4*HMN/SNI6
    RETURN
END
SUBROUTINE CONST
C   CALCULATE CONSTANTS
C
C CALCULATES OTHER CONSTANTS AND PARAMETERS FOR PROBLEM

```

```

C
C
COMMON/BLK2/POW,LAMBDA,NA,ND,B4,SN,SP,SO,S1,RE,RS,RSH,A,B,H
COMMON/BLK3/EP,SO,AO,A1,A2,A3,BO,B1,B2,B3,EGGO,ALPHAO,BETAO
COMMON/BLK4/XKKO,MUN,MUP,TAUN,TAUP,DN,DP,PHIO,NI,LN,LP,VBI
COMMON/BLK6/PI,PI2,Q,ZJ,T,TO,NIA1,NIA2,TNO,TPO,W,ALPHA
COMMON/BLK7/NEIGV,KB,KBTG,XGRAPH

C
C
REAL MUN,MUP,KBTG,KB,LAMBDA,NA,ND,NIA1,NIA2,NI,LN,LP

C
C
C CONVERT WAVELENGTH (MICRONS) TO ENERGY (EV)
ENER=1.2402/LAMBDA
C CALCULATE BANDGAP AS FUNCTION OF TEMPERATURE
EGT=EGGO-ALPHAO*T*T/(T+BETAO)
C CALCULATE ENERGY SHIFT DUE TO TEMPERATURE
DELE=XKKO*(T-TO)
E=ENER+DELE
C CALCULATE ABSORPTION COEFFICIENT
CALL ABSORP(E,ALPHA1)
ALPHA=ALPHA1
C CALCULATE LIFETIMES
TAUN=TNO/(1.+NA/B4)
TAUP=TPO/(1.+ND/B4)
C CALCULATE MOBILITIES
CALL MOBIL(Y1,Y2)
MUN=Y1 $ MUP=Y2
C CALCULATE DIFFUSION COEFFICIENTS
DN=KBTG*MUN $ DP=KBTG*MUP
C CALCULATE DENSITY OF PHOTONS IN PHOTON'S/CM2-S
PHIO=POW*LAMBDA*5.03306E21
C CALCULATE INTRINSIC CARRIER DENSITY
POWER=-EGT/(2.*KBTG)
CALL EXPON(POWER,ANS)
NI=NIA1*NIA2*(T**1.5)*ANS
C CALCULATE BUILT IN VOLTAGE
VBI=KBTG*ALOG(NA*ND/(NI*NI))
VOLTS=0.0
CALL WIDTH(VOLTS)
C CALCULATE DIFFUSION LENGTHS
LP=SQRT(DP*TAUP) $ LN=SQRT(DN*TAUN)
C CALCULATE ALL NECESSARY EIGENVALUES FOR PROBLEM
CALL ESET
RETURN
END
SUBROUTINE ABSORP(E,ALPHA)
C CALCULATE THE ABSORPTION COEFFICIENT FOR GIVEN ENERGY E
C
C
COMMON/BLK1/NDATA,ENERG(25),ALP(25)

C
C
C
I=0

```

```

      IF(E.LT.ENERG(1))GO TO 10
20  CONTINUE
      I=I+1
      IF(I.GT.NDATA)GO TO 30
      IF((ENERG(I).LE.E).AND.(ENERG(I+1) .GE. E))GO TO 40
      GO TO 20
40  ALPHA=ALP(I)+(ALP(I+1)-ALP(I))*(E-ENERG(I))/(ENERG(I+1)-ENERG(I))
      RETURN
10  ALPHA=0.
      RETURN
30  ALPHA=ALP(NDATA)
      RETURN
      END
      SUBROUTINE EXPON(X,ANS)
C      EXPONENTIAL TERM IN CASE ARGUMENTS GET LARGE
      IF(X.LT.-500) GO TO 10
      IF(X .GT. 700)GO TO 20
      ANS=EXP(X)
      RETURN
10  ANS=0.0
      RETURN
20  WRITE(6,30)
30  FORMAT(1X,29H ARG TOO LARGE, EXP FUNCTION )
      STOP 444
      END
      SUBROUTINE ESET
C      CALCULATE EIGENVALUES FOR ORTHOGONAL FUNCTIONS
C
C
      COMMON/BLK2/POW,LAMBDA,NA,ND,B4,SN,SP,SO,S1,RE,RS,RSH,A,B,H
      COMMON/BLK4/XKKO,MUN,MUP,TAUN,TAUP,DN,DP,PHIO,NI,LP,VBI
      COMMON/BLK5/ETAN(200),XIN(200),XIP(200),ETAP(200)
      COMMON/BLK6/PI,PI2,Q,ZJ,T,TO,NIA1,NIA2,TNO,TPO,W,ALPHA
      COMMON/BLK7/NEIGV,KB,KBTG,XGRAPH
C
      REAL MUN,MUP,NI,LP,NIA1,NIA2,KB,KBTG,NA,ND,LAMBDA
C
C  CALCULATE EIGENVALUES FOR TOP REGION X-DIRECTION
      R1=SO $ R2=DP $ R3=A $ N4=NEIGV
      CALL EIGEN(XIP,R1,R2,R3,N4)
C  CALCULATE EIGENVALUES FOR TOP REGION Y-DIRECTION
      R1=SO $ R3=B
      CALL EIGEN(ETAP,R1,R2,R3,N4)
C  CALCULATE EIGENVALUES FOR BOTTOM REGION
      R1=S1 $ R2=DN $ R3=A
      CALL EIGEN(XIN,R1,R2,R3,N4)
      RETURN
      END
      SUBROUTINE EIGEN(XX, S,D,H,N)
C      FINDS EIGENVALUES FOR EQUATION TAN(X) = C/X, C=CONSTANT
C
C
      COMMON/BLK6/PI,PI2,Q,ZJ,T,TO,NIA1,NIA2,TNO,TPO,W,ALPHA
C

```

ORIGINAL PAGE IS  
OF POOR QUALITY

```

      REAL NIA1,NIA2
C      DIMENSION XX(200)
      F(Z)=TAN(Z)-C/Z
      FP(Z)=C/(Z*Z)+1./((COS(Z)**2)
C SOLVES EQUATION X*TANX=C
C N MUST BE .LE. 200
      C=S*H/D
      IF(C.EQ.0) GO TO 1001
C GUESS AT FIRST ROOT
      X1=PI/4.
      M=1 $ IC=1
200  Y1=F(X1)
      IF(Y1.GT.0)GO TO 10
C Y1 IS NEGATIVE
      X2=X1
      Y2=Y1
5    X1=.5*(X2+(2*M-1)*PI/2)
      Y1=F(X1)
      IF(Y1.GT.0)GO TO 20
C Y1 IS NEGATIVE
      X2=X1
      Y2=Y1
      GO TO 5
10   X2=(M-1)*PI+.8*(X1-(M-1)*PI)
      Y2=F(X2)
      IF(Y2.LT.0)GO TO 20
      X1=X2
      Y1=Y2
      GO TO 10
20   X=(X1+X2)/2.
      Y=F(X)
      IF(ABS(Y) .LT. 1.0E-5)GO TO 100
      IF(Y .LT. 0) GO TO 30
      X1=X
      Y1=Y
      GO TO 20
30   X2=X
      Y2=Y
      GO TO 20
100  XX(IC)=X
      M=M+1 $ IC=IC+1
      X1=X+PI
      IF(IC.GT.N) GO TO 300
      GO TO 200
300  CONTINUE
      RETURN
1001 WRITE(6,234)
234 FORMAT(45HRECOMBINATION VELOCITY OF ZERO NOT ALLOWED )
      END

```

SUBROUTINE MOBIL(XMUN,XMUP)

C CALCULATE MOBILITIES IN N AND P REGIONS

C  
C  
C

```

COMMON/BLK2/POW,LAMBDA,NA,ND,B4,SN,SP,SO,S1,RE,RS,RSH,A,B,H
COMMON/BLK3/EP SO,AO,A1,A2,A3,BO,B1,B2,B3,EGGO,ALPHAO,BETAO
COMMON/BLK4/XKKO,MUN,MUP,TAUN,TAUP,DN,DP,PHIO,NI,LN,LP,VBI
COMMON/BLK6/PI,PI2,Q,ZJ,T,TO,NIA1,NIA2,TNO,TPO,W,ALPHA

```

```

REAL LAMBDA,NA,ND,MUN,MUP,NI,LN,LP,NIA1,NIA2

```

# MOBILITY OF ELECTRONS

```

RQ=2./3.
BB1=A1*T*T/(NA**RQ)
D=NA*BB1*(1.-.5*BB1)
X1=AO*(T**1.5)/D
ZZ=-A3*ALOG(T)
CALL EXPON(ZZ,ANS)
X2=A2*ANS
R=1./X2 + 1./X1
XMUN=1./R

```

# MOBILITY OF HOLES

```

ZZZ=-B3*ALOG(T)
CALL EXPON(ZZZ,ANS)
X1=B2*ANS
BB1=B1*T*T/(ND**RQ)
D=ND*BB1*(1.-.5*BB1)
X2=BO*(T**1.5)/D
R=1./X2 +1./X1
XMUP=1./R
RETURN
END

```

# SUBROUTINE WIDTH(VOLTS)

```

CALCULATE WIDTH OF DEPLETION REGION

```

```

COMMON/BLK2/POW,LAMBDA,NA,ND,B4,SN,SP,SO,S1,RE,RS,RSH,A,B,H
COMMON/BLK3/EP SO,AO,A1,A2,A3,BO,B1,B2,B3,EGGO,ALPHAO,BETAO
COMMON/BLK4/XKKO,MUN,MUP,TAUN,TAUP,DN,DP,PHIO,NI,LN,LP,VBI
COMMON/BLK6/PI,PI2,Q,ZJ,T,TO,NIA1,NIA2,TNO,TPO,W,ALPHA
COMMON/BLK7/NEIGV,KB,KBTG,XGRAPH

```

```

REAL KB,KBTG,LAMBDA,LN,LP,MUN,MUP,NA,ND,NI,NIA1,NIA2

```

```

ABC=(1./ND + 1./NA)
W2=(2.*EP SO*(8.85E-14)/Q)*(VBI-VOLTS)*ABC
W=SQRT(W2)
RETURN
END

```

# SUBROUTINE SPEC

```

CALCULATE SPECTRAL RESPONSE

```

```

COMMON/BLK3/EP SO,AO,A1,A2,A3,BO,B1,B2,B3,EGGO,ALPHAO,BETAO
CALCULATE SPECTRAL RESPONSE

```

```

DIMENSION WAV(200),SP(200),SN(200),SDR(200),SR(200)

```

```

C      I=0
90     I=I+1
      E=EGGO-.05+.025*(I-1)
      IF((E.GT.5.0).OR.(I.GT.200))GO TO 100
      WAV(I)=1.2402/E
      CALL SHORT(S1P,S1N,S1DR,E)
      SN(I)=S1N
      SP(I)=S1P
      SDR(I)=S1DR
      SR(I)=S1N+S1P+S1DR
      WRITE(6,80)I,E,WAV(I),S1P,S1N,S1DR
80     FORMAT(I5,5E15.5)
      GO TO 90
100    CONTINUE
      MAX=I-1
      I=I-1
C      NORMALIZE SPECTRAL RESPONSE
      XMAX=0.
      DO 110 K=1,MAX
      IF(SR(K).GT.XMAX)XMAX=SR(K)
110    CONTINUE
      DO 120 K=1,MAX
      SN(K)=SN(K)/XMAX
      SP(K)=SP(K)/XMAX
      SDR(K)=SDR(K)/XMAX
      SR(K)=SR(K)/XMAX
120    CONTINUE
C      PLOT GRAPH
      NXL=20 $ SX=10.          $ XOFF=.5
      NYL=28 $ SY=10.          $ YOFF=.5
      ISYM=0 $ XMIN=0.         $ XMAX=1.2
      IEC=0
      CALL GRAPH(WAV,SN,SP,SDR,SR,I)
      RETURN
      END
      SUBROUTINE GRAPH(WAV,SN,SP,SDR,SR,I)
C      GRAPHICS OUTPUT OF PREVIOUS RESULTS FOR SPECTRAL RESPONSE
      DIMENSION WAV(200),SN(200),SP(200),SDR(200),SR(200)
      CALL CALPLT(1.5,1.0,-3)
      XPG=5.0
      XDV=10.0
      XTIC=.5
      YPG=5.0
      YDV=10.0
      YTIC=.5
      CALL ASCALE(WAV,XPG,I,1,XDV)
      CALL ASCALE(SR,YPG,I,1,YDV)
      CALL AXES(0.,0.,0.,XPG,0.0,WAV(I+2),-XTIC,XDV,
120H WAVELENGTH (MICRONS) ,14,-20)
      CALL AXES(0.,0.,90.,YPG,0.0.,2,-YTIC,YDV,
1 28H NORMALIZED SPECTRAL RESPONSE ,14,28)
      SFX=1./WAV(I+2)
      SFY=5.0
      CALL CALPLT(WAV(1)*SFX,SN(1)*SFY,3)

```



```

DO 100 J=1,I
CALL CALPLT(WAV(J)*SFX,SN(J)*SFY,2)
100 CONTINUE
CALL CALPLT(WAV(1)*SFX,SP(1)*SFY,3)
DO 101 J=1,I
CALL CALPLT(WAV(J)*SFX,SP(J)*SFY,2)
101 CONTINUE
CALL CALPLT(WAV(1)*SFX,SDR(1)*SFY,3)
DO 102 J=1,I
CALL CALPLT(WAV(J)*SFX,SDR(J)*SFY,2)
102 CONTINUE
CALL CALPLT(WAV(1)*SFX,SR(1)*SFY,3)
DO 103 J=1,I
CALL CALPLT(WAV(J)*SFX,SR(J)*SFY,2)
103 CONTINUE
CALL CALPLT(0.,6.,-3)
RETURN
END
SUBROUTINE SHORT(S1P,S1N,S1DR,E)
SHORT CIRCUIT CURRENT

C
C
C
C
COMMON/BLK2/POW,LAMBDA,NA,ND,B4,SN,SP,SO,S1,RE,RS,RSH,A,B,H
COMMON/BLK4/XKKO,MUN,MUP,TAUN,TAUP,DN,DP,PHIO,NI,LN,LP,VBI
COMMON/BLK6/PI,PI2,Q,ZJ,T,TO,NIA1,NIA2,TNO,TPO,W,ALPHA
COMMON/BLK7/NEIGV,KB,KBTG,XGRAPH

C
REAL LAMBDA,NA,ND,MUN,MUP,NI,LN,LP,KB,KBTG,NIA1,NIA2

C
C CALCULATES THE SPECTRAL RESPONSE COMPONENTS
C CALCULATES DOUBLE SUMMATION OVER I,J
CALL ABSORP(E,ALP1)
ALPHA=ALP1
S1P=0 $ S1N=0
DO 10 I=1,NEIGV
DO 20 J=1,NEIGV
CALL NUMBS(I,J,SNIJ,SPIJ)
S1P=S1P+SPIJ
S1N=S1N+SNIJ
20 CONTINUE
10 CONTINUE
CALL EXPON(-ALPHA*ZJ,Q1)
CALL EXPON(-ALPHA*W,Q2)
S1DR=Q1*(1.-Q2)*4.*A*B
RETURN
END
SUBROUTINE DCURRENT(IO)
DARK CURRENT

C
C
C
C
COMMON/BLK2/POW,LAMBDA,NA,ND,B4,SN,SP,SO,S1,RE,RS,RSH,A,B,H
COMMON/BLK4/XKKO,MUN,MUP,TAUN,TAUP,DN,DP,PHIO,NI,LN,LP,VBI
COMMON/BLK5/ETAN(200),XIN(200),XIP(200),ETAP(200)

```

```

COMMON/BLK6/PI,PI2,Q,ZJ,T,TO,NIA1,NIA2,TNO,TPO,W,ALPHA
COMMON/BLK7/NEIGV,KB,KBTG,XGRAPH
C
REAL NNO,NPO,LAMBDA,NA,ND,MUN,MUP,NI,LN,LP,NIA1,NIA2
REAL KB,KBTG,IO,NN,NP
C
Y1(X,Z)=Z*COSH(X)+SINH(X)
Y2(X,Z)=Z*SINH(X)+COSH(X)
Y3(X,Z)=(Z+TANH(X))/(1+Z*TANH(X))
C DOPING DENSITIES
PPO=NA
NNO=ND
NPO=NI*NI/PPO
PNO=NI*NI/NNO
SUM1=0 $ SUM2=0
DO 10 I=1,NEIGV
DO 20 J=1,NEIGV
DEN2=(ETAP(J)/B)**2 +(XIP(I)/A)**2
GIJ2=LP*LP/(1.+LP*LP*DEN2)
GIJ=SQRT(GIJ2)
DEN3=(XIN(I)/A)**2 +(ETAN(J)/B)**2
SIJ2=LN*LN/(1.+LN*LN*DEN3)
SIJ=SQRT(SIJ2)
NP=SP*GIJ/DP $ NN=SN*SIJ/DN
UJNNORM=A+(SO*A*A/DN)*(COS(XIN(J))/XIN(J))**2
VINNORM=B+(S1*B*B/DN)*(COS(ETAN(I))/ETAN(I))**2
F1=SIN(XIN(J)) $ F2=SIN(ETAN(I))
HP=H-ZJ-W
F3=16*A*A*B*B*Q*DN*NI*NI/(NA*SIJ)
F4=(F1/XIN(J))**2 $ F5=(F2/ETAN(I))**2
F6=1./(UJNNORM*VINNORM)
TERMN=F3*F4*F5*F6*Y3((HP/SIJ),NN)
UJPNORM=A+(SO*A*A/DP)*(COS(XIP(J))/XIP(J))**2
VIPNORM=B+(S1*B*B/DP)*(COS(ETAP(I))/ETAP(I))**2
F1=SIN(XIP(J)) $ F2= SIN(ETAP(I))
G3=16*A*A*B*B*Q*DP*NI*NI/(ND*GIJ)
G4=(F1/XIP(J))**2 $ G5=(F2/ETAP(I))**2
G6=1./(UJPNORM*VIPNORM)
TERMP=G3*G4*G5*G6*Y3((ZJ/GIJ),NP)
SUM1=SUM1+TERMN
SUM2=SUM2+TERMP
20 CONTINUE
10 CONTINUE
IO=SUM1+SUM2
RETURN
END
SUBROUTINE NUMBS(I,J,SNIJ,SPIJ)
C I,J TH TERM OF DOUBLE FOURIER SERIES
C
C
C
COMMON/BLK2/POW,LAMBDA,NA,ND,B4,SN,SP,SO,S1,RE,RS,RSH,A,B,H
COMMON/BLK4/XKKO,MUN,MUP,TAUN,TAUP,DN,DP,PHIO,NI,LN,LP,VBI
COMMON/BLK5/ETAN(200),XIN(200),XIP(200),ETAP(200)
COMMON/BLK6/PI,PI2,Q,ZJ,T,TO,NIA1,NIA2,TNO,TPO,W,ALPHA

```

```

COMMON/BLK7/NEIGV,KB,KBTG,XGRAPH
C
REAL LAMBDA,NA,ND,MUN,MUP,NI,LN,LP,NIA1,NIA2,KB,KBTG,NN,NP
EXTERNAL FUN
C
  G(Z)=FUN(-ALPHA*Z)
  Y1(X,Z)=Z*COSH(X)+SINH(X)
  Y2(X,Z)=Z*SINH(X)+COSH(X)
C
C
C
  UJPNOR=A+(SO*A*A/DP)*(COS(XIP(J))/XIP(J))**2
  DEN2=(ETAP(I)/B)**2 +(XIP(J)/A)**2
  GIJ2=LP*LP/(1.+LP*LP*DEN2)
  GIJ=SQRT(GIJ2)
  VIPNOR=B+(SO*B*B/DP)*(COS(ETAP(I))/ETAP(I))**2
  UJNNOR=A+(S1*A*A/DN)*(COS(XIN(J))/XIN(J))**2
  VINNOR=B+(S1*B*B/DN)*(COS(ETAN(I))/ETAN(I))**2
  DEN3=(XIN(J)/A)**2 +(ETAN(I)/B)**2
  SIJ2=LN*LN/(1.+LN*LN*DEN3)
  SIJ=SQRT(SIJ2)
  NP=SP*GIJ/DP      $  NN=SN*SIJ/DN
  TEST=(ALPHA*GIJ-1)
  IF(ABS(TEST).LE..001)GO TO 10
  SPI1=16*ALPHA*A*A*B*B*GIJ/(UJPNOR*VIPNOR*((ALPHA*GIJ)**2-1))
  F4=SIN(XIP(J))      $  F5=SIN(ETAP(I))
  SPI2=((F5/ETAP(I))**2)*((F4/XIP(J))**2)
  SPI3=NP+ALPHA*GIJ-G(ZJ)*Y1((ZJ/GIJ),NP)
  SPI4=(SPI3/Y2((ZJ/GIJ),NP))-ALPHA*GIJ*G(ZJ)
  SPIJ=SPI1*SPI2*SPI4
  GO TO 40
10  SPI1=16*ALPHA*A*A*B*B*GIJ/(UJPNOR*VIPNOR*(ALPHA*GIJ+1))
    F4=SIN(XIP(J))      $  F5=SIN(ETAP(I))
    SPI2=((F5/ETAP(I))**2)*((F4/XIP(J))**2)
    BX=ZJ/GIJ
    SUM=BX      $  XL=BX
20  RATIO=(1+(NP+1)*SUM)/(NP*SINH(BX)+COSH(BX))
    SPI3=RATIO-G(ZJ)
    SPIJ=SPI1*SPI2*SPI3
40  CONTINUE
    HP=H-ZJ-W
    G5=SIN(XIN(J))      $  G6=SIN(ETAN(I))
    SNI1=16*ALPHA*A*A*B*B*SIJ*G((ZJ+W))
    SNI2=(G5/XIN(J))**2
    SNI3=(G6/ETAN(I))**2
    SNI4=1./(UJNNOR*VINNOR)
    TEST=ALPHA*SIJ-1
    IF(ABS(TEST).LE..001)GO TO 50
    SNI5=1./((ALPHA*SIJ)**2 -1.)
    XA=NN*(COSH(HP/SIJ)-G(HP))+SINH(HP/SIJ)
    XB=ALPHA*SIJ*G(HP)
    SNI6=ALPHA*SIJ-(XA+XB)/Y2((HP/SIJ),NN)
    SNIJ=SNI1*SNI2*SNI3*SNI4*SNI5*SNI6
    RETURN
50  CONTINUE

```

```

        BY=HP/SIJ
        SUM=BY
60  RATIO=((NN-1.)*SUM - 1)*G(HP)/(NN*SINH(BY)+COSH(BY))
        SNI5=(1.+RATIO)/(ALPHA*SIJ+1.)
        SNIJ=SNI1*SNI2*SNI3*SNI4*SNI5
        RETURN
        END
        FUNCTION FUN(X)
        IF(X.LT.-230)GO TO 10
        FUN=EXP(X)
        RETURN
10  FUN=0
        RETURN
        END
        SUBROUTINE IV(WAVE)
        C      CURRENT-VOLTAGE CURVE
        C
        C      CALCULATE CURRENT-VOLTAGE CURVE
        C
        C
        COMMON/BLK2/POW,LAMBDA,NA,ND,B4,SN,SP,SO,S1,RE,RS,RSH,A,B,H
        COMMON/BLK4/XKKO,MUN,MUP,TAUN,TAUP,DN,DP,PHIO,NI,LN,LP,VBI
        COMMON/BLK5/ETAN(200),XIN(200),XIP(200),ETAP(200)
        COMMON/BLK6/PI,PI2,Q,ZJ,T,TO,NIA1,NIA2,TNO,TPO,W,ALPHA
        COMMON/BLK7/NEIGV,KB,KBTG,XGRAPH
        COMMON/BLK8/VOC,PMAX,EFF,ISC
        C
        C
        DIMENSION AMPS(100),VOLTS(100)
        REAL IREC,IB,IO,ISC,I
        REAL LAMBDA,NA,ND,LN,LP,MUP,MUN,NIA1,NIA2,KB,KBTG,NI
        C  CALCULATE IV CURVE
        FFF=Q*PHIO*(1-RE)
        E=1.2402/WAVE
        ICOUNT=0          $ PMAX=-.5
        DELVO=.0125
        DELV=.025
        C  CALCULATE ISC (LIGHT CURRENT)
        CALL SHORT(S1P,S1N,S1DR,E)
        ISC=FFF*(S1P+S1N+S1DR)
        V=-DELV
100  CONTINUE
        ICOUNT=ICOUNT+1
        V=V+DELV
        CALL WIDTH(V)
        C  CALCULATE DARK CURRENT
        CALL DCURRENT(IO)
        IREC=4*A*B*Q*NI*W*PI2*2*SINH(V/(2*KBTG))
        IREC=IREC/((VBI-V)/KBTG)
        IREC=IREC/SQRT(TAUN*TAUP)
        C  SOLVE FOR I
        U1=1+RS/RSH
        U=.999
        IB=ISC-IREC-V/RSH+IO
        VOLTS(ICOUNT)=V*1000

```


```

110  CONTINUE
      Z=(V+U*IB*RS)/KBTG
      F=IB*U*U1-IB+IO*EXP(Z)
      FP=IB*U1+IO*(RS*IB/KBTG)*EXP(Z)
      U2=U-F/FP
      ERROR=ABS(U2-U)
      IF(ERROR.LT.1.OE-6) GO TO 120
      U=U2
      GO TO 110
120  I=U2*IB
      AMPS(ICOUNT)=I*1000
      P=I*V
      IF(P.GT.PMAX)PMAX=P
      IF((I.LT.O).OR.(VBI.LT.(V+DELV)))GO TO 130
      IF(V.GT..85) DELV=DELVO
      GO TO 100
130  AMPS(ICOUNT)=O.
      PIN=POW*1000*4*A*B
      EFF=PMAX*100/PIN
      VOLTS(ICOUNT)=VOLTS(ICOUNT-1)+DELV/100.
      VOC=VOLTS(ICOUNT)
      N=ICOUNT $ YMIN=O $ XMIN=O
      YMAX=1.2*AMPS(1)
      XMAX=1.2*VOLTS(ICOUNT)
      NXL=20
      NYL=19
      ISYM=O $ SX=5.O $ SY=5.O
      XOFF=O.75 $ YOFF=O.75
      CALL GRAPHIV(VOLTS,AMPS,ICOUNT)
      CALL NFRAME
      RETURN
      END
      SUBROUTINE GRAPHIV(X,Y,I)
C    GRAPHICS OF CURRENT-VOLTAGE RESULTS
      DIMENSION X(100),Y(100)
      COMMON/BLK7/NEIGV,KB,KBTG,XGRAPH
      XPG=5.O
      XDV=10.
      XTIC=.5
      YPG=5.O
      YDV=10.O
      YTIC=.5
      CALL ASCALE(X,XPG,I,1,XDV)
      CALL ASCALE(Y,YPG,I,1,YDV)
      CALL AXES(O.,O.,O.,XPG,O.O,X(I+2),-XTIC,XDV,
1  20HVOLTAGE (MILLIVOLTS) ,.14,-20)
      CALL AXES(O.,O.,90.,YPG,O.O,Y(I+2),-YTIC,YDV,
1  19HCURRENT (MILLIAMPS) ,.14,19)
      SFX=1./X(I+2)
      SFY=1./Y(I+2)
      CALL CALPLT(X(1)*SFX,Y(1)*SFY,3)
      DO 100 J=1,I
      CALL CALPLT(X(J)*SFX,Y(J)*SFY,2)
100  CONTINUE
      CALL CALPLT(O.,6.,-3)

```

CALL CHARACT(O.O,O.O,.1,5HGRAPH,O.O,5)  
CALL WHERE(XX,YY,IXX)  
CALL NUMBER(XX+.O7,O.,.1,XGRAPH,O.O,-1)  
CALL NFRAME  
RETURN  
END

a)



b)




FIGURE C1. Representative output from program "SC3D" illustrating the spectral response, the current-voltage relation and contour plot of current density in the planes  $Z=Z_j$  and  $Z=Z_j+W$ .




FIGURE C1. (c) Contour plot of  $J_p(x, y)$  in plane  $Z=Z_j$ .






FIGURE C1. (d) Contour plot of  $J_n(x,y)$  in plane  $Z=Z_j+W$ .

## APPENDIX D

PROGRAM "VSC3D" FOR VERTICAL JUNCTION SOLAR CELL  
3-DIMENSIONAL

```

PROGRAM VSC3D(INPUT,OUTPUT,TAPE5=INPUT,TAPE6=OUTPUT,TAPE8)
C
C SC3D=SOLAR CELL 3 DIMENSIONAL (ILLUMINATED FROM SIDE X=A)
C
C GREEN'S FUNCTION SOLUTION
C
COMMON/BLK1/NDATA,ENERG(25),ALP(25)
COMMON/BLK2/POW,LAMBDA,NA,ND,B4,SN,SP,SO,S1,RE,RS,RSH,A,B,H
COMMON/BLK3/EP50,A0,A1,A2,A3,B0,B1,B2,B3,EGGO,ALPHA0,BETA0
COMMON/BLK4/XKKO,MUN,MUP,TAUN,TAUP,DN,DP,PHIO,NI,LN,LP,VBI
COMMON/BLK5/ETAN(50),XIN(50),XIP(50),ETAP(50),XN(50),XP(50)
COMMON/BLK6/PI,PI2,Q,ZJ,T,TO,NIA1,NIA2,TNO,TPO,W,ALPHA
COMMON/BLK7/NEIGV,KB,KBTG,XGRAPH
COMMON/BLK8/VOC,PMAX,EFF,ISC
COMMON/BLK9/SPTOP,SNBOT
DIMENSION ENERG5(25),ENERGGA(25),ENERGGE(25)
DIMENSION ALPS(25),ALPGA(25),ALPGE(25)
C
C
C
REAL LAMBDA,NA,ND,NIA1,NIA2,MUN,MUP,KB,KBTG,LN,LP,NI,ISC
REAL NIAS1,NIAS2,NIAGA1,6(>Ics.TTC'IAGE25*P&K -,+I
C
CALL PSEUDO
C
C NAMELIST VARIABLES
C
NAMELIST/PARAM/POW,NA,ND,LAMBDA,A,B,H,ZJ,T,RS,RSH,SN,SP,
1 SO,S1,NEIGV,ITYPE,ISWITCH
C
C POW = LASER POWER (KW/CM2)
C NA=DOPING DENSITY (CM-3)
C ND=DOPING DENSITY (CM-3)
C LAMBDA=WAVELENGTH (MICRONS)
C A=HALF WIDTH OF X-DIRECTION ( -A .LE. X .LE. A)
C B=HALF WIDTH OF Y-DIRECTION ( -B .LE. Y .LE. B)
C H=DEPTH OF CELL IN Z-DIRECTION ( 0 .LE. Z .LE. H)
C ZJ=JUNCTION DEPTH FROM Z=0 (CM)
C T= TEMPERATURE (DEG K)
C RS=SERIES RESISTANCE OHMS
C RSH=SHUNT RESISTANCE OHMS
C SN=SURFACE RECOMBINATION VELOCITY TOP (CM/S)
C SP=SURFACE RECOMBINATION VELOCITY BOTTOM (CM/S)
C SO=SURFACE RECOMBINATION VELOCITY TOP SIDES
C S1=SURFACE RECOMBINATION VELOCITY BOTTOM SIDES
C NEIGV=NUMBER OF EIGENVALUES
C ITYPE = TYPE OF MATERIAL
C ITYPE = 1 FOR SILICON (SI)
C ITYPE = 2 FOR GALLIUM ARSENIDE (GAAS)
C ITYPE = 3 FOR GERMANIUM (GE)
C ISWITCH TURNS CONTOUR PLOT ON AND OFF
C ISWITCH=0 CONTOUR PLOT IS OFF
C ISWITCH=1 CONTOUR PLOT IS ON

```

C

C

C

C

## NOMINAL VALUES FOR NAMELIST VARIABLES

```

POW=.001      $ RE=.05
LAMBDA=.8     $ ITYPE = 1
TO=300.       $ T=300.
RS=0.0        $ RSH=1.0E6
SN=1.0        $ SP=1.0
SO=1.0        $ S1=1.0
NA=1.25E17    $ ND=5.0E19
A=.5          $ B=.500
H=5.00E-4     $ ZJ=2.5E-4
NEIGV=15
ISWITCH=1

```

C

C

## SILICON PARAMETERS

NDATAS=20

```

DATA (ENERGS(K),K=1,8)/1.1,1.15,1.24,1.378,1.46,1.77,2.067,2.48/
DATA (ENERGS(K),K=9,15)/2.76,3.1,3.26,3.5,3.6,4.0,4.2/
DATA (ENERGS(K),K=16,20)/5.0,5.2,6.0,8.0,10.0/
DATA (ALPS(K),K=1,7)/1.0,10.0,100.0,350.0,950.0,2.E3,4.5E3/
DATA (ALPS(K),K=8,14)/1.0E4,2.0E4,5.0E4,1.0E5,1.0E6,1.1E6,1.8E6/
DATA (ALPS(K),K=15,20)/2.5E6,1.9E6,2.0E6,1.5E6,1.3E6,1.1E6/

```

## C CONSTANTS FOR MOBILITIES

DATA ASO,AS1,AS2,AS3/65.02,5.72E-9,2.49E9,2.5/

DATA BSO,BS1,BS2,BS3/54.46,6.76E-9,2.93E9,2.7/

## C CONSTANTS FOR BANDGAP AS FUNCTION OF TEMPERATURE

DATA EGGOS,ALPHAOS,BETAOS/1.16,7.02E-4,1108./

## C CONSTANTS FOR INTRINSIC CARRIER DENSITY

DATA NIAS1,NIAS2/4.9E15,1.61/

## C CONSTANTS FOR LIFETIMES

DATA TNOS,TPOS,B4/1.86E-4,3.52E-3,7.1E15/

EPSOS=11.6

## C GALLIUM ARSENIDE PARAMETERS

## C ABSORPTION COEFFICIENT CURVE FOR GAAS

NDATAGA=16

DATA (ENERGGA(K),K=1,8)/1.37,1.38,1.4,1.41,1.42,1.43,1.44,1.5/

DATA (ENERGGA(K),K=9,16)/1.6,1.8,2.0,2.4,3.0,3.5,4.0,4.5/

DATA (ALPGA(K),K=1,8)/18.,32.,119.,175.,2.5E3,4.5E3,6.E3,1.4E4/

DATA (ALPGA(K),K=9,16)/1.8E4,3.E4,4.E4,1.E5,2.E5,3.E5,4.E5,5.E5/

C

## C CONSTANTS FOR MOBILITIES

DATA AGAO,AGA1,AGA2,AGA3/5076.11,5.24E-9,6.43E5,1.0/

DATA BGAO,BGA1,BGA2,BGA3/1477.3,8.59E-8,6.05E7,2.1/

## C CONSTANTS FOR BANDGAP

DATA EGGOGA,ALPHGA,BETGA/1.519,5.4E-4,204./

## C CONSTANTS FOR INTRINSIC CARRIER DENSITY

DATA NIAGA1,NIAGA2/4.9E15,.0488844/

## C CONSTANTS FOR LIFETIMES

DATA TNOGA,TPOGA,B4/8.8179E-7,1.404E-7,7.1E15/

EPSOGA=13.1

## C GERMANIUM PARAMETERS

# C GERMANIUM SOLAR CELL PARAMETERS

NDATAGE=22

DATA (ENERGGE(K),K=1,8)/.66,.68,.7,.73,.76,.79,.8,.81/

DATA (ENERGGE(K),K=9,16)/.83,.85,.875,.9,.97,1.7,2.6,3./

DATA (ENERGGE(K),K=17,22)/3.6,4.,4.4,5.0,6.0,8./

DATA (ALPGE(K),K=1,8)/1.,10.,20.,60.,100.,600.,1.E3,4.E3/

DATA (ALPGE(K),K=9,16)/5.E3,8.E3,8.5E3,9.E3,1.E4,1.E5,7.E5,8.E5/

DATA (ALPGE(K),K=17,22)/1.E6,1.4E6,2.0E6,1.3E6,1.2E6,1.0E6/

C

DATA AGE0,AGE1,AGE2,AGE3/458.68,7.92E-9,6.08E7,1.66/

DATA BGEO,BGE1,BGE2,BGE3/3140.27,1.79E-7,1.18E9,2.33/

DATA EGGGE,ALPHGE,BETGE/.741,4.77E-4,235./

DATA NIAGE1,NIAGE2/4.9E15,.33313/

DATA TNOGE,TPOGE,B4/2.1022E-5,2.1007E-5,7.1E15/

EPSOGE=16.

C

C READ IN ANY CHANGES TO THE ABOVE PARAMETERS

C

XGRAPH=0.

100 CONTINUE

READ(5,PARAM)

IF(EOF(5))600,601

600 WRITE(6,603)

603 FORMAT(1X,28HEND OF FILE ENCOUNTERED-STOP )

STOP 1313

601 CONTINUE

C

WRITE(6,110)

110 FORMAT(/ /)

Q=1.6E-19

XKKO=1.2E-3

PI=3.1415926536

PI2=PI\*.5

KB=8.6172E-5

KBTG=KB\*T

C

EPSO IS THE PERMITIVITY

XGRAPH=XGRAPH+1

C

C SETUP PARAMETERS FOR CORRECT TYPE OF PHOTOCONVERTER MATERIALS

C ITYPE = 1 (SI)

C ITYPE = 2 (GAAS)

C ITYPE = 3 (GE)

IF(ITYPE .EQ. 1) WRITE(6,111)

IF(ITYPE .EQ. 2) WRITE(6,112)

IF(ITYPE .EQ. 3) WRITE(6,113)

111 FORMAT(1X,25HSILICON PHOTOCONVERTER , /)

112 FORMAT(1X,35HGALLIUM ARSENIDE PHOTOCONVERTER , /)

113 FORMAT(1X,25HGERMANIUM PHOTOCONVERTER , /)

IF(ITYPE .EQ. 1) GO TO 10

IF(ITYPE .EQ. 2) GO TO 20

C

GERMANIUM DATA GOES HERE

NDATA=NDATAGE

DO 40 I=1,NDATA

ENERG(I)=ENERGGE(I)

40 ALP(I)=ALPGE(I)

```

      AO=AGEO $ A1=AGE1 $ A2=AGE2 $ A3=AGE3
      BO=BGEO $ B1=BGE1 $ B2=BGE2 $ B3=BGE3
      EGGO=EGGOGE $ ALPHAO=ALPHGE $ BETAO=BETGE
      NIA1=NIAGE1 $ NIA2=NIAGE2
      TNO=TNOGE $ TPO=TPOGE
      EPSO=EPSOGE
      GO TO 30
10  CONTINUE
C    SILICON PARAMETERS
      NDATA=NDATAS
      DO 41 I=1,NDATA
      ENERG(I)=ENERGS(I)
41  ALP(I)=ALPS(I)
      AO=ASO $ A1=AS1 $ A2=AS2 $ A3=AS3
      BO=BSO $ B1=BS1 $ B2=BS2 $ B3=BS3
      EGGO=EGGOS $ ALPHAO=ALPHAOS $ BETAO=BETAOS
      NIA1=NIAS1 $ NIA2=NIAS2
      TNO=TNOS $ TPO=TPOS
      EPSO=EPSOS
      GO TO 30
20  CONTINUE
C    GALLIUM ARSENIDE PARAMETERS
      NDATA=NDATAGA
      DO 42 I=1,NDATA
      ENERG(I)=ENERGGA(I)
42  ALP(I)=ALPGA(I)
      AO=AGAO $ A1=AGA1 $ A2=AGA2 $ A3=AGA3
      BO=BGAO $ B1=BGA1 $ B2=BGA2 $ B3=BGA3
      EGGO=EGGOGA $ ALPHAO=ALPHGA $ BETAO=BETGA
      NIA1=NIAGA1 $ NIA2=NIAGA2
      TNO=TNOGA $ TPO=TPOGA
      EPSO=EPSOGA
30  CONTINUE
C    CALCULATE CONSTANTS
      CALL CONST
C    CALCULATE SPECTRAL RESPONSE
      CALL SPEC
C    CALCULATE I-V CURVE
      CALL IV(LAMBDA)
      WRITE(6,199)XGRAPH
199  FORMAT(T20,6HGRAPH ,F3.0 )
      WRITE(6,200)ISC,VOC,EFF,RSH,DN,NEIGV
200  FORMAT(/,T2,4HISC=,E12.5,T20,4HVOC=,E12.5,T40,4HEFF=,
1  E12.5,T60,4HRS=,E12.5,T80,3HDN=,E12.5,T99,8HNEIGV = ,I5)
      WRITE(6,201)NA,ND,ZJ,S1,DP,NIA1
201  FORMAT(T2,3HNA=,E12.5,T20,3HND=,E12.5,T40,3HZJ=,E12.5,
1T60,3HS1=,E12.5,T80,3HDP=,E12.5,T99,7HNIA1 = ,E12.5)
      WRITE(6,202)TAUN,TAUP,LN,LP,TNO,NIA2
202  FORMAT(T2,5HTAUN=,E12.5,T20,5HTAUP=,E12.5,T40,3HLN=,E12.5,
1 T60,3HLP=,E12.5,T80,6HTNO = ,E12.5,T99,7HNIA2 = ,E12.5)
      WRITE(6,203)A,B,H,SO,TPO
203  FORMAT(T2,2HA=,E12.5,T20,2HB=,E12.5,T40,2HH=,E12.5,T60,3HSO=,
1 E12.5,T80,6HTPO = ,E12.5)
      WRITE(6,204)MUN,MUP,LAMBDA,POW,SPTOP
204  FORMAT(T2,4HMUN=,E12.5,T20,4HMUP=,E12.5,T40,7HLAMBDA=,F10.4,

```

```

1T60,4HPOW=,E12.5 ,T80,6HSPTOP= ,E12.5 )
WRITE(6,205)T,RS,SN,SP,SNBOT
205 FORMAT(T2,2HT=,E12.5,T20,3HRS=,E12.5,T40,3HSN=,E12.5,
1 T60,3HSP=,E12.5,T80,6HSNBOT= ,E12.5 )
WRITE(6,206)W,PMAX,NI,VBI,ALPHA
206 FORMAT(T2,2HW=,E12.5,T20,5HPMAX=,E12.5,T40,3HNI=,E12.5,
1 T60,4HVBI=,E12.5,T80,6HALPHA=,E12.5,///)
IF(ISWITCH .EQ. 1) CALL CONTOUR
GO TO 100
END

SUBROUTINE CONTOUR
DIMENSION AAA(40,40),BBB(40,40)
C AAA IS 40X40 ARRAY OF CURRENT DENSITY VALUES AT X,Y AND Z=ZJ
C BBB IS 40X40 ARRAY OF CURRENT DENSITY VALUES AT X,Y AND Z=ZJ+W
C
N=40
C CALCULATE JP AND STORE IN AAA. FIND AMAX AND AMIN VALUES FOR ARRAY
C
CALL CDENAB(AAA,BBB,AMAX,AMIN,BMAX,BMIN,N)
C
C CALCULATE JN AND STORE IN BBB. FIND BMAX AND BMIN VALURS FOR ARRAY
C
C AAA ARE VALUES OF XJP
C BBB ARE VALUES OF XJN
C
C
C
C PLOT CONTOUR GRAPH OF AAA
CALL CONREC(AAA,N,N,N,AMIN,AMAX,0,0,-1,0)
CALL EZTRN
CALL NFRAME
WRITE(6,199)
199 FORMAT(///)
C PLOT CONTOUR GRAPH OF BBB
C
CALL CONREC(BBB,N,N,N,BMIN,BMAX,0,0,-1,0)
CALL EZTRN
CALL NFRAME
RETURN
END

SUBROUTINE CDENAB(AAA,BBB,AMAX,AMIN,BMAX,BMIN,N)
COMMON/BLK2/POW,LAMBDA,NA,ND,B4,SN,SP,SO,S1,RE,RS,RSH,A,B,H
COMMON/BLK4/XKKO,MUN,MUP,TAUN,TAUP,DN,DP,PHIO,NI,LN,LP,VBI
COMMON/BLK6/PI,PI2,Q,ZJ,T,TO,NIA1,NIA2,TNO,TPO,W,ALPHA
REAL NA,ND,LAMBDA,LN,LP,MUN,MUP,NI,NIA1,NIA2
DIMENSION AAA(40,40),BBB(40,40)
C CALCULATE JP(X,Y) AND STORE IN AAA
C CALCULATE JN(X,Y) AND STORE IN BBB
DELY=2.*A/FLOAT(N+1)
AMIN=5.E5
AMAX=0.0
DELY=2.*B/FLOAT(N+1)
YWQ=ZJ+W

```

```

      WRITE(6,99)
99  FORMAT(T5,1HX,T15,1HY,T25,2HZJ,T43,2HJP,T55,1HX,
      1 T65,1HY,T75,4HZJ+W,T93,2HJN )
      BMIN=5.OE5
      BMAX=0.0
      DO 10 J=1,N
      DO 20 I=1,N
      X=-A+I*DELX
      Y=-B+J*DELY
      CALL SUMIJ(X,Y,XJP,XJN)
      AAA(I,J)=2.0*Q*ALPHA*PHIO*(1-RE)*XJP
      BBB(I,J)=2.0*Q*ALPHA*PHIO*(1-RE)*XJN
      WRITE(6,100)X,Y,ZJ,AAA(I,J),X,Y,YWQ,BBB(I,J)
100  FORMAT(1X,3F10.4,E15.7,3X,3F10.6,E15.7)
      IF(AAA(I,J).GT.AMAX) AMAX=AAA(I,J)
      IF(AAA(I,J).LT.AMIN) AMIN=AAA(I,J)
      IF(BBB(I,J).GT.BMAX) BMAX=BBB(I,J)
      IF(BBB(I,J).LT.BMIN) BMIN=BBB(I,J)
20  CONTINUE
10  CONTINUE
      RETURN
      END

      SUBROUTINE SUMIJ(X,Y,XJP,XJN)
C
      COMMON/BLK2/POW,LAMBDA,NA,ND,B4,SN,SP,SO,S1,RE,RS,RSH,A,B,H
      COMMON/BLK4/XKKO,MUN,MUP,TAUN,TAUP,DN,DP,PHIO,NI,LN,LP,VBI
      COMMON/BLK6/PI,PI2,Q,ZJ,T,TO,NIA1,NIA2,TNO,TPO,W,ALPHA
      REAL NA,ND,MUN,MUP,NI,LN,LP,NIA1,NIA2,KB,KBTG,LAMBDA
C
      XJP=0.0
      XJN=0.0
      DO 10 I=1,NEIGV
      DO 20 J=1,NEIGV
      CALL TERNIJ(X,Y,I,J,FPIJ,FNIJ)
      XJP=XJP+FPIJ
      XJN=XJN+FNIJ
20  CONTINUE
10  CONTINUE
      RETURN
      END

      SUBROUTINE TERNIJ(X,Y,I,J,FPIJ,FNIJ)
      COMMON/BLK2/POW,LAMBDA,NA,ND,B4,SN,SP,SO,S1,RE,RS,RSH,A,B,H
      COMMON/BLK4/XKKO,MUN,MUP,TAUN,TAUP,DN,DP,PHIO,NI,LN,LP,VBI
      COMMON/BLK5/ETAN(50),XIN(50),XIP(50),ETAP(50),XN(50),XP(50)
      COMMON/BLK6/PI,PI2,Q,ZJ,T,TO,NIA1,NIA2,TNO,TPO,W,ALPHA
      COMMON/BLK7/NEIGV,KB,KBTG,XGRAPH
      REAL NA,ND,MUN,MUP,NI,LN,LP,NIA1,NIA2,KB,KBTG
      REAL LAMBDA
      EXTERNAL FUN
C
      G(Z)=FUN(-ALPHA*Z)
C
      FPIJ (TOP REGION) N-REGION
      WJPNOR=.5*ZJ-.25*SIN(2*XP(J))*ZJ/XP(J)

```



```

XMUI=ETAP(I)/B
XLAMJ=(XP(J))/ZJ
DEN2=(XMUI**2)+(XLAMJ**2)
GIJ2=LP*LP/(1.+LP*LP*DEN2)
GIJ=SQRT(GIJ2)
CC=ALPHA*ALPHA*GIJ2-1
VIPNOR=B+(SO*B*B/DP)*(COS(ETAP(I))/ETAP(I))*2
SPI1=B*SIN(ETAP(I))/ETAP(I)
SPI2=ZJ*(1.-COS(XP(J)))/XP(J)
SPI3=XLAMJ/WJPNOR
SPI4=COS(XMUI*Y)/VIPNOR
CALL SUB1(X,A,GIJ,SO,DP,ALPHA,CC,SPI5)
FPIJ=SPI1*SPI2*SPI3*SPI4*SPI5
C CALCULATE FNIJ BOTTOM REGION (P-REGION) EVALUATE AT Z=ZJ+W
HP=H-(ZJ+W)
WJNNOR=.5*HP-.25*SIN(2*XN(J))*HP/XN(J)
VINNOR=B+(S1*B*B/DN)*(COS(ETAN(I))/ETAN(I))*2
XMUI=ETAN(I)/B
XLAMJ=XN(J)/HP
DEN3=(XLAMJ**2)+(XMUI**2)
SIJ2=LN*LN/(1.+LN*LN*DEN3)
SIJ=SQRT(SIJ2)
EE=ALPHA*ALPHA*SIJ2-1
SNI1=B*SIN(ETAN(I))/ETAN(I)
SNI2=HP*(1.-COS(XN(J)))/XN(J)
SNI3=XLAMJ/WJNNOR
SNI4=COS(XMUI*Y)/VINNOR
CALL SUB1(X,A,SIJ,S1,DN,ALPHA,EE,SNI5)
FNIJ=SNI1*SNI2*SNI3*SNI4*SNI5
RETURN
END

```

```

SUBROUTINE SUB1(X,A,GIJ,SO,DP,ALPHA,CC,SPI5)
EXTERNAL FUN
G2=GIJ*GIJ
G1=SO/DP
AB1=G1-ALPHA
AB2=G1+ALPHA
AO=G2*AB1*EXP(-2.*A*ALPHA)/CC
A1=AO*GIJ*G1
A2=G2*AB2/CC
A3=A2*GIJ*G1
BO=2.*G1
B1=(1./GIJ)+G1*G1*G2
H=ALPHA*(X-A)
Q1=TANH(2.*A/GIJ)
R1=-G2*BO*EXP(H)/CC
R2=(-GIJ*(1+G1*G1*G2)*EXP(H)/CC)*Q1
ARG1=-(X+A)/GIJ
ARG2=(X-3*A)/GIJ
ARG3=(X-A)/GIJ
ARG4=-(X+3*A)/GIJ
DEN=1+FUN(ARG4)
R3=AO*(FUN(ARG1)+FUN(ARG2))/DEN
R4=A1*(FUN(ARG1)-FUN(ARG2))/DEN

```

```

R5=A2*(FUN(ARG3)+FUN(ARG4))/DEN
R6=A3*(FUN(ARG3)-FUN(ARG4))/DEN
SPI5=(R1+R2+R3+R4+R5+R6)/(BO+B1*Q1)
RETURN
END

```

# SUBROUTINE CONST

```

C
C CALCULATES OTHER CONSTANTS AND PARAMETERS FOR PROBLEM
C
C
COMMON/BLK2/POW,LAMBDA,NA,ND,B4,SN,SP,SO,S1,RE,RS,RSH,A,B,H
COMMON/BLK3/EPSO,AO,A1,A2,A3,BO,B1,B2,B3,EGGO,ALPHAO,BETAO
COMMON/BLK4/XKKO,MUN,MUP,TAUN,TAUP,DN,DP,PHIO,NI,LN,LP,VBI
COMMON/BLK6/PI,PI2,Q,ZJ,T,TO,NIA1,NIA2,TNO,TPO,W,ALPHA
COMMON/BLK7/NEIGV,KB,KBTG,XGRAPH
C
C
REAL MUN,MUP,KBTG,KB,LAMBDA,NA,ND,NIA1,NIA2,NI,LN,LP
C
C
C CONVERT WAVELENGTH (MICRONS) TO ENERGY (EV)
ENER=1.2402/LAMBDA
C CALCULATE BANDGAP AS FUNCTION OF TEMPERATURE
EGT=EGGO-ALPHAO*T*T/(T+BETAO)
C CALCULATE ENERGY SHIFT DUE TO TEMPERATURE
DELE=XKKO*(T-TO)
E=ENER+DELE
C CALCUALTE ABSORPTION COEFFICIENT
CALL ABSORP(E,ALPHA1)
ALPHA=ALPHA1
C CALCULATE LIFETIMES
TAUN=TNO/(1.+NA/B4)
TAUP=TPO/(1.+ND/B4)
C CALCULATE MOBILITIES
CALL MOBIL(Y1,Y2)
MUN=Y1 $ MUP=Y2
C CALCULATE DIFFUSION COEFFICIENTS
DN=KBTG*MUN $ DP=KBTG*MUP
C CALCUALTE DENSITY OF PHOTONS IN PHOTON'S/CM2-S
PHIO=POW*LAMBDA*5.03306E21
C CALCULATE INTRINSIC CARRIER DENSITY
POWER=-EGT/(2.*KBTG)
CALL EXPON(POWER,ANS)
NI=NIA1*NIA2*(T**1.5)*ANS
C CALCULATE BUILT IN VOLTAGE
VBI=KBTG*ALOG(NA*ND/(NI*NI))
VOLTS=0.0
CALL WIDTH(VOLTS)
C CALCULATE DIFFUSION LENGTHS
LP=SQRT(DP*TAUP) $ LN=SQRT(DN*TAUN)
C CALCULATE ALL NECESSARY EIGENVALUES FOR PROBLEM
CALL ESET
RETURN
END

```

```

SUBROUTINE ABSORP(E,ALPHA)
C
C
COMMON/BLK1/NDATA,ENERG(25),ALP(25)
C
C
C
I=0
IF(E.LT.ENERG(1))GO TO 10
20 CONTINUE
I=I+1
IF(I.GE.NDATA)GO TO 30
IF((ENERG(I).LE.E).AND.(ENERG(I+1) .GE. E))GO TO 40
GO TO 20
40 ALPHA=ALP(I)+(ALP(I+1)-ALP(I))*(E-ENERG(I))/(ENERG(I+1)-ENERG(I))
RETURN
10 ALPHA=0.
RETURN
30 ALPHA=ALP(NDATA)
RETURN
END

SUBROUTINE EXPON(X,ANS)
IF(X.LT.-500) GO TO 10
IF(X .GT. 700)GO TO 20
ANS=EXP(X)
RETURN
10 ANS=0.0
RETURN
20 WRITE(6,30)
30 FORMAT(1X,29H ARG TOO LARGE, EXP FUNCTION )
STOP 444
END

SUBROUTINE ESET
C
C
COMMON/BLK2/POW,LAMBDA,NA,ND,B4,SN,SP,SO,S1,RE,RS,RSH,A,B,H
COMMON/BLK4/XKKO,MUN,MUP,TAUN,TAUP,DN,DP,PHIO,NI,LN,LP,VBI
COMMON/BLK5/ETAN(50),XIN(50),XIP(50),ETAP(50),XN(50),XP(50)
COMMON/BLK6/PI,PI2,Q,ZJ,T,TO,NIA1,NIA2,TNO,TPO,W,ALPHA
COMMON/BLK7/NEIGV,KB,KBTG,XGRAPH
C
REAL MUN,MUP,NI,LN,LP,NIA1,NIA2,KB,KBTG,NA,ND,LAMBDA
C
C CALCULATE EIGENVALUES FOR TOP REGION X-DIRECTION
R1=SO $ R2=DP $ R3=A $ N4=NEIGV
CALL EIGEN(XIP,R1,R2,R3,N4)
C CALCULATE EIGENVALUES FOR TOP REGION Z-DIRECTION
R1=SP $ R2=DP $ R3=ZJ
CALL EIG(XP,R1,R2,R3,N4)
C CALCULATE EIGENVALUES FOR TOP REGION Y-DIRECTION
R1=SO $ R3=B
CALL EIGEN(ETAP,R1,R2,R3,N4)
C CALCULATE EIGENVALUES FOR BOTTOM REGION

```

```

R1=S1 $ R2=DN $ R3=A
CALL EIGEN(XIN,R1,R2,R3,N4)
C   CALCULATE EIGENVALUES BOTTOM REGION Z-DIRECTION
R1=SN $ R2=DN $ R3=H-ZJ-W
CALL EIG(XN,R1,R2,R3,N4)
C CALCULATE EIGENVALUES FOR BOTTOM REGION
R1=S1 $ R3=B
CALL EIGEN(ETAN,R1,R2,R3,N4)
WRITE(6,99)(XIP(J),J=1,N4)
WRITE(6,98)
WRITE(6,99)(ETAP(J),J=1,N4)
WRITE(6,98)
WRITE(6,99)(XIN(J),J=1,N4)
WRITE(6,98)
WRITE(6,99)(ETAN(J),J=1,N4)
WRITE(6,98)
WRITE(6,99) (XP(J),J=1,N4)
WRITE(6,98)
WRITE(6,99) (XN(J),J=1,N4)
WRITE(6,98)
99  FORMAT(1X,(SE15.6))
98  FORMAT(/)
    RETURN
    END

```

```

SUBROUTINE EIG(XX,S,D,H,N)
DIMENSION XX(50)
DOUBLE PRECISION X,X1,X2,Y,Y1,Y2,PI,PI2
F(Z)=1+C*Z*DCOS(Z)/DSIN(Z)
C N MUST BE LESS THAN 50
C=D/(S*H)
PI=3.1415926535897932
PI2=.5*PI
C XX=ETAJ*ZJUNCTION
IF(S.LE.0)GO TO 1001
C GUESS AT FIRST ROOT
X1=PI2
M=1 $ IC=1
200 Y1=F(X1)
IF(Y1.GT.0)GO TO 10
C Y1 IS NEGATIVE, DECREASE X
X2=X1 $ Y2=Y1
5 X1=.5*(X2+(2*M-1)*PI2)
Y1=F(X1)
IF(Y1.GT.0) GO TO 20
C Y1 IS NEGATIVE
X2=X1 $ Y2=Y1
GO TO 5
10 CONTINUE
C Y1 IS POSITIVE, INCREASE X
X2=.5*(X1+M*PI)
Y2=F(X2)
IF(Y2.LT.0) GO TO 20
X1=X2 $ Y1=Y2
GO TO 10

```

ORIGINAL PAGE IS  
OF POOR QUALITY

```
20  X=(X1+X2)/2.
    Y=F(X)
    IF(DABS(Y) .LT. 1.0E-6) GO TO 100
    IF(Y.LT.0) GO TO 30
    X1=X $ Y1=Y
    GO TO 20
30  X2=X
    Y2=Y
    GO TO 20
100 CONTINUE
    ZZ=X
    XX(IC)=ZZ
    M=M+1 $ IC=IC+1
    X1=X+PI
    IF(IC.GT. N) GO TO 308
    GO TO 200
308 RETURN
1001 WRITE(6,234)
234 FORMAT(1X,45HRECOMBINATION VELOCITY OF ZERO NOT ALLOWED )
    END
```

```
    SUBROUTINE EIGEN(XX, S,D,H,N)
C
    COMMON/BLK6/PI,PI2,Q,ZJ,T,TO,NIA1,NIA2,TNO,TPO,W,ALPHA
C
    REAL NIA1,NIA2
C
    DIMENSION XX(50)
    F(Z)=TAN(Z)-C/Z
C SOLVES EQUATION X*TANX=C
C N MUST BE .LE. 200
    C=S*H/D
    IF(C.EQ.0) GO TO 1001
C GUESS AT FIRST ROOT
    X1=PI/4.
    M=1 $ IC=1
200  Y1=F(X1)
    IF(Y1.GT.0)GO TO 10
C Y1 IS NEGATIVE
    X2=X1
    Y2=Y1
5    X1=.5*(X2+(2*M-1)*PI2)
    Y1=F(X1)
    IF(Y1.GT.0)GO TO 20
C Y1 IS NEGATIVE
    X2=X1
    Y2=Y1
    GO TO 5
10  X2=(M-1)*PI+.8*(X1-(M-1)*PI)
    Y2=F(X2)
    IF(Y2.LT.0)GO TO 20
    X1=X2
    Y1=Y2
    GO TO 10
20  X=(X1+X2)/2.
```

```

      Y=F(X)
      IF(ABS(Y) .LT. 1.0E-6)GO TO 100
      IF(Y .LT. 0) GO TO 30
      X1=X
      Y1=Y
      GO TO 20
30    X2=X
      Y2=Y
      GO TO 20
100   XX(IC)=X
      M=M+1 $ IC=IC+1
      X1=X+PI
      IF(IC.GT.N) GO TO 308
      GO TO 200
308   CONTINUE
      RETURN
1001  WRITE(6,234)
234   FORMAT(45HRECOMBINATION VELOCITY OF ZERO NOT ALLOWED )
      END

```

```

      SUBROUTINE MOBIL(XMUN,XMUP)

```

```

C
C
C
      COMMON/BLK2/POW,LAMBDA,NA,ND,B4,SN,SP,SO,S1,RE,RS,RSH,A,B,H
      COMMON/BLK3/EPSO,AO,A1,A2,A3,B0,B1,B2,B3,EGGO,ALPHAO,BETAO
      COMMON/BLK4/XKKO,MUN,MUP,TAUN,TAUP,DN,DP,PHIO,NI,LN,LP,VBI
      COMMON/BLK6/PI,PI2,Q,ZJ,T,TO,NIA1,NIA2,TNO,TPO,W,ALPHA

```

```

C
C
      REAL LAMBDA,NA,ND,MUN,MUP,NI,LN,LP,NIA1,NIA2

```

```

C MOBILITY OF ELECTRONS

```

```

      RQ=2./3.
      BB1=A1*T*T/(NA**RQ)
      D=NA*BB1*(1.-.5*BB1)
      X1=AO*(T**1.5)/D
      ZZ=-A3*ALOG(T)
      CALL EXPON(ZZ,ANS)
      X2=A2*ANS
      R=1./X2 + 1./X1
      XMUN=1./R

```

```

C MOBILITY OF HOLES

```

```

      ZZZ=-B3*ALOG(T)
      CALL EXPON(ZZZ,ANS)
      X1=B2*ANS
      BB1=B1*T*T/(ND**RQ)
      D=ND*BB1*(1.-.5*BB1)
      X2=B0*(T**1.5)/D
      R=1./X2 +1./X1
      XMUP=1./R
      RETURN
      END

```

# SUBROUTINE WIDTH(VOLTS)

```
COMMON/BLK2/POW,LAMBDA,NA,ND,B4,SN,SP,SO,S1,RE,RS,RSH,A,B,H
COMMON/BLK3/EP50,A0,A1,A2,A3,B0,B1,B2,B3,EGGO,ALPHAO,BETAO
COMMON/BLK4/XKKO,MUN,MUP,TAUN,TAUP,DN,DP,PHIO,NI,LN,LP,VBI
COMMON/BLK6/PI,PI2,Q,ZJ,T,TO,NIA1,NIA2,TNO,TPO,W,ALPHA
COMMON/BLK7/NEIGV,KB,KBTG,XGRAPH
```

```
REAL KB,KBTG,LAMBDA,LN,LP,MUN,MUP,NA,ND,NI,NIA1,NIA2
```

```
ABC=(1./ND + 1./NA)
W2=(2.*EP50*(8.85E-14)/Q)*(VBI-VOLTS)*ABC
W=SQRT(W2)
RETURN
END
```

# SUBROUTINE SPEC

## CALCULATE SPECTRAL RESPONSE

```
COMMON/BLK2/POW,LAMBDA,NA,ND,B4,SN,SP,SO,S1,RE,RS,RSH,A,B,H
COMMON/BLK3/EP50,A0,A1,A2,A3,B0,B1,B2,B3,EGGO,ALPHAO,BETAO
COMMON/BLK4/XKKO,MUN,MUP,TAUN,TAUP,DN,DP,PHIO,NI,LN,LP,VBI
COMMON/BLK6/PI,PI2,Q,ZJ,T,TO,NIA1,NIA2,TNO,TPO,W,ALPHA
COMMON/BLK9/SPTOP,SNBOT
```

```
REAL LAMBDA,NA,ND,MUN,MUP,NI,LN,LP,NIA1,NIA2
```

```
DIMENSION WAV(200),SSP(200),SSN(200),SR(200)
```

```
SPTOP=-1.
SNBOT=-1.
```

```
I=0
```

```
I=I+1
```

```
E=EGGO-.15+.025*(I-1)
```

```
IF((E.GT.5.0).OR.(I.GT.200))GO TO 100
```

```
WAV(I)=1.2402/E
```

```
FFF=WAV(I)*Q*POW*(5.03306E21)*(1-RE)
```

```
PIN=2*B*H*POW*1000.
```

```
CALL SHORT(S1P,S1N,E)
```

```
SSN(I)=S1N*FFF/PIN
```

```
SSP(I)=S1P*FFF/PIN
```

```
SR(I)=SSN(I)+SSP(I)
```

```
GO TO 90
```

```
100 CONTINUE
```

```
MAX=I-1
```

```
I=I-1
```

## NORMALIZE SPECTRAL RESPONSE

```
XMAX=0.
```

```
DO 110 K=1,MAX
```

```
IF(SR(K).GT.XMAX)XMAX=SR(K)
```

```
110 CONTINUE
```

```
DO 120 K=1,MAX
```

```

SSN(K)=SSN(K)/XMAX
SSP(K)=SSP(K)/XMAX
SR(K)=SR(K)/XMAX
IF(SSN(K) .GT. SNBOT) SNBOT=SSN(K)
IF(SSP(K) .GT. SPTOP) SPTOP=SSP(K)
120 CONTINUE
C PLOT GRAPH
CALL GRAPH(WAV,SSN,SSP,SR,I)
RETURN
END

SUBROUTINE GRAPH(WAV,SN,SP,SR,I)
DIMENSION WAV(200),SN(200),SP(200),SR(200)
CALL CALPLT(1.5,.75,-3)
XPG=5.0
XDV=10.0
XTIC=.5
YPG=5.0
YDV=10.0
YTIC=.5
CALL ASCALE(WAV,XPG,I,1,XDV)
CALL ASCALE(SR,YPG,I,1,YDV)
CALL AXES(0.,0.,0.,XPG,0.0,WAV(I+2),-XTIC,XDV,
120HWAVELENGTH (MICRONS) ..14,-20)
CALL AXES(0.,0.,90.,YPG,0.0..2,-YTIC,YDV,
1 28HNORMALIZED SPECTRAL RESPONSE ..14,28)
SFX=1./WAV(I+2)
SFY=5.0
CALL CALPLT(WAV(1)*SFX,SN(1)*SFY,3)
DO 100 J=1,I
CALL CALPLT(WAV(J)*SFX,SN(J)*SFY,2)
100 CONTINUE
CALL CALPLT(WAV(1)*SFX,SP(1)*SFY,3)
DO 101 J=1,I
CALL CALPLT(WAV(J)*SFX,SP(J)*SFY,2)
101 CONTINUE
CALL CALPLT(WAV(1)*SFX,SR(1)*SFY,3)
DO 103 J=1,I
CALL CALPLT(WAV(J)*SFX,SR(J)*SFY,2)
103 CONTINUE
CALL CALPLT(0.,6.,-3)
RETURN
END

SUBROUTINE SHORT(S1P,S1N,E)
C
C
C
COMMON/BLK2/POW,LAMBDA,NA,ND,B4,SN,SP,SO,S1,RE,RS,RSH,A,B,H
COMMON/BLK4/XKKO,MUN,MUP,TAUN,TAUP,DN,DP,PHIO,NI,LN,LP,VBI
COMMON/BLK6/PI,PI2,Q,ZJ,T,TO,NIA1,NIA2,TNO,TPO,W,ALPHA
COMMON/BLK7/NEIGV,KB,KBTG,XGRAPH
C
REAL LAMBDA,NA,ND,MUN,MUP,NI,LN,LP,KB,KBTG,NIA1,NIA2
C

```



C CALCULATES THE SPECTRAL RESPONSE COMPONENTS

C CALCULATES DOUBLE SUMMATION OVER I,J

CALL ABSORP(E,ALP1)

ALPHA=ALP1

S1P=0 \$ S1N=0

DO 10 I=1,NEIGV

DO 20 J=1,NEIGV

CALL NUMBS(I,J,SNIJ,SPIJ)

S1P=S1P+SPIJ

S1N=S1N+SNIJ

20 CONTINUE

10 CONTINUE

RETURN

END

SUBROUTINE DCURRENT(IO)

C  
C  
C

COMMON/BLK2/POW,LAMBDA,NA,ND,B4,SN,SP,SO,S1,RE,RS,RSH,A,B,H

COMMON/BLK4/XKKO,MUN,MUP,TAUN,TAUP,DN,DP,PHIO,NI,LN,LP,VBI

COMMON/BLK5/ETAN(50),XIN(50),XIP(50),ETAP(50),XN(50),XP(50)

COMMON/BLK6/PI,PI2,Q,ZJ,T,TO,NIA1,NIA2,TNO,TPO,W,ALPHA

COMMON/BLK7/NEIGV,KB,KBTG,XGRAPH

C

REAL NNO,NPO,LAMBDA,NA,ND,MUN,MUP,NI,LN,LP,NIA1,NIA2

REAL KB,KBTG,IO,NN,NP

C

Y1(X,Z)=Z\*COSH(X)+SINH(X)

Y2(X,Z)=Z\*SINH(X)+COSH(X)

Y3(X,Z)=(Z+TANH(X))/(1+Z\*TANH(X))

C DOPING DENSITIES

PPO=NA

NNO=ND

NPO=NI\*NI/PPO

PNO=NI\*NI/NNO

SUM1=0 \$ SUM2=0

DO 10 I=1,NEIGV

DO 20 J=1,NEIGV

DEN2=(ETAP(J)/B)\*\*2 +(XIP(I)/A)\*\*2

GIJ2=LP\*LP/(1+LP\*LP\*DEN2)

GIJ=SQRT(GIJ2)

DEN3=(XIN(I)/A)\*\*2 +(ETAN(J)/B)\*\*2

SIJ2=LN\*LN/(1+LN\*LN\*DEN3)

SIJ=SQRT(SIJ2)

NP=SP\*GIJ/DP \$ NN=SN\*SIJ/DN

UJNNORM=A+(SO\*A\*A/DN)\*(COS(XIN(J))/XIN(J))\*\*2

VINNORM=B+(S1\*B\*B/DN)\*(COS(ETAN(I))/ETAN(I))\*\*2

F1=SIN(XIN(J)) \$ F2=SIN(ETAN(I))

HP=H-ZJ-W

F3=16\*A\*A\*B\*B\*Q\*DN\*NI\*NI/(NA\*SIJ)

F4=(F1/XIN(J))\*\*2 \$ F5=(F2/ETAN(I))\*\*2

F6=1/(UJNNORM\*VINNORM)

TERMN=F3\*F4\*F5\*F6\*Y3((HP/SIJ),NN)

UJPNORM=A+(SO\*A\*A/DP)\*(COS(XIP(J))/XIP(J))\*\*2

```

VIPNORM=B+(S1*B*B/DP)*(COS(ETAP(I))/ETAP(I))*2
F1=SIN(XIP(J)) $ F2= SIN(ETAP(I))
G3=16*A*A*B*B*Q*DP*NI*NI/(ND*GIJ)
G4=(F1/XIP(J))*2 $ G5=(F2/ETAP(I))*2
G6=1./(UJPNORM*VIPNORM)
TERMP=G3*G4*G5*G6*Y3((ZJ/GIJ),NP)
SUM1=SUM1+TERMN
SUM2=SUM2+TERMP
20 CONTINUE
10 CONTINUE
IO=SUM1+SUM2
RETURN
END

SUBROUTINE NUMBS(I,J,SNIJ,SPIJ)
C
C
C
COMMON/BLK2/POW,LAMBDA,NA,ND,B4,SN,SP,SO,S1,RE,RS,RSH,A,B,H
COMMON/BLK4/XKKO,MUN,MUP,TAUN,TAUP,DN,DP,PH10,NI,LN,LP,VBI
COMMON/BLK5/ETAN(50),XIN(50),XIP(50),ETAP(50),XN(50),XP(50)
COMMON/BLK6/PI,PI2,Q,ZJ,T,TO,NIA1,FI2,TNO,TPO,W,ALPHA
COMMON/BLK7/NEIGV,KB,KBTG,XGRAPH
C
REAL LAMBDA,NA,ND,MUN,MUP,NI,LN,LP,NIA1,NIA2,KB,KBTG
C *****
C
C
WJPNOR=.5*ZJ-.25*ZJ*SIN(2*XP(J))/XP(J)
DEN2=(ETAP(I)/B)*2 +(XP(J)/ZJ)*2
GIJ2=LP*LP/(1.+LP*LP*DEN2)
GIJ=SQRT(GIJ2)
VIPNOR=B+(SO*B*B/DP)*(COS(ETAP(I))/ETAP(I))*2
HP=H-ZJ-W
WJNNOR=.5*HP-.25*HP*SIN(2*XN(J))/XN(J)
VINNOR=B+(S1*B*B/DN)*(COS(ETAN(I))/ETAN(I))*2
DEN3=(XN(J)/HP)*2 +(ETAN(I)/B)*2
SIJ2=LN*LN/(1.+LN*LN*DEN3)
SIJ=SQRT(SIJ2)
XLAMJ=XP(J)/ZJ
SPI1=4*B*B*XLAMJ/WJPNOR
SPI2=ZJ*(1-COS(XP(J)))/XP(J)
SPI3=(SIN(ETAP(I))/ETAP(I))*2
CC=ALPHA*ALPHA*GIJ2-1
AA=A
AALP=ALPHA
DPP=DP
SSO=SO
DD=GIJ/CC
CALL INTEG(AA,AALP,GIJ,CC,DPP,SSO,SPI4)
SPIJ=ALPHA*SPI1*SPI2*SPI3*SPI4/(VIPNOR)
C *****
SNI1=4*B*B
XLAMJ=XN(J)/HP
SNI2=HP*(1-COS(XN(J)))/XN(J)

```

C-2

```

SNI3=(SIN(ETAN(I))/ETAN(I))*2
EE=ALPHA*ALPHA*SIJ2-1
SSO=S1
DPP=DN
SNI4=XLAMJ/WJNNOR
CALL INTEG(AA,AALP,SIJ,EE,DPP,SSO,SNI5)
SNIJ=ALPHA*SNI1*SNI2*SNI3*SNI4*SNI5/(VINNOR)
RETURN
END

```

```

SUBROUTINE INTEG(AA,AALP,GIJ,CC,DP,SO,SPI4)
ARG1=2*AA/GIJ
ARG2=2*AA*AALP
CALL EXPON(-ARG2,ARG3)
ARG4=1-ARG3 $ ARG5=1+ARG3
ARG6=GIJ**4
DP2=DP*DP
GIJ2=GIJ*GIJ
SO2=SO*SO
IF(AALP.LE.0)GO TO 200
A11=-2*SO*GIJ2/(AALP*DP)
A12=AALP*SO*ARG6/DP
A13=SO2*ARG6/(DP2)
A1=((A11+A12)*ARG4+A13*ARG5)/CC
C
CC=ALPHA*ALPHA*GIJ2-1
B11=-GIJ*(1+SO2*GIJ2/(DP2))/AALP
B12=AALP*(GIJ**3)
B13=SO*(GIJ**3)/DP
B1=((B11+B12)*ARG4+B13*ARG5)/CC
C11=-SO*AALP*ARG6/DP
C12=-SO2*ARG6/(DP2)
C1=(C11*ARG4+C12*ARG5)/CC
50 B=(1./GIJ)+(SO2*GIJ/(DP2))
A=2*SO/DP
R=TANH(ARG1)
IF(ARG1.GT.700) GO TO 100
SPI4=(A1+B1*R+C1/COSH(ARG1))/(A+B*R)
RETURN
100 SPI4=(A1+B1*R)/(A+B*R)
RETURN
200 CONTINUE
A11=-4*SO*GIJ2*AA/DP
A12=2*SO2*ARG6/DP2
A1=(A11+A12)/CC
B11=-GIJ2*(1+SO2*GIJ2/DP2)*2*AA
B12=SO*GIJ*GIJ2*2/DP
B1=(B11+B12)/CC
C1=-SO2*ARG6*2/(DP2*CC)
GO TO 50
END

```

```

FUNCTION FUN(X)
IF(X.LT.-230)GO TO 10
FUN=EXP(X)
RETURN
10 FUN=0
RETURN
END

SUBROUTINE IV(WAVE)
C
C CALCULATE CURRENT-VOLTAGE CURVE
C
C
COMMON/BLK2/POW,LAMBDA,NA,ND,B4,SN,SP,SO,S1,RE,RS,RSH,A,B,H
COMMON/BLK4/XKKO,MUN,MUP,TAUN,TAUP,DN,DP,PHIO,NI,LN,LP,VBI
COMMON/BLK5/ETAN(50),XIN(50),XIP(50),ETAP(50),XN(50),XP(50)
COMMON/BLK6/PI,PI2,Q,ZJ,T,TO,NIA1,NIA2,TNO,TPO,W,ALPHA
COMMON/BLK7/NEIGV,KB,KBTG,XGRAPH
COMMON/BLK8/VOC,PMAX,EFF,ISC
C
C
DIMENSION AMPS(100),VOLTS(100)
REAL IREC,IB,IO,ISC,I
REAL LAMBDA,NA,ND,LN,LP,MUP,MUN,NIA1,NIA2,KB,KBTG,NI
C CALCULATE IV CURVE
FFF=Q*PHIO*(1-RE)
E=1.2402/WAVE
ICOUNT=0 $ PMAX=-.5
DELVO=.0125
DELV=.025
V=-DELV
100 CONTINUE
ICOUNT=ICOUNT+1
V=V+DELV
CALL WIDTH(V)
C CALCULATE ISC (LIGHT CURRENT)
CALL SHORT(S1P,S1N,E)
YA1=FFF*S1P
YA2=FFF*S1N
ISC=YA1+YA2
C CALCULATE DARK CURRENT
CALL DCURRENT(IO)
IREC=4*A*B*Q*NI*W*PI2*2*SINH(V/(2*KBTG))
IREC=IREC/((VBI-V)/KBTG)
IREC=IREC/SQRT(TAUN*TAUP)
C SOLVE FOR I
U1=1+RS/RSH
U=.999
IB=ISC-IREC-V/RSH+IO
VOLTS(ICOUNT)=V*1000
110 CONTINUE
Z=(V+U*IB*RS)/KBTG
F=IB*U*U1-IB+IO*EXP(Z)
FP=IB*U1+IO*(RS*IB/KBTG)*EXP(Z)
U2=U-F/FP

```

```

        ERROR=ABS(U2-U)
        IF(ERROR.LT.1.0E-6) GO TO 120
        U=U2
        GO TO 110
120    I=U2*IB
        AMPS(ICOUNT)=I*1000
        WRITE(6,99)ISC,IO,IREC,V,YA1,YA2
99    FORMAT(1X,6E15.7)
        P=I*V
        IF(P.GT.PMAX)PMAX=P
        IF((I.LT.0).OR.(VBI.LT.(V+DELV)))GO TO 130
        IF(V.GT..85) DELV=DELVO
        GO TO 100
130    AMPS(ICOUNT)=0.
        PIN=POW*1000*2*B*H
        VOC=KBTG*ALOG(1.+(ISC-IREC)/IO)
        EFF=PMAX*100/PIN
        IF(ICOUNT .GT. 1) VOLTS(ICOUNT)=VOLTS(ICOUNT-1)+DELV/100.
        IF(ICOUNT .EQ. 1) VOLTS(ICOUNT)=VOC
        CALL GRAPHIV(VOLTS,AMPS,ICOUNT)
        CALL NFRAME
        RETURN
        END

```

```

SUBROUTINE GRAPHIV(X,Y,I)
DIMENSION X(100),Y(100)
COMMON/BLK7/NEIGV,KB,KBTG,XGRAPH
XPG=5.0
XDV=10.
XTIC=.5
YPG=5.0
YDV=10.0
YTIC=.5
CALL ASCALE(X,XPG,I,1,XDV)
CALL ASCALE(Y,YPG,I,1,YDV)
CALL AXES(0.,0.,0.,XPG,0.0,X(I+2),-XTIC,XDV,
1 20HVOLTAGE (MILLIVOLTS) ,.14,-20)
CALL AXES(0.,0.,90.,YPG,0.0,Y(I+2),-YTIC,YDV,
1 19HCURRENT (MILLIAMPS) ,.14,19)
SFX=1./X(I+2)
SFY=1./Y(I+2)
CALL CALPLT(X(1)*SFX,Y(1)*SFY,3)
DO 100 J=1,I
CALL CALPLT(X(J)*SFX,Y(J)*SFY,2)
100 CONTINUE
CALL CALPLT(0.,6.,-3)
CALL CHARACT(0.0,0.0,.1,5HGRAPH,0.0,5)
CALL WHERE(XX,YY,IXX)
CALL NUMBER(XX+.07,0.,.1,XGRAPH,0.0,-1)
CALL NFRAME
RETURN
END

```




FIGURE D1. Representative output from the program "VSC3D" illustrating the spectral response, the current-voltage relation and contour plots of the current density in the planes  $Z=Z_j$  and  $Z=Z_j+W$ .




FIGURE D1. (c) Contour plot of current density in plane  $Z_j$ .  $J_p(x,y) = \text{constant}$ .




FIGURE D1. (d) Contour plot of current density in plane  $Z_j+W$ .  
 $J_n(x,y) = \text{constant}$ .